

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: UZIN PE 460 Comp. A

1.2 Relevant identified uses of the substance or mixture and uses advised against No special requirements.

Sector of Use

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
For professional use only.

Product category PC1 Adhesives, sealants

Application of the substance / the mixture 2 Component Epoxy DPM

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Producer:

UZIN UTZ SE

Dieselstraße 3

D-89079 Ulm

Phone.: +49 (0)731 4097-0

Fax: +49 (0)731 4097-110

Supplier in the UK:

Uzin Utz UK Ltd.

Unit 2, Mitchell Court

Central Park, Rugby

Warwickshire, CV23 0UY,

Telephone +44 (0) 1788 530 080

Fax +44 (0) 1788 536508

Email info@uk.uzin-utz.com

Further information obtainable from:

Product safety department

email: msds.info@uzin-utz.com

1.4 Emergency telephone number:

Medical emergencies (GIZ-Nord Poisons Center): +49 551 19240

Transportation emergencies: +49 621 60 43 333

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Repr. 1A

H360F May damage fertility.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. A

(Contd. of page 1)

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS07 GHS08 GHS09

Signal word Danger

Hazard-determining components of labelling:

Bisphenol-A-epoxy resin (average molecular weight ≤ 700)

alkyl C12-C14 glycidyl ether

Bisphenol-F-epoxy resin (average molecular weight ≤ 700)

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

Additional information: Restricted to professional users.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: 2 Component Epoxy DPM

Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5 Reg.nr.: 01-2119456619-26	Bisphenol-A-epoxy resin (average molecular weight ≤ 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	25-50%
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40	Bisphenol-F-epoxy resin (average molecular weight ≤ 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 68609-97-2 EINECS: 271-846-8 Reg.nr.: 01-2119485289-22	alkyl C12-C14 glycidyl ether ⚠ Repr. 1A, H360F; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	10-<20%

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. A

(Contd. of page 2)

CAS: 17557-23-2

EINECS: 241-536-7

Reg.nr.: 01-2120759332-55

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane

 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317;
Aquatic Chronic 3, H412

3-<5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed** Allergic reactions

· **4.3 Indication of any immediate medical attention and special treatment needed**

Also observe the safety data sheet of component B.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents:**

CO₂ powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Wear suitable protective clothing, gloves and eye/face protection.

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Prevent formation of aerosols.

Wash hands before breaks and at the end of work.

(Contd. on page 4)

GB

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. A

(Contd. of page 3)

- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Protect from humidity and water.
Protect from frost.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing
Avoid contact with the eyes and skin.
Wear suitable protective clothing, gloves and eye/face protection.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Respiratory protection:** Not necessary. Ensure that room is well-ventilated during processing.
- **Hand protection**



Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability (EN 374)

- **Material of gloves**
Butyl rubber, BR
Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.5 mm
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
At least 480 minutes.
- **Eye/face protection**



Tightly sealed goggles or face protection (EN 166)

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Fluid
- **Colour:** Blue
- **Odour:** Weak, characteristic
- **Odour threshold:** Not determined.

(Contd. on page 5)

Safety data sheet

according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. A

(Contd. of page 4)

· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	>100 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	400 mPas
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.1 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. A

(Contd. of page 5)

10.3 Possibility of hazardous reactions

May produce violent reactions with bases and numerous organic substances including alcohols and amines. Exothermic polymerisation.

Caution: Epoxy material can become extremely hot and may foam up in the container approx. 15-30 min after mixing. Therefore, mix only in metal containers, then apply immediately. Do not leave unattended after mixing. Remove container with mixed product residues to outdoors to allow to react.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Irritant gases/vapours

At elevated temperatures hazardous decomposition products such as carbon dioxide, carbon monoxide, smoke or nitric oxides may be evolved.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

Primary irritant effect:

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity May damage fertility.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 1675-54-3 Bisphenol-A-epoxy resin (average molecular weight ≤ 700)

EC50/48h 1.8 mg/l (*Daphnia magna*)

EC50/72h 11 mg/l (*Scenedesmus capricornutum*)

LC50/96h 2 mg/l (*Piscis*)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Toxic for fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Toxic for aquatic organisms

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. A

(Contd. of page 6)

Also poisonous for fish and plankton in water bodies.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

The product contains materials that are harmful to the environment.

Do not allow product to reach ground water, water course or sewage system.

Mix both product components, allow to harden, then dispose of as construction waste.

Disposal should be in accordance with local, state or national legislation.

· Uncleaned packaging:

· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA

UN3082

· 14.2 UN proper shipping name

· ADR

3082 ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S. (Epoxy resins)

· IMDG


ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S. (Epoxy resins), MARINE POLLUTANT

· IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S. (Epoxy resins)

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



· Class

9 Miscellaneous dangerous substances and articles.

· Label

9

· 14.4 Packing group

· ADR, IMDG, IATA

III

· 14.5 Environmental hazards:

· Marine pollutant:

Yes

Symbol (fish and tree)

· Special marking (ADR):

Symbol (fish and tree)

· Special marking (IATA):

Symbol (fish and tree)

· 14.6 Special precautions for user

Warning: Miscellaneous dangerous substances and
articles.

· Hazard identification number (Kemler code):

90

· EMS Number:

F-A,S-F

· Stowage Category

A

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

Not dangerous according to the above specifications.

· ADR

· Limited quantities (LQ)

5L

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. A

(Contd. of page 7)

· Transport category	3
· Tunnel restriction code	(-)
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESINS), 9, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

- **Regulated explosives precursors**

None of the ingredients is listed.

- **Regulated poisons**

None of the ingredients is listed.

- **Reportable explosives precursors**

None of the ingredients is listed.

- **Reportable poisons**

None of the ingredients is listed.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category E2** Hazardous to the Aquatic Environment

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

- **Relevant phrases**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

- **Recommended restriction of use** For professional use only.

- **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- **Department issuing SDS:** Product safety department

- **Contact:**

Product Safety Department

Phone: +49 (0)731 4097 207

E-mail: msds.info@uzin-utz.com

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 9)

Safety data sheet
according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. A

(Contd. of page 8)

*ICAO: International Civil Aviation Organisation**ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonised System of Classification and Labelling of Chemicals**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Skin Sens. 1: Skin sensitisation – Category 1**Repr. 1A: Reproductive toxicity – Category 1A**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3**** Data compared to the previous version altered.**

GB

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: UZIN PE 460 Comp. B

1.2 Relevant identified uses of the substance or mixture and uses advised against No special requirements.

Sector of Use

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
For professional use only.

Product category PC1 Adhesives, sealants

Application of the substance / the mixture 2 Component Epoxy DPM

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Producer:

UZIN UTZ SE

Dieselstraße 3

D-89079 Ulm

Phone.: +49 (0)731 4097-0

Fax: +49 (0)731 4097-110

Supplier in the UK:

Uzin Utz UK Ltd.

Unit 2, Mitchell Court

Central Park, Rugby

Warwickshire, CV23 0UY,

Telephone +44 (0) 1788 530 080

Fax +44 (0) 1788 536508

Email info@uk.uzin-utz.com

Further information obtainable from:

Product safety department

email: msds.info@uzin-utz.com

1.4 Emergency telephone number:

Medical emergencies (GIZ-Nord Poisons Center): +49 551 19240

Transportation emergencies: +49 621 60 43 333

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B

H314 Causes severe skin burns and eye damage.

Eye Dam. 1

H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Sens. 1

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. B

(Contd. of page 1)

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05 GHS07 GHS09

Signal word Danger

Hazard-determining components of labelling:

m-phenylenebis(methylamine)

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Phenol, styrenated

Polyoxypropylenediamine

2,4,6-tris(dimethylaminomethyl)phenol

Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

Additional information: Restricted to professional users.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Determination of endocrine-disrupting properties

CAS: 61788-44-1 Phenol, styrenated

List II

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: 2 Component Epoxy DPM

Dangerous components:

CAS: 61788-44-1

EC number: 701-443-9

Reg.nr.: 01-2119980970-27

Phenol, styrenated

⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1A, H317

25-50%

(Contd. on page 3)

GB

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. B

(Contd. of page 2)

CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50	<i>m</i> -phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-<20%
CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	3-aminomethyl-3,5,5-trimethylcyclohexylamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	10-<20%
CAS: 9046-10-0 Reg.nr.: 01-2119557899-12	Polyoxypropylenediamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 3, H412	10-<20%
CAS: 112-53-8 EINECS: 203-982-0 Reg.nr.: 01-2119485976-15	Lauryl alcohol ⚠ Aquatic Chronic 2, H411; ⚠ Eye Irrit. 2, H319	5-<10%
CAS: 90-72-2 EINECS: 202-013-9 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Skin Sens. 1B, H317	3-<5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** Allergic reactions
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂ powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.

(Contd. on page 4)

GB

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. B

(Contd. of page 3)

- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Wear suitable protective clothing, gloves and eye/face protection.
Immediately remove all soiled and contaminated clothing
Avoid contact with the eyes and skin.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Protect from frost.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing
Avoid contact with the eyes and skin.
Wear suitable protective clothing, gloves and eye/face protection.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Respiratory protection:** Not necessary. Ensure that room is well-ventilated during processing.
- **Hand protection**



Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability (EN 374)

- **Material of gloves**
Butyl rubber, BR
Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.5 mm
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
At least 480 minutes.

(Contd. on page 5)

GB

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. B

(Contd. of page 4)

· Eye/face protection



Tightly sealed goggles or face protection (EN 166)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state	Fluid
· Colour:	Yellowish
· Odour:	Amine-like
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	>200 °C
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	>100 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	650 mPas
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void

(Contd. on page 6)

GB

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. B

(Contd. of page 5)

· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Strong exothermic reaction with acids.
Caution: Epoxy material can become extremely hot and may foam up in the container approx. 15-30 min after mixing. Therefore, mix only in metal containers, then apply immediately. Do not leave unattended after mixing. Remove container with mixed product residues to outdoors to allow to react.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Corrosive gases/vapours
At elevated temperatures hazardous decomposition products such as carbon dioxide, carbon monoxide, smoke or nitric oxids may be evolved.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

CAS: 1477-55-0 m-phenylenebis(methylamine)

Oral	LD50	930 mg/kg (rat)
Dermal	LD50	3,100 mg/kg (rabbit)
Inhalative	LC50/4 h	1.34 mg/l (rat)

CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	LD50	1,030 mg/kg (ATE) 1,030 mg/kg (rat) (OECD 401)
Dermal	LD50	1,840 mg/kg (rabbit)
Inhalative	LC50/4 h	>5 mg/l (rat)

CAS: 112-53-8 Lauryl alcohol

Oral	LD50	12,800 mg/kg (rat)
------	------	--------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. B

(Contd. of page 6)

· 11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 61788-44-1 Phenol, styrenated

List II

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 112-53-8 Lauryl alcohol

LC50/96h >100 mg/l (*Leuciscus idus*)

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Remark: Toxic for fish

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system.

Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

The product contains materials that are harmful to the environment.

Do not allow product to reach ground water, water course or sewage system.

Mix both product components, allow to harden, then dispose of as construction waste.

Disposal should be in accordance with local, state or national legislation.

· Uncleaned packaging:

· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA

UN2735

· 14.2 UN proper shipping name

· ADR

2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(Polyoxypropylenediamine, m-phenylenebis(methylamine)), ENVIRONMENTALLY
HAZARDOUS

· IMDG

POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(Polyoxypropylenediamine, m-phenylenebis(methylamine)), MARINE POLLUTANT

(Contd. on page 8)

Safety data sheet

according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. B

(Contd. of page 7)

· IATA	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylenediamine, m-phenylenebis(methylamine))
· 14.3 Transport hazard class(es)	
· ADR, IMDG	
	
· Class	8 Corrosive substances.
· Label	8
· IATA	
	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: Phenol, styrenated
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Hazard identification number (Kemler code):	80
· EMS Number:	F-A,S-B
· Segregation groups	(SGG18) Alkalis
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	E
· UN "Model Regulation":	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (POLYOXYPROPYLENEDIAMINE, M-PHENYLENEBIS(METHYLAMINE)), 8, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

(Contd. on page 9)

GB

Safety data sheet according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. B

(Contd. of page 8)

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU**· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category E2** Hazardous to the Aquatic Environment**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t**· REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 75**· 15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Recommended restriction of use For professional use only.**· Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: Product safety department**· Contact:**

Product Safety Department

Phone: +49 (0)731 4097 207

E-mail: msds.info@uzin-utz.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)

Safety data sheet
according to UK REACH

Printing date 10.10.2024

Version No. 10

Revision: 10.10.2024

Trade name: UZIN PE 460 Comp. B

(Contd. of page 9)

*ATE: Acute toxicity estimate values**Acute Tox. 4: Acute toxicity – Category 4**Skin Corr. 1B: Skin corrosion/irritation – Category 1B**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Skin Sens. 1: Skin sensitisation – Category 1**Skin Sens. 1A: Skin sensitisation – Category 1A**Skin Sens. 1B: Skin sensitisation – Category 1B**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3**** Data compared to the previous version altered.**

GB