



1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product:** Tarkett LinoWall xf²™ homogeneous linoleum wallcovering, single layer on jute backing with xf²™ surface protection.
- 1.2. **Manufacturer:**
Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkett.com

1.3. Proprietary Product Description:

- 1.3.1. **Construction:** Tarkett LinoWall xf²™ consists of an homogeneous layer of oxidized linseed oil and natural resins mixed with wood or cork flour, limestone and pigments affixed to a jute backing. The marbled pattern extends evenly throughout the total thickness. Surface has xf²™ treatment for surface protection that is resistant to stains.

1.3.2. Styles:

LinoWall

- Thickness: 2mm (0.080")
- Surface Protection: xf²™
- Colors: 6 available
- Weight/yd² (/m²): 5.35 lbs (2.9 kg)
- Width: 6' 6" (2 m) & 3' 3.3" (1 m) nominal
- Length: 46' – 59' (14 - 18 m)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Flexibility** (ASTM F 137): Passes
- 2.2. **Chemical Resistance** (ASTM F925): Passes
- 2.3. **Static Load Limit** (ASTM F970): ≤ 0.005" residual indentation (150 psi load)
- 2.4. **Flame Spread / Smoke** (ASTM E84, Flame Spread/Smoke): Class B, ≤ 450
- 2.5. **Flame Spread / Smoke (Canada) CAN/ULC S102.2:** ≤ 300 FS/300 Smoke
- 2.6. **CAN/ULC S102.2:** FSR 30 / SDC 65

3. INSTALLATION

- 3.1. See LinoWall xf²™ sheet installation instructions for complete details.
- 3.2. **Adhesives:**
- **Tarkett 965**
Coverage:
Porous Substrate: 125-150 sq. ft./gal.
Non-porous Substrate: 125-150 sq. ft./gal.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to LinoWall xf² maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com

Contact Technical support at (800)-899-8916 or Email: Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 10-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com
www.tarkett.com