

MX PLUS

Facility Solutions



KEY BENEFITS

- Tool-less Components – ¼ turn connections; double O-ring design
- Snap-on Cover
- Large, easy-to-use paddles with locking catch
- Engines slide into snap-guides for easy service and re-configuration
- Easily serviced diaphragm with ¼ turn cover
- Compact footprint
- Both Aire-Gap and Flex-Gap backflow devices to meet national and local codes

MX Plus dispensers are field serviceable and highly flexible proportioners, offering configurations that allow for up to eight products and two flow rates with a choice of Flex-Gap or Aire-Gap back flow prevention.

Dispensing is activated by pushing smooth-operating large buttons that can be locked into the on position for hands-free dispensing. Simply engage the catch to keep the flow open then press the button again and release to stop the flow. Spray bottles can be filled using one hand by pushing the bottle against the actuator bar.

One-engine and two-engine cabinets are available and may be equipped with either a single product engine or a dial 4 selector engine for each button. Designed for flexibility, each MX Plus can be reconfigured several ways in the field without tools.

The water inlet can be quickly swapped from one side to the other with a simple quarter turn of the water quick connect. Single product engines can be replaced with a dial 4 selector engine in a few simple steps: Slide the engine assembly out of the snap guides. Remove the single product engine with a quarter turn. Replace with a dial-4 assembly. Pop out the blanking plate from the cover to reveal a round hole for the dial selector.

Connect your four chemical supply lines and replace the snap-on cover.



Trusted solutions. – Simple. Clean. Connected.

TECHNICAL DATA

Flow Rates

1 GPM (3.8 LPM) bottle fill
4 GPM (15.2 LPM) bucket fill

Back Flow Prevention

Flex-Gap or Aire-Gap

Max. Water Temperature

140° F (60° C)

Optimal Min. Pressure

30 PSI (2 bar)

Optimal Max. Pressure

60 PSI (4 bar)

Certifications









A.S.S.E.
I.A.P.M.O. (UPC)

Features

- One hand bottle fill
- Large, ergonomic buttons
- Easy slide lock and release catch for buttons
- Built-in Flow-Control technology for accurate dilution in varying water pressures
- Snap On/Off cover
- Included tip kit and poly tubing, foot valves and product labels
- Optional compression, John Guest, or barb fittings available



VALVE ASSEMBLY

Model Numbers		Description
NOTE: Model numbers ending with -FE come with BSP threads. Models ending with -F and marked with  are available with BSP threads. To order, change the suffix from “F” to “FE”.		
FLEX-GAP	AIRE-GAP	
7866101-F 	7866101-A	MX Plus Proportioner, 1 Product Bottle Fill, 1 GPM
7866104-F 	7866104-A	MX Plus Proportioner, 1 Product Bucket Fill, 4 GPM
7866201-F 	7866201-A	MX Plus Proportioner, 2-Product Bucket Fill, 4 GPM
7866205-F 	7866205-A	MX Plus Proportioner, 2-Product, 1 & 4 GPM
7866401-F 	7866401-A	MX Plus Proportioner, 4-Product Bottle Fill, 1 GPM
7866404-F 	7866404-A	MX Plus Proportioner, 4-Product Bucket Fill, 4 GPM
7866501-F 	7866501-A	MX Plus Proportioner, 5-Product 1 GPM & 4 GPM
7866802-F	7866802-A	MX Plus Proportioner, 8-Product 1 GPM & 4 GPM

OPTIONS

7114100	Faucet Plus Kit Knight Chem Proportioner
0800394	Hose, Hi-Pressure, 6 FT Length EPDM, M/F
0800402	Hose Wye, Brass with Ball Valve Shut Offs

ACCESSORIES

Model #	Description
6400006	Metering Tip Wrench
7225918-4	Wire Rack, 4 Product w/Top and MTG Hardware
7366041-25	Quick Water Connection, Hose Swivel-US, 25 each
7366040-25	Quick Water Connection, Hose Swivel-UK, 25 each
0600873-10	Quick Water Connection, 3/8" John Guest Elbow, 10 each
0600874-10	Quick Water Connection, 3/8" Compression, 10 each
7366035	Quick Connect, 1/2" Barb, 25 each
7366049	Quick Connect, Valve Connector (join dispenser together)

