

*Rely on us.*<sup>SM</sup>



# Hydrofast® GS 312 CtP

Designed and tuned to the requirements of and implementation on sensitive CtP plates

## Fountain solution for all Sheetfed presses

### Product Features

- Hydrofast® GS 312 CtP is suitable for use on all sheetfed presses and dampening systems.
- Special additives reduce precipitation of calcium compounds on ink rollers and thus minimise roller stripping.
- Hydrophilic additives allow quick start up after stopping and makes coating with gum unnecessary.

### Advantages of Hydrofast® GS 312 CtP

- Contains surfactants for fast adjustment of the ink/water balance.
- Allows a short damping adjustment leading to brilliant prints.
- Achieves brilliant prints with a low water supply.
- Typical IPA levels 8-10%.

**FlintGroup**

# Hydrofast® GS 312 CtP

Features	Advantages	Benefits
<ul style="list-style-type: none"><li>• CtP safe.</li></ul>	<ul style="list-style-type: none"><li>• High plate lifetime.</li></ul>	<ul style="list-style-type: none"><li>• Reduced costs.</li><li>• High productivity.</li></ul>
<ul style="list-style-type: none"><li>• Short dampening level</li></ul>	<ul style="list-style-type: none"><li>• Brilliant print results</li><li>• Enhanced ink drying.</li></ul>	<ul style="list-style-type: none"><li>• High print quality</li><li>• High productivity</li><li>• Fast subsequent processing</li></ul>
<ul style="list-style-type: none"><li>• Calcium friendly.</li></ul>	<ul style="list-style-type: none"><li>• No precipitation on rollers.</li></ul>	<ul style="list-style-type: none"><li>• Less deglazing maintenance.</li></ul>
<ul style="list-style-type: none"><li>• OEM approved.</li></ul>	<ul style="list-style-type: none"><li>• Corrosion inhibited.</li></ul>	<ul style="list-style-type: none"><li>• Press protection.</li></ul>

<b>Product code</b>	KT10-012G-#### (final 4 digits relate to pack size).
<b>Pack sizes</b>	10kg (FJF9), 20kg (FJH5) and 200kg (FJN1).
<b>Recommended dosage</b>	Between 2% and 3%, depending on local water conditions.
<b>IPA</b>	Between 8% and 10%.
<b>pH value</b>	4.8 – 5.3 depending on water quality and dosage.
<b>Density</b>	1.05 (±0.02) kg/l.
<b>Notes</b>	When preparing the dampening solution, first add the dampening solution additive to the water and then if necessary add alcohol, otherwise incompatibility may occur.
<b>Approvals</b>	OEM approved (Heidelberg, KBA and manroland Sheetfed presses) in accordance with Fogra corrosion and elastomer swell testing criteria.

## More products. Streamlined access. Greater results.

Flint Group's Print Media division offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

### **Inks and Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.**

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

**You are welcome to contact us for further information.**

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability.

Product names followed by ® are trademarks registered by Flint Group Incorporated.

**Print Media Europe**  
Varn House, Brinell Drive,  
Northbank Industrial Park, Irlam,  
Greater Manchester, M44 5BL, UK.

**T +44 (0)161 775 5412**  
**F +44 (0)161 775 5415**  
**printmedia.eu@flintgrp.com**  
**www.flintgrp.com**