

TECHNICAL DATA SHEET

Varn® Ecolo-Clean 369

KV35-020

Description:

Varn® Ecolo-Clean™ 369 wash outperforms competitive products in the 30% VOC and higher VOC categories. Its proprietary formula cuts and lifts ink from contact surfaces, significantly limiting residue on blankets and rollers and minimizing blanket swelling. With its deep-clean, ample roller lubrication and improved ink transfer, this wash makes cleaning easier, better for your press equipment and more eco-friendly. Designed to clean conventional inks only.

Application:

- Avoid freezing and excessive heat. Allow product to reach room temperature prior to use. For auto-wash systems, do not dilute. For manual cleaning, the product can be used undiluted or diluted. To dilute, mix 2 parts of wash with up to 1 part of water.

Key Features:

- Low VOCs.
- Cuts and lifts ink instead of diluting and smearing.
- Limits restarts and waste by maintaining a hydrophilic dampening system.
- Low residue.
- Deep-cleaning power on blankets and rollers keeps consumables performing optimally.
- Extends roller life.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 20/07/2026

TECHNICAL DATA SHEET

Varn® Ecolo-Clean 369

KV35-020

Limitations:

- Not suitable for use with UV inks.

The final product/packaging structure and complete packaging must be tested and approved according to the intended application by the printer/packer. If your application covers any of the above, or other non-standard applications, please consult your local Flint Group technical support for guidance.

Storage:

- The product should be processed within 12 months after production date.
- To prolong the shelf life, we recommend storing the product in its original, un-opened packaging at room temperature (68 -78 °F), as correct storage conditions are essential.

Quality / Environment / Health & Safety

Flint Group maintains a comprehensive Management System that integrates quality, environment, health & safety. Our production and quality control processes meet high industry standards, ensuring product safety and reliability. When used as intended, our products are safe and pose no hazards under normal conditions. For more details, refer to the Safety Data Sheet.

Handling precautions – skin sensitization

Ensure the use of proper protective equipment when handling chemicals. For detailed guidance, refer to the Safety Data Sheet and consult with your PPE (Personal Protective Equipment) provider.

Additional Information

Please contact your local Flint Group Customer/Technical Service if further information is required.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 20/07/2026