



*Rely on us.*SM

Novacoat® 8855 BIO matt varnish

Matt varnish based on BIO-binders for perfecting

K+E® Novacoat® oil-based overprint varnishes for sheetfed offset

Product features

- Novacoat® 8855 BIO is a matt varnish based on renewable raw materials, which is especially suited for the use in perfecting presses and offers excellent rub protection.
- The matt varnish is ideally suited for perfecting presses and well suited for straight-line printing.
- Novacoat® 8855 BIO is particularly well suited for wet on wet applications and well suited for wet on dry applications.
- Novacoat® 8855 BIO can be mixed with the silk matt varnish Novacoat® 8833 BIO and the high gloss varnish Novacoat® 8844 BIO to achieve a variety of gloss and/or matt effects.

Advantages of Novacoat® 8855 BIO matt varnish

- Especially suited for the use in perfecting presses.
- Excellent rub protection.
- Very well suited for wet on wet and well suited for wet on dry applications.
- Fastest oxidative drying.
- Suitable for further processing in laser printers.
- Ideal for coated and uncoated paper and board.



FlintGroup

Novacoat® 8855 BIO matt varnish



Printing properties						
Gloss	Matt effect	Wet on Wet suitability	Wet on Dry suitability	Setting	Rub protection	Suitability for Perfecting
-	6	7	5	5	6	6
1 = Characteristic weakly expressed 7 = Characteristic strongly expressed						
<i>The assessment of the varnish properties was made under standardised printing conditions. In individual cases, under special conditions, as in printing with very thick layers of varnish, the classification of certain properties may be different.</i>						

Novacoat® 8855 BIO matt varnish

Drying properties

Oxidative drying.

Substrates

Coated and uncoated paper and board.

Remarks

Printing inks varnished with an oil-based overprint varnished don't need any specific fastness properties.

Optimal application quantity: 1.5 – 1.8 g/m²

If the quantity remains within this range, optimal rub protection and matt effect can be achieved.

Exceptions

Don't use Novacoat® 8855 BIO on food packaging without functional barrier.

More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Flint CPS Inks Germany GmbH
Commercial, Publication & Sheetfed Inks
Sieglestrasse 25
70469 Stuttgart, Germany

T +49 711 98 16-0
F +49 711 98 16-700
sheetfed@flintgrp.com
www.flintgrp.com

Product names followed by ® are trademarks registered by Flint Group (represented by Flint CPS Inks Holdings LLC or Flint CPS Inks Germany GmbH).