

TECHNICAL DATA SHEET

Varn® Apollo 901 KS15-001



- Description:** Varn® Apollo 901 is designed with built-in antistatic properties and improved marking protection for SNC, SCA, SCB, and lightweight coated stocks. This allows operators to control delivery and stacking of folded product at press speeds up to 3,000 fpm.
- Application:**
- Start at 4 ounces per gallon of water to prevent streaking, marking and static problems. Add product at one ounce per gallon for more difficult marking and static problems.
- Key Features:**
- Provides anti-static protection along with silicone lubrication.
 - Allows printers to exceed performance metrics of speed, quality, and waste.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 13/08/2026

TECHNICAL DATA SHEET

Varn® Apollo 901

KS15-001



Limitations:

- Not suitable for Goss' post-oven Ecocool® web moistening system.

The final product/packaging structure and complete packaging must be tested and approved according to the intended application by the printer/packer. If your application covers any of the above, or other non-standard applications, please consult your local Flint Group technical support for guidance.

Storage:

- The product should be processed within 12 months after production date.
- To prolong the shelf life, we recommend storing the product in its original, un-opened packaging at room temperature (68 -78 °F), as correct storage conditions are essential.

Quality / Environment / Health & Safety

Flint Group maintains a comprehensive Management System that integrates quality, environment, health & safety. Our production and quality control processes meet high industry standards, ensuring product safety and reliability. When used as intended, our products are safe and pose no hazards under normal conditions. For more details, refer to the Safety Data Sheet.

Handling precautions – skin sensitization

Ensure the use of proper protective equipment when handling chemicals. For detailed guidance, refer to the Safety Data Sheet and consult with your PPE (Personal Protective Equipment) provider.

Additional Information

Please contact your local Flint Group Customer/Technical Service if further information is required.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 13/08/2026