

TECHNICAL DATA SHEET

Varn® SUPREME CERT 762 KT25-017



- Description:** Varn® Supreme CERT 762 fount is a general purpose OEM approved sheetfed fountain concentrate formulated for use with conventional and UV/LED inks. This OEM approved fountain solution is compatible with all press parts, including metal, rubber and plastic. Varn® Supreme CERT 762 fount is corrosion-resistant and minimizes plastic swell while providing excellent print performance.
- Application:**
- Recommended dosage: 4.5-6.5 ounces per gallon of water. For best results, start with a clean dampening system. Conductivity per ounce above water is 185 micromhos.
- Key Features:**
- Low odor
 - Reduces ink feedback into the water rollers and recirculation tanks
 - Reduces piling
 - Offers improved start-ups compared with competing fountain solutions in this category
- Certifications:**
- OEM approved (Heidelberg, KBA and manroland Sheetfed presses, manroland Goss newspaper presses and commercial presses) in accordance with Fogra corrosion and elastomer swell testing criteria.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 11/08/2026

TECHNICAL DATA SHEET

Varn® SUPREME CERT 762 KT25-017

**Storage:**

- The product should be processed within 12 months after production date.
- To prolong the shelf life, we recommend storing the product in its original, un-opened packaging at room temperature (68 -78 °F), as correct storage conditions are essential.

Quality / Environment / Health & Safety

Flint Group maintains a comprehensive Management System that integrates quality, environment, health & safety. Our production and quality control processes meet high industry standards, ensuring product safety and reliability. When used as intended, our products are safe and pose no hazards under normal conditions. For more details, refer to the Safety Data Sheet.

Handling precautions – skin sensitization

Ensure the use of proper protective equipment when handling chemicals. For detailed guidance, refer to the Safety Data Sheet and consult with your PPE (Personal Protective Equipment) provider.

Additional Information

Please contact your local Flint Group Customer/Technical Service if further information is required.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 11/08/2026