

Novaboard® C 1090 RACE BIO

The fast drying, high rub resistant, BIO process series

K+E® standard process inks for sheetfed offset

Product Features

- Novaboard® C 1090 RACE BIO is a colour-intense, very rub-resistant process ink series, based on renewable raw materials. Fast setting with very fast oxidative drying properties.
- · It is optimally suited for straight-line printing on all multi-colour printing presses as well as perfecting presses.
- Suitable for most diverse substrates, Novaboard® C 1090 RACE BIO is also ideal for picking sensitive papers and provides maximum substrate choice flexibility.
- Furthermore, Novaboard® C 1090 RACE BIO has outstanding process stability and an excellent ink water balance.

Advantages of Novaboard® C 1090 RACE BIO

- Highest rub resistance.
- Very well suited for all kind of substrates especially for picking sensitive papers.
- Fastest oxidative drying.
- Excellent printability also on perfecting presses.
- Newest binder technology with optimised ink-water stability.
- Very fast setting.
- Very high gloss.
- High process stability.





Novaboard® C 1090 RACE BIO

K+E	Fastness properties					Printing properties								
	Light fastness	Alcohol	Solvent mixture	Alkali	Hot-calendering	Dot gain	Gloss	Setting	Oxidative drying	Rub resistance	Rapid further processing	Suitability for gloss	. 3	
Novaboard® C 1090						6	6	5	6	7	6	7	7	7
Novaboard® 1 C 1090 RACE BIO Yellow	5	+	+	+	+	1 = Characteristic weakly expressed 7 = Characteristic strongly expressed The assessment of the colour properties was								
Novaboard® 2 C 1090 RACE BIO Magenta	5	+	+	-	+									
Novaboard® 4 C 1090 RACE BIO Cyan	8	+	+	+	+	made under standardised printing conditions. In individual cases, under special conditions,								
Novaboard® 1090 RACE BIO Black, fast blue-toned	8	+	+	+	+	as in printing with very high ink densities, the classification of certain properties may be different.								
	Light fastness properties according to ISO 12040: from 1 (low) to 8 (high)													
	Fastness properties according to ISO 2836: + = Resistance provided - = Resistance not provided													

Drying properties Partly duct-fresh.

Substrates Optimally suited for matt, gloss coated papers as well as uncoated papers and board.

Remarks Due to its partly duct-fresh setting, Novaboard® C 1090 RACE BIO provides an excellent

compromise between conventional duct-fresh and oxidative drying.

Novaboard® C 1090 RACE BIO has high process stability which allows stable production printing and this ensures top quality and maximum economic efficiency at the same time. Further, this series shows very good suitability for reduced alcohol printing. Suited for print

corresponding to ISO 12647-2.

Exceptions Not for use on food packaging without functional barrier.

More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.