

TECHNICAL DATA SHEET

Varn® Enviroflex UV Wash KV10-OCT



Description:	A low hazard flexographic anilox roller and ink metering system cleaner which incorporates water miscible characteristics for the effective removal of glaze and is especially designed for use with UV inks for UV narrow web applications.
Application:	• ROLLERS: • Use Varn® Enviroflex UV Wash undiluted. • Apply to a damped wash up cloth. • INK METERING SYSTEM: • Use Varn® Enviroflex UV Wash undiluted. • Apply to a damped wash up cloth.
Key Features:	• Specially formulated for UV inks. • Water miscible. • Environmentally friendly and fully biodegradable. • High flashpoint (80°C) AIII. • Low odour.
Certifications:	• ISEGA certified for safe use in the printing process of food packaging materials.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 09/05/2026

TECHNICAL DATA SHEET

Varn® Enviroflex UV Wash KV10-OCT

**Limitations:**

- Not suitable for use with conventional oil based inks.

The final product/packaging structure and complete packaging must be tested and approved according to the intended application by the printer/packer. If your application covers any of the above, or other non-standard applications, please consult your local Flint Group technical support for guidance.

Storage:

- The products should be processed within 24 months after production date.
- Once opened the products should be processed within 12 months.
- To prolong the shelf life of the wash, we recommend storing the product in its original, un-opened packaging at room temperature (20 - 25°C), as correct storage conditions are essential.

Quality / Environment / Health & Safety

Flint Group maintains a comprehensive Management System that integrates quality, environment, health & safety. Our production and quality control processes meet high industry standards, ensuring product safety and reliability. When used as intended, our products are safe and pose no hazards under normal conditions. For more details, refer to the Safety Data Sheet.

Handling precautions – skin sensitization

Ensure the use of proper protective equipment when handling chemicals. For detailed guidance, refer to the Safety Data Sheet and consult with your PPE (Personal Protective Equipment) provider.

Additional Information

Please contact your local Flint Group Customer/Technical Service if further information is required.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 09/05/2026