

UCURA FLEX 3300 LM FB Matt



Low migration matt varnish for labels

Product Features

- UV curing varnish
- Fast curing
- Suited for food packaging
- Varnishing on both sides
- Suited for embossing and Corrugated cardboard lamination

Advantages of UCURA FLEX 3300 LM FB Matt

- Good matt effect
- Good flow
- Very elastic
- Outstanding rub resistance



UCURA FLEX 3300 LM FB Matt

Shelf life and storage Recommended storage temp. 10-25°C. Protect from frost and heat.

Direct sunlight should be avoided to prevent polymerization. Stable for a minimum of 12 months from the date of manufacture.

Special notes To get optimal results, we recommend an accurate control of the polymerization process

under the UV lamps.

Packaging 25 kg pails, 200 Kg drums, 1000 Kg tanks

Remarks The UCURA FLEX 3300 LM FB Matt has extremely low odour and low migration

characteristics.

It will comply with EU Regulations 1935/2004 and 2023/2006.

We recommend an accurate cleaning of the printing press and coating unit in order to

eliminate traces of former coatings not suitable for food packaging,

UCURA FLEX 3300 LM FB Matt is only suitable for indirect food contact.

Substrates Varnishing of labels, Corona pre-treated PE film, Corona pre-treated PP film and PVC film

In view of the wide substrates offered by various manufacturers, we recommend carrying out

your own tests before starting a print run.

Printing Process Varnishing units with chambered doctor blade (varnish amount approx. 4 – 6 g/m²)

Flexo printing (varnish amount approx. 3 – 5 g/m²)

Stir varnish thoroughly before use!

Viscosity approx. 75 sec/20°C, DIN 4mm-cup

Code VW78-011D UCURA FLEX 3300 LM FB Matt

More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.