

# Novalux® F 30 POSTER BIO

The series for prints requiring high light resistance

## Special process inks for sheetfed offset

### Product Features

- Novalux® F 30 POSTER BIO is a duct-fresh process ink series, based on renewable raw materials, suited for prints with high light resistance, for example posters and displays.
- The series consists of a light resistant Yellow and Magenta with high light resistance. Yellow and Magenta can be combined with all duct-fresh Cyan and Black inks of our standard process ink range.
- The series is optimally suited for straight-line printing on all multi-colour printing presses as well as for perfecting presses.
- Due to the high colour intensity of Novalux® F 30 POSTER BIO the printing of sensitive substrates is also possible without any problems. Despite the provided special light resistance the series is suited for printing work corresponding to ISO 12647-2.

### Advantages of Novalux® F 30 POSTER BIO

- Especially for prints with high light resistance.
- Suited for printing work corresponding to ISO 12647-2 – despite high light resistance.
- BIO-binders – based on renewable raw materials.
- Ideally suited for gloss coated and uncoated papers and board.

# Novalux® F 30 POSTER BIO

	Fastness properties					Printing properties								
	Light fastness	Alcohol	Solvent mixture	Alkali	Hot-calendering	Dot gain	Gloss	Setting	Oxidative drying	Rub resistance	Rapid further processing	Suitability for gloss coated papers/board	Suitability for uncoated papers/board	Suitability for matt coated papers/board
<b>Novalux® F 30 POSTER BIO</b>						5	5	5	5	6	5	7	7	6
<b>Novalux® 1 F 30 POSTER BIO Yellow</b>	6-7	+	-	+	+	1 = Characteristic weakly expressed 7 = Characteristic strongly expressed								
<b>Novalux® 2 F 30 POSTER BIO Magenta</b>	7	+	+	+	+	<b>The assessment of the colour properties was made under standardised printing conditions. In individual cases, under special conditions, as in printing with very high ink densities, the classification of certain properties may be different.</b>								
Light fastness properties according to ISO 12040: from 1 (low) to 8 (high) Fastness properties according to ISO 2836: + = Resistance provided - = Resistance not provided														

## Drying properties

Duct-fresh.

## Substrates

Ideally suited for gloss coated and uncoated papers and board. Very well suited for matt coated papers and board.

## Remarks

The colour shades of Novalux® F 30 POSTER BIO correspond to ISO 12647-2 and therefore comply as far as possible with the colour shades of standard process inks. The series can be combined with all duct-fresh Cyan and Black inks of our standard process ink range.

## Exceptions

Not for use on food packages without functional barrier.

## Further Information

For further information regarding light resistance in sheetfed offset please refer to our corresponding Technical Review.

## More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

## Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

## You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Flint CPS Inks Germany GmbH  
 Commercial, Publication & Sheetfed Inks  
 Sieglestrasse 25  
 70469 Stuttgart, Germany

T +49 711 98 16-0  
 F +49 711 98 16-700  
 sheetfed@flintgrp.com  
 www.flintgrp.com

Product names followed by ® are trademarks registered by Flint Group (represented by Flint CPS Inks Holdings LLC or Flint CPS Inks Germany GmbH).