

UCURA Lac Stampable Matt OPV

UV matt overprint varnish for commercial applications

EC coating for sheetfed offset and web offset

Product Features

- UCURA Lac Stampable Matt OPV is a modern offset UV varnish, which has been developed to combine
 excellent offset stability with a matt finish.
- UCURA Lac Stampable Matt OPV is ideally suited for paper and board as well as PVC, PE, PP, ABS, etc.

Advantages of UCURA Lac Stampable Matt OPV

- Matt effect.
- Hot Foil stampable.
- Glueable.
- Fast curing properties.
- Good rub resistance.
- High chemical resistance.
- Wide range of suitable substrates.



UCURA Lac Stampable Matt OPV

Shelf life and storage Recommended storage temp. 5-35 °C.

Direct sunlight should be avoided to prevent polymerization.

Stable for a minimum of 18 months from the date of manufacture.

Special notes To get optimal results, we recommend an accurate control of the polymerization process under

the UV lamps.

Packaging 2,5 kg pails

Substrates Paper and board. Synthetic materials such as PVC, PE, PP, ABS etc. can also be used.

Printing Process Printing unit

Exceptions Not for use on food packaging without functional barrier.

Codes VW72-001D-X1BJ UCURA Lac Stampable Matt OPV; 2,5kg

More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.