

Transparent whites for sheetfed offset

Range overview

Product features

- Transparent whites are used for the lightening of printing inks and as an important component in colour mixing.
- They are formulated ready-to-print and their composition corresponds to the one of spot inks. Based on BIO-binders, they contain transparent fillers instead of coloured pigments.
- Flint Group's transparent white range is designed to cater for a variety of needs, types of substrates and areas of application in sheetfed offset.
- Each base colour ink series is supplemented by a specific transparent white, which features the same printing properties as the base colour inks. If spot inks are mixed with the appropriate transparent white, the transparent white does not change the printability properties and the rheological properties remain largely unchanged.
- All products of the transparent white portfolio feature good printability.

Advantages of the transparent white range

- Ready-to-print.
- For lightening of printing inks and as a component in colour mixing.
- Good printability.
- The rheological properties remain largely unchanged.
- Range caters for a variety of areas of application and types of substrates.
- Optimally matched to Flint Group's base colour ink series.

Transparent whites for sheetfed offset

Product	Product Code	Product features / Drying properties	Dosage recommendation	Printing properties							
				Gloss	Setting	Oxidative drying	Rub resistance	Rapid further processing	Suitability for coated papers/board	Suitability for uncoated papers/board	Suitability for foils
Novavit® Easy Mix BIO Transparent white	VI60-000*	Duct-fresh. As a component in colour mixing, to mix PANTONE® colour shades and for continuous printing.	as required	5	5	3	3	3	6	5	1
Novavit® Eco Mix BIO Transparent white	VI62-000*	Duct-fresh. As a component in colour mixing, to mix PANTONE® colour shades.	as required	5	5	3	3	3	6	5	1
Novavit® BCS BIO INTENSIVE Transparent white	VZ19-000*	Duct-fresh. As a component in colour mixing. All purpose transparent white.	as required	5	5	2	3	2	6	5	1
Novaboard® BCS BIO INTENSIVE Transparent white	VZ21-000*	Drying by oxidation and setting. As a component in colour mixing. Very good rub resistance.	as required	5	3	6	6	6	6	6	4
Novavit® 6 P 12 BIO Transparent white	VI78-010*	Drying by oxidation and setting. As a component in colour mixing. Slightly opaque.	as required	3	4	5	5	5	6	5	1
Novaplast® 1 S 110 Transparent white	VI81-091*	Drying by oxidation only. As a component in colour mixing, for non-absorbent substrates.	as required	5	3	7	6	5	5	5	7
Novasens® BCS PREMIUM Transparent white	VZ93-000*	Drying by setting only. As a component in colour mixing, for food packaging printing.	as required	4	3	1	2	3	6	4	1

* Depending on the producing site

1 = Characteristic weakly expressed 7 = Characteristic strongly expressed

The assessment of the colour properties was made under standardised printing conditions. In individual cases, under special conditions, as in printing with very high ink densities, the classification of certain properties may be different

You are welcome to contact us for further information.

Flint CPS Inks Germany GmbH
Commercial, Publication & Sheetfed Inks
Sieglesstrasse 25
70469 Stuttgart, Germany

T +49 711 98 16-0
F +49 711 98 16-700
sheetfed@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group (represented by Flint CPS Inks Holdings LLC or Flint CPS Inks Germany GmbH). PANTONE® is a registered trademark of Pantone, Inc.

Transparent whites for sheetfed offset

Additives

All products are ready-to-print. With the exception of Novasens® BCS PREMIUM Transparent white the following additives may be used to adapt viscosity and tack:

Printing oil L (VU20-019*)	1 - 3 % to adapt viscosity and tack
Reduxpaste 4800 BIO (VU10-032*)	2 - 5 % to adapt the tack

Never add dryers to Novasens® BCS PREMIUM Transparent white or to the fountain solution. Only the below mentioned products are suitable as additives:

Novasens® PREMIUM Reducer (VU10-01C*)	1 - 3 % to adapt viscosity and tack
Novasens® PREMIUM Reduxpaste (VU10-01M*)	2 - 5 % to adapt the tack

Surface Finishing/ Fastness properties

The formulation of the transparent whites corresponds to those of the respective base colour ink series, and instead of coloured pigments, transparent fillers are used. For subsequent finishing necessary resistance requirements are determined by the properties of the pigments. The use of transparent whites does not have any influence with regard to the fastness properties of the ink.

Exceptions

With the exception of Novasens® BCS PREMIUM Transparent white all products of the transparent white range are not for use on food packaging without functional barrier.

More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Flint CPS Inks Germany GmbH
Commercial, Publication & Sheetfed Inks
Sieglestrasse 25
70469 Stuttgart, Germany

T +49 711 98 16-0
F +49 711 98 16-700
sheetfed@flintgrp.com
www.flintgrp.com

Product names followed by ® are trademarks registered by Flint Group (represented by Flint CPS Inks Holdings LLC or Flint CPS Inks Germany GmbH).
PANTONE® is a registered trademark of Pantone, Inc.