

UCURA FLEX 3200 LM FB Gloss



Low odour and low migration UV Varnish for coated papers and cardboards for packaging

Product Features

- UV curing varnish
- Fast curing
- Suited for food packaging
- Transparent varnish film

Advantages of UCURA FLEX 3200 LM FB Gloss

- Very good gloss
- Good flow
- Low odour
- Very good rub resistance
- Good stampability



UCURA FLEX 3200 LM FB Gloss

Shelf life and storage	Recommended storage temp. 10-25°C. Protect from frost and heat. Direct sunlight should be avoided to prevent polymerization. Stable for a minimum of 12 months from the date of manufacture.
Special notes	To get optimal results, we recommend an accurate control of the polymerization process under the UV lamps.
Packaging	25 kg pails, 200 Kg drums, 1000 Kg tanks
Remarks	The UCURA FLEX 3200 LM FB Gloss has extremely low odour and low migration characteristics. It will comply with EU Regulations 1935/2004 and 2023/2006.
	We recommend an accurate cleaning of the printing press and coating unit in order to eliminate traces of former coatings not suitable for food packaging,
	UCURA FLEX 3200 LM FB Gloss is only suitable for indirect food contact.
Substrates	Coated papers and cardboards for packaging, collapsible boxes as well as varnishing of labels
	In view of the wide substrates offered by various manufacturers, we recommend carrying out your own tests before starting a print run.
Printing Process	Flexo printing (varnish amount approx. 3 – 6 g/m²) Coating machines (varnish amount approx. 4 – 10 g/m²) Varnishing units (varnish amount approx. 4 – 8 g/m²)
	Stir varnish thoroughly before use!
Viscosity	approx. 105 sec/20°C, DIN 4mm-cup
Code	VW78-010D UCURA FLEX 3200 LM FB Gloss

More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Flint Group Commercial, Publication & Sheetfed Inks F +49 711 98 16-700 Sieglestrasse 25 70469 Stuttgart, Germany

T +49 711 98 16-0 sheetfed@flintgrp.com www.flintgrp.com

Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH).