Rely on us.⁵⁰

Varn[®] Sunday Fount

VAR

Formulated for high speed Heidelberg Sunday and Goss M-Series presses

Fountain solution for high speed Heatset web offset presses

Product Features

- Varn[®] Sunday Fount is a specially formulated fount solution to meet the exacting demands of modern high speed Heatset Web Offset Presses.
- Varn[®] Sunday Fount is the result of extensive research and development in the interaction of fount and ink at high speeds i.e. >15 mp/s.
- Varn[®] Sunday Fount incorporates dynamic surface tension properties which give the printer the latitude normally associated with alcohol but without any environmental risks.
- Varn[®] Sunday Fount has been formulated to meet the demands of modern plate technology including CtP and is compatible with the majority of negative and positive (baked) plates.
- Varn[®] Sunday Fount is an extremely clean running fount solution, minimising ink feedback onto dampers and into re-circulating tanks.

Advantages of Varn[®] Sunday Fount

- Eliminates alcohol.
- Reduces waste.
- Proven performance >15mp/s.
- Compatible with dayGraphica sleeves.
- Minimise ink feedback into dampeners.





Varn® Sunday Fount

Features	Advantages	Benefits
 Dynamic surface tension properties. 	 Reproduces the advantages of alcohol, without detriment to the environment. Effective ink/water balance. Reduces ink feedback to the dampening system. Eliminates piling. 	 Safer working environment. Gives printer the latitude he had with alcohol. Cleaner running and reduced downtime. Fewer blanket washes, therefore less waste and decreased production time.
 Flashpoint above 100°C. 	Safer handling and storage properties.Classified as non-hazardous.	Complies with health and safety legislation requirements.Safer pressroom conditions.
• Compatible with the majority of inks, stocks and water conditions.	 Increased flexibility in choice of consumables. 	Cost savings.

Product code	KT10-5SFG-#### (final 4 digits relate to pack size). Also available in a version to suit hard/alkaline waters of more that 250 ppm calcium carbonate and/or 15°dh hardness - KT10-5S2G-####.	
Pack sizes	20kg (01H5), 200kg (01N1), 600kg (01U6) and 1000kg (01U0).	
Recommended dosage	Between 2% and 4% concentration to reach pH 4.5 - 5.5, depending on local water conditions.	
Flashpoint	>100°C (AIII).	

More products. Streamlined access. Greater results.

Flint Group's Print Media division offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks and Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability.

Print Media Europe Varn House, Brinell Drive, Northbank Industrial Park, Irlam, Greater Manchester, M44 5BL, UK. T +44 (0)161 775 5412 F +44 (0)161 775 5415 printmedia.eu@flintgrp.com www.flintgrp.com Product names followed by $\ensuremath{\mathbb{R}}$ are trademarks registered by Flint Group Incorporated.