8212 Non-compressible

Unique Blanket with Unique Printing Qualities

The dayGraphica 8212 has a superior cast surface that prevents swelling and tackiness, resists piling and allows for easy wash-up. The instant release characteristics eliminate the battle with sheet curl and give a good hard dot reproduction. The top layer provides resiliency and the bottom layer maintains stability.

Features	Benefits
Superior cast surface conventional blanket	 Reduces solvent penetration. Prevents swell and tackiness. Resists piling. Easy wash-up.
Super quick release	 Instant release-eliminating sheet curl, hard dot reproduction. Low-stretch fabric provides gauge retention.

Specifications

Color:

Blue

Surface:

Cast Finish

Thickness:

2 Ply 1,32mm/.052" Nominal

3 Ply 1,67mm/.066" Nominal

4 Ply 1,98mm/.076" Nominal

5 Ply 2,57mm/.101" Nominal

Face Compound:

Solvent Resistant Rubber Blend

Hardness:

81° Shore A

Sheetfed	Large Commercial	Medium Commercia
Packaging	Folding Carton	Metal Deco

Compressibility Deflection:

2 Ply 0.002" Typical at 145 psi

3 Ply 0.003" Typical at 145 psi

4 Ply 0.003" Typical at 145 pis

5 Ply 0.004" Typical at 145 psi

Elongation:

2 Ply 1.1% Typical at 57 ppi

3 Ply 1.0% Typical at 57 ppi

4 Ply 0.9% Nominal at 57 ppi

5 Ply 0.8% Typical at 57 ppi

Tensile Strength:

2 Ply 390 ppi Typical

3 Ply 550 ppi Typical

4 Ply 670 ppi Typical

5 Ply 780 ppi Typical

For more information about this Day product, contact us at 800-525-6510 visit us online at www.dayintl.com



Day International Inc. 130 West Second Street Suite 1700 Dayton, OH 45402 T +1 800 877 8187 www.dayintl.com

