

TECHNICAL DATA SHEET

Varn® Filtrate 60 Wash
KV10-075**Description:**

A roller and blanket cleaner for Coldset Web and sheetfed offset systems.

Suitable for use in recycling systems and has been approved by Technotrans for use with the Ecoclean system.

This wash has a flashpoint of >60°C and is suitable for coldset and sheetfed applications.

Application:

- For use in automatic wash systems equipped with filtration units: Use Varn® Filtrate 60 Wash neat and replenish recycled solvent as required.
-
- For manual applications: Apply via wash up bottle or lint free cloth as part of normal wash up procedure.

Key Features:

- Low odour.
- Can be recycled by filtration or distillation.
- Approved for use with the Technotrans ecoclean system.
- High flashpoint (>60°C) AIII.
- Excellent ink solvency properties.
- Fast effluent separation

Certifications:

- OEM approved (manroland & KBA Coldset Web presses, Technotrans Ecoclean washing agent recycling systems for sheetfed and web offset presses) in accordance with Fogra corrosion and elastomer swell testing criteria. WIFAG corrosion approval.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 09/05/2026

TECHNICAL DATA SHEET

Varn® Filtrate 60 Wash

KV10-075

**Storage:**

- The products should be processed within 24 months after production date.
- Once opened the products should be processed within 12 months.
- To prolong the shelf life of the wash, we recommend storing the product in its original, un-opened packaging at room temperature (20 - 25°C), as correct storage conditions are essential.

Quality / Environment / Health & Safety

Flint Group maintains a comprehensive Management System that integrates quality, environment, health & safety. Our production and quality control processes meet high industry standards, ensuring product safety and reliability. When used as intended, our products are safe and pose no hazards under normal conditions. For more details, refer to the Safety Data Sheet.

Handling precautions – skin sensitization

Ensure the use of proper protective equipment when handling chemicals. For detailed guidance, refer to the Safety Data Sheet and consult with your PPE (Personal Protective Equipment) provider.

Additional Information

Please contact your local Flint Group Customer/Technical Service if further information is required.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 09/05/2026