

TECHNICAL DATA SHEET

dayGraphica® Superstrip FB

Formerly Duco Superstrip FB

Fabric backed strippable blanket for water-based and UV coatings

Description:	Fabric backed coater / stripper Polished surface compatible with water based and most UV coatings Easy and consistent stripping properties Clean cuts, with visible cut lines for easy stencil preparation Compressible layer gives smash resistance for added durability
Application:	• Strippable blanket for water-based and UV coatings
Key features:	• Excellent smash recovery. • Easy stencil peeling. • Unique construction - Enables repeat runs where precise register is not critical. • Dual compatibility cast surface - Optimum coating transfer with both aqueous and UV coatings. • High quality stabilising fabric and stripping layer - Clean edged precision cutting and Deep stencil depth. • Dense low stretch fabric - Provides extra stability.
Colour:	• Turquoise
Surface:	• Ground
Thickness:	• 1.70mm / 0.067" • 1.96mm / 0.077"
Nominal Stencil Depth:	• 3ply: 0.7mm / 0.028" • 4ply: 0.8mm / 0.031"
Face Compound:	• Solvent Resistant Rubber Blend
Compressibility:	• 1.70mm / 0.067" • 0.12mm Typical at 1060 kPa • 0.16mm Typical at 2060 kPa • 1.96mm / 0.077" • 0.16mm Typical at 1060 kPa • 0.22mm Typical at 2060 kPa
Surface roughness (Ra):	• 0.9µm typical
Ink Compatibility:	• UV & Water based coatings

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 20/04/2026

TECHNICAL DATA SHEET

dayGraphica® Superstrip FB

Formerly Duco Superstrip FB

Fabric backed strippable blanket for water-based and UV coatings

Storage:

- To prolong the shelf life, we recommend storing the product in its original, un-opened packaging at room temperature (20 - 25°C).
- Protect from long-term exposure to direct light. Sunlight and fluorescent light can cause discoloration of the surface.
- Product should be used within 12 months of production.

Quality / Environment / Health & Safety

Flint Group maintains a comprehensive Management System that integrates quality, environment, health & safety. Our production and quality control processes meet high industry standards, ensuring product safety and reliability. When used as intended, our products are safe and pose no hazards under normal conditions.

Handling precautions

No handling precautions under normal conditions.

Additional Information

Please contact your local Flint Group Customer/Technical Service if further information is required.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 20/04/2026