

Rely on us.SM

dayGraphica[®] 8899 Newsprinter

Meet deadlines and improve print quality

Printing Blankets: Offset - No-Pack

The dayGraphica[®] 8899 is designed to help you efficiently achieve the standards of quality expected from today's newsprinter, with crisp black and color headlines, sharp contrast and quality four-color process. It's more resistant to smashes and web wraps and it uses the same surface compound and textures that have proven their durability on other dayGraphica newspaper blankets. That means you can expect millions of quality impressions and reduced blanket changes from this tough performer.

Advantages of dayGraphica[®] 8899 Newsprinter

- Performs well in both single-width and double-width no-pack newspaper applications
- Excellent abrasion resistance
- Maximum smash resistance
- Rebounds quickly
- High density carcass prevents gauge loss and provides long life

NEWS. DOUBLE WIDE.



FlintGroup

dayGraphica® 8899 Newsprinter

Meet deadlines and improve print quality

Features	Benefits
Highly ground surface	Uniform gauge and consistency. Ideal texture for carrying and transferring ink. Maximum release characteristics. Precise printability.
Compatible rubber surface compound	Solvent resistant. Excellent abrasion resistance. Excellent release characteristics. More consistent feed characteristics.
Durability-engineered carcass	High-density carcass prevents gauge loss and provides long life.
Patented closed-cell compressible layer	Enables blanket to achieve precise and even printing pressure across entire printing surface. Maximum smash resistance. Key factor in blanket durability. Rebounds quickly.
Application versatility	Performs well in both single-width and double-width no-pack newspaper applications.

Specifications:

Color: Green

Surface: Ground

Thickness:

2,06mm thru 2,24mm/.081"
thru .088" Nominal

Face Compound:

Solvent Resistant Rubber Blend

Hardness:

77° Shore A

Compressibility Deflection:

0,15mm at 1060 kpa/.006" at 154 psi Typical

0,20mm at 2060 kpa/.008" at 299 psi Typical

Elongation:

1,1% at 10 N/mm/1.1% at 57 ppi Typical

Tensile Strength:

100N/mm/571 ppi Typical

**Inks,
blankets,
chemicals
& more**

Rely on us™
to bring greater value to your pressroom.

For more information:

Flint Group
Print Media North America
14909 N. Beck Road
Plymouth, MI 48170
+1 734 781 4600
printmedia.na@flintgrp.com

www.flintgrp.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. Customers are responsible for confirming suitability of this product for their application. In no event shall Flint Group be liable for any errors, facts or opinions contained herein, or any claims by any party alleging reliance on these materials, regardless of the form of action.

Product names followed by a ® are trademarks registered by a Flint Group company.

Version 5/2015 Page 2 of 2