

## UCURA FLEX 2100 BF Gloss

UV Varnish for coated papers and cardboards for packaging, collapsible boxes

## **Product Features**

- UV curing varnish with very good gloss.
- Fast curing
- Free of benzophenone and 4-methylbenzophenone
- Short exposure of the prints (2 4 sec.) to temperature of approx. 160 180 °C possible
- Suited for varnishing on both sides

### Advantages of UCURA FLEX 2100 BF Gloss

- Very good gloss
- Good flow
- No sheet curling
- Chemical and water resistant
- Excellent rub resistance



# UCURA FLEX 2100 BF Gloss

Shelf life and storage	Recommended storage temp. 10-25 °C. Protect from frost and heat. Direct sunlight should be avoided to prevent polymerization. Stable for a minimum of 12 months from the date of manufacture.
Special notes	To get optimal results, we recommend an accurate control of the polymerization process under the UV lamps.
Packaging	25 kg pails, 200 Kg drums, 1000 Kg tanks
	Coated papers and cardboards for packaging, collapsible boxes as well as varnishing of self adhesive labels and thermal label paper. Also suited for inmould labels on paper or Corona pre-treated PE film, Corona pre-treated PP film and PVC film.
	In view of the wide substrates offered by various manufacturers, we recommend carrying out your own tests before starting a print run.
	Flexo printing (varnish amount approx. $3 - 6 \text{ g/m}^2$ ) Coating machines (varnish amount approx. $4 - 10 \text{ g/m}^2$ ) Varnishing units (varnish amount approx. $4 - 8 \text{ g/m}^2$ ) Stir varnish thoroughly before use!
Exceptions	Not for use on food packaging without functional barrier.
Viscosity	approx. 40 sec/20°C, DIN 4mm-cup
Code	VW78-004D UCURA FLEX 2100 BF Gloss

### More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

### Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

Flint Group

Sieglestrasse 25

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

T +49 711 98 16-0 Commercial, Publication & Sheetfed Inks F +49 711 98 16-700 sheetfed@flintgrp.com 70469 Stuttgart, Germany www.flintgrp.com

Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH).