

TECHNICAL DATA SHEET

Varn® MAJESTA EDGE XL FOUNT KT15-033

**Description:**

Varn® Majesta EDGE XL is a versatile heatset fount that performs well with all heatset inks in brush or spray dampening systems. With its unique blend of materials, Majesta EDGE XL has been proven to enhance press performance, maintain a cleaner and more stable fountain solution delivery system, and keep the non-image areas of the plates and blankets clean throughout the press runs. It is designed for use with today's wide variety of substrates.

Application:

- Recommended dosage: Use 3-6 ounces per gallon of water (depending on equipment and requirements). Conductivity per ounce above water 420 micromhos. Increase product by ½ ounce per gallon as needed to achieve desired print quality.
- For best results start with a clean dampening system.

Key Features:

- Low doses
- Enables improved ink transfer
- Reduces paper piling and ink build-up on dampening rollers
- Strong chelating package
- Superior protection of non-image areas of plates and blankets

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 20/07/2026

TECHNICAL DATA SHEET

Varn® MAJESTA EDGE XL FOUNT KT15-033



Storage:

- The product should be processed within 12 months after production date.
- To prolong the shelf life, we recommend storing the product in its original, un-opened packaging at room temperature (68 -78 °F), as correct storage conditions are essential.

Quality / Environment / Health & Safety

Flint Group maintains a comprehensive Management System that integrates quality, environment, health & safety. Our production and quality control processes meet high industry standards, ensuring product safety and reliability. When used as intended, our products are safe and pose no hazards under normal conditions. For more details, refer to the Safety Data Sheet.

Handling precautions – skin sensitization

Ensure the use of proper protective equipment when handling chemicals. For detailed guidance, refer to the Safety Data Sheet and consult with your PPE (Personal Protective Equipment) provider.

Additional Information

Please contact your local Flint Group Customer/Technical Service if further information is required.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 20/07/2026