

TECHNICAL DATA SHEET

Varn® Roller Lube KU40-1RL

**Description:**

Lubricates rollers when printing either for half web or on printing units that require lubrication when running without ink.

This product is safe for use on most types of rubber compound (except EPDM). It can be sprayed on blankets at start-up to reduce tack and has a high flashpoint (>100°C) and so is not classified as flammable or hazardous.

Allows ink to be applied without requiring washing up of the roller train.

Application:

- Apply sufficient Varn® Roller Lube to wet all rollers.
- Must be re-applied every six hours (minimum) - do not allow to run dry.

Key Features:

- Lubricates rollers when printing half web.
- Lubricates units without running ink.
- Can be sprayed or applied from wash up bottle.
- High flashpoint (>100°C) AIII.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 17/05/2026

TECHNICAL DATA SHEET

Varn® Roller Lube KU40-1RL

**Limitations:**

- Not suitable for use on EPDM compounds.
- Not for use for food packaging without functional barrier.

The final product/packaging structure and complete packaging must be tested and approved according to the intended application by the printer/packer. If your application covers any of the above, or other non-standard applications, please consult your local Flint Group technical support for guidance.

Storage:

- The products should be processed within 12 months after production date.
- To prolong the shelf life of the product, we recommend storage in its original, un-opened packaging at room temperature (20 - 25°C), as correct storage conditions are essential.

Quality / Environment / Health & Safety

Flint Group maintains a comprehensive Management System that integrates quality, environment, health & safety. Our production and quality control processes meet high industry standards, ensuring product safety and reliability. When used as intended, our products are safe and pose no hazards under normal conditions. For more details, refer to the Safety Data Sheet.

Handling precautions – skin sensitization

Ensure the use of proper protective equipment when handling chemicals. For detailed guidance, refer to the Safety Data Sheet and consult with your PPE (Personal Protective Equipment) provider.

Additional Information

Please contact your local Flint Group Customer/Technical Service if further information is required.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 17/05/2026