

TECHNICAL DATA SHEET

Varn® UV 142

KV35-017



- Description:** Varn® UV 142 wash is effective and easy to use. Its design also maximizes roller and blanket life—an important feature for any cost-effective printing operation. Designed exclusively for UV printing, this water-miscible wash is suitable for use with a wide variety of rollers and blankets used in energy curable printing.
- Application:**
- For best results, allow Varn® UV 142 wash to reach room temperature.
 - BLANKETS: Saturate shop towel with Varn® UV 142 wash and clean blanket. Wipe dry.
 - ROLLERS: Apply sufficient amount of product onto rollers. Allow wash to penetrate ink, then engage wash-up attachment. Continue to add small amounts of product until rollers are clean.
- Key Features:**
- Easy to use.
 - Low rubber swell extends roller & blanket life.
 - High flashpoint.
 - Compatible with EPDM, Chameleon rollers, and nitrile rubber.
 - One application removes all debris.
 - Water miscible.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 20/07/2026

TECHNICAL DATA SHEET

Varn® UV 142 KV35-017



Limitations:

- Do not use on unbaked positive plates.

The final product/packaging structure and complete packaging must be tested and approved according to the intended application by the printer/packer. If your application covers any of the above, or other non-standard applications, please consult your local Flint Group technical support for guidance.

Storage:

- The product should be processed within 12 months after production date.
- To prolong the shelf life, we recommend storing the product in its original, un-opened packaging at room temperature (68 -78 °F), as correct storage conditions are essential.

Quality / Environment / Health & Safety

Flint Group maintains a comprehensive Management System that integrates quality, environment, health & safety. Our production and quality control processes meet high industry standards, ensuring product safety and reliability. When used as intended, our products are safe and pose no hazards under normal conditions. For more details, refer to the Safety Data Sheet.

Handling precautions – skin sensitization

Ensure the use of proper protective equipment when handling chemicals. For detailed guidance, refer to the Safety Data Sheet and consult with your PPE (Personal Protective Equipment) provider.

Additional Information

Please contact your local Flint Group Customer/Technical Service if further information is required.

For more details, contact your nearest Flint Group Packaging Solutions office or dealer.

Flint Group Packaging Solutions
www.flintgrp.com
info@flintgrp.com

DISCLAIMER

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers/Users must always make every effort to ensure that the products employed are suitable and appropriate for the purpose intended. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group.

Version: 20/07/2026