

## Technical Specifications

<b>Product Name</b>	<b>VersaPort™ Wide</b> <b>VersaPort™ Narrow</b>
<b>Model Name</b>	<b>PORT-AS-99600</b> <b>PORT-AS-99602</b>
<b>Type</b>	AS-99600 AS-99602
<b>Region</b>	Global
<b>Manufacturer</b>	AutoStore AS
<b>Dimensions</b>	Wide: L: 1,792 mm / W: 753 mm / H: 1,102 mm Narrow: L 2,387 mm / W: 533 mm / H: 1,102 mm
<b>Weight</b>	Wide: 108 kg (incl., frame) Narrow: 117 kg (incl., frame)
<b>Weight Accuracy</b>	+/- 100 g
<b>Max. Load Including Bin</b>	35 kg
<b>Bin Height Support</b>	220, 330, and 425 mm
<b>Max. Bin Throughput</b>	180 Bins/hr. on 16-level (330 mm Bins) 170 Bins/hr. on 18-level (330 mm Bins) 240 Bins/hr. on mezzanine level
<b>Min. Bin Exchange Time</b>	Wide: Weight function disabled: 7.5 s   Weight function enabled: 9 s Narrow: Weight function disabled: 8.5 s   Weight function enabled: 10 s
<b>Storage Temperature</b>	-25 °C to +55 °C
<b>Operating Temperature</b>	+1 °C to +35 °C
<b>Operating Humidity</b>	40 to 90 % non-condensing
<b>Furniture Material</b>	Aluminum and plastic material
<b>Working Height</b>	900 to 1,110 mm (25 mm increments)
<b>Noise Level</b>	< 70 dBA
<b>Power</b>	24 VDC, 5A Average: 100 W
<b>Power Contact</b>	Kycon KPJX-4S-S
<b>Signal</b>	Shielded Ethernet, RJ45
<b>IP Class</b>	IP20