

SRC PIPE

NEW SOUTH WALES



RCPA, the Australian Pipe Company, is the leading manufacturer of Vertically Cast Concrete Pipes in Australia.


The dry-cast pipe making process was introduced to Australia by RCPA and has been in use for two decades. Vertically casting is the most efficient method of pipe manufacture available.

Benefits of RCPA SRC Pipes;

- Rapid production rates
- Pipes comply with AS/NZS 4058:2007
- Precision Manufacturing technology
- Low impact and sustainable process

SRCPIPE

Rubber Ring Joint



Somersby

Nom. ID (mm)	Pipe ID (mm)	Socket OD (mm)	Pipe OD (mm)			Weight (kg)		
			Class 2	Class 3	Class 4	Class 2	Class 3	Class 4
375	372	546	-	-	449	-	-	318
450	447	643	-	-	540	-	-	470
525	522	734	-	621	621	-	584	590
600	597	825	700	700	700	703	706	724
675	671	913	781	781	781	837	841	855
750	746	1004	870	870	870	1025	1029	1045
825	821	1093	951	951	951	1179	1187	1205
900	896	1184	1038	1038	1038	1401	1408	1437
1050	1046	1345	1188	1188	1188	1650	1667	1698

Thornton

Nom. ID (mm)	Pipe ID (mm)	Socket OD (mm)	Pipe OD (mm)			Weight (kg)		
			Class 2	Class 3	Class 4	Class 2	Class 3	Class 4
750	746	1005	876	876	876	1030	1034	1258
825	821	1093	961	961	961	1204	1212	1471
900	896	1184	1044	1044	1044	1395	1421	1722
1050	1046	1345	1198	1198	1198	1685	1714	1756
1200	1196	1527	1400	1400	1400	2481	2516	2561
1350	1345	1690	1570	1570	1570	3057	3087	3106
1500	1495	1910	1730	1730	1730	3694	3725	3772
1650	1645	2053	1840	-	-	3550	3640	-
1800	1794	2223	1996	-	-	4046	4119	-
2100	2094	2553	2300	-	-	4920	-	-

*Dimensions and weights subject to change

- Effective length = 2340mm
- Rubber rings supplied with all pipes
- Other classes available on request
- Pipes listed above conform with AS/NZS 4058:2007 for normal environment exposure conditions
- Marine environment pipes available on request
- DN600 and smaller manufactured without lifting holes
- DN675 and larger supplied with lifting holes



1800 88 7272

www.rcpa.com.au

Issue: May 2026