WAX

Waxes can be natural secretions of plants or animals, such as beeswax, or by-products of petroleum refining. Wax is commonly used in the paper and boxboard industries to make products such as cartons and paper packaging moisture resistant. Wax can also help prevent food products from sticking to paper packaging.

SUGGESTED PUMPS:



1224A-BXB SERIES™

- Cast Iron
- Jacketed for steam/oil heating prior to pump startup
- O-Pro[®] Barrier Seal to virtually eliminate leaking & mess associated with traditional packed pumps
- Capacities to 200 GPM

WAX APPLICATIONS:

- Box coatings for food boxes
- Fresh produce coating
- Paper coating
- Candle manufacturing



227C SERIES™

- 316 Stainless Steel
- Jacketed for steam/oil heating prior to pump startup
- Capacities to 320 GPM



4224A SERIES™

- Cast Iron
- Jacketed for steam/oil heating prior to pump startup
- Mechanical seal options
- Capacities to 500 GPM

VIKING IN THE PROCESS:

Once melted, many waxes are relatively low viscosity liquids, but viscosities can be higher for some specialty waxes. Viking pumps are used for manufacturing and refining oilseed waxes at oilseed processors, petroleum-based waxes at oil refineries, and bees wax at honey processors. They are also used to transfer molten wax in downstream product manufacturing applications such as box coatings. Viking pumps are used to transfer liquid wax from the melter to curtain coaters that feed box blanks under a curtain of liquid wax that coats one side of the blank and passes it to a drying section.

Cast iron construction is typically satisfactory, but stainless may be required for purity considerations. Depending on specific melting temperature, jacketed pumps are frequently required. Standard construction pumps with carbon bushings can generally be used, but some crude or filled waxes may require hardened constructions, such as tungsten carbide idler pin and bushing.

Note: O-Pro[®] seals are patented.

INTERESTED IN A PRODUCT? CONTACT YOUR STOCKING DISTRIBUTOR TODAY!





