VIKING PUMP[®]



1127A SERIES™, 1327A SERIES™

STAINLESS STEEL CONSTRUCTION | UNIVERSAL PRODUCT LINE



ABOUT 0-PR0®

Viking Pump[®] is the leader in internal gear innovation and the latest development is the O-Pro[®] seal technology. This new series benefits from the enhancement of our own factory engineered and installed seal. This technology features a robust seal and lubrication chamber, all in one.

FEATURES & BENEFITS

- 316 stainless steel construction for process fluid compatibility
- O-Pro[®] Guard provides a robust sealing solution for many markets
- O-Pro® Guard rebuildable design offers minimal downtime and low cost



* Range may increase with end clearance adjustment

PERFORMANCE

MODELS	SPECIFICATIONS					
Non-Jacketed*	Performance			Standard Ports		
O-Pro [®] Guard Seal	Max Speed, RPM	GPM	m³/h	Size, Inches	Туре	Orientation
H1127A	760	6	1.4	1.5	Flange	Right Angle
HL1127A	760	13	3	1.5	Flange	Right Angle
K1127A	520	50	11	2	Flange	Right Angle
KK1127A	520	65	15	2	Flange	Right Angle
LQ1127A	520	100	23	2.5	Flange	Right Angle
LL1127A	520	135	31	3	Flange	Right Angle
LS1127A	520	160	36	3	Flange	Right Angle
Q1127A	350	200	45	4	Flange	Right Angle
QS1127A	350	320	73	6	Flange	Opposite
N1327A	280	475	108	6	Flange	Opposite
R1327A	225	880	200	8	Flange	Opposite
RS1327A	225	1280	290	10	Flange	Opposite

*1327A Series™ include jacketed parts as standard.

PORTING

- Right Angle (90°) (Rotatable Casing), H-Q
- Opposite (180°) (Rotatable Casing), QS-RS
- Flanged (ANSI)

SEALING

O-Pro[®] Guard Seal

MOUNTING

Foot Mount

OPTIONS

Jacketing (1227A Series™, 1327A Series™)

TYPICAL APPLICATIONS

Soaps, Detergents Paints & Inks & Surfactants Edible Oils General Chemicals Peanut Butter





CURVES



CONTACT YOUR STOCKING DISTRIBUTOR TODAY



VIKING PUMP, INC. A Unit of IDEX Corporation 406 State Street Cedar Falls, Iowa 50613 U.S.A. vikingpump.com

GLOBAL LEADER IN POSITIVE DISPLACEMENT PUMPING SOLUTIONS: Cedar Falls, Iowa, USA | Windsor, Ontario, Canada | Shannon, Ireland | Eastbourne, United Kingdom

