

## COMPLETION SOLUTIONS | SUBSURFACE SAFETY VALVES

# NEXStar™ tubing-retrievable safety valve

Enhanced TRSV with simple, compact design for improved performance

## FEATURES

- Non-elastomer dynamic piston seals
- Flow tube debris barriers
- Unique flow tube design prevents debris from settling on top of flow tube
- MTM body joints
- Available with full MTM well containment capability in closed position
- Optional through flapper equalizing feature

## BENEFITS

- Tested in field applications, reliable hydraulic actuator; dynamic seals independently verified gas-tight
- Critical components isolated from well debris with valve in open position
- Simple, compact design
- API 14A 13th edition verified

## Overview

The Halliburton NEXStar™ tubing-retrievable safety valve (TRSV) builds on the legacy of the Halliburton NE™ safety valve platform with improved performance features. The NEXStar TRSV is a single rod-piston non-elastomer flapper valve designed for general production with greater reliability and long life. The valve includes an embedded resilient seal in the flapper/seat assembly for improved low-pressure sealing performance while maintaining full metal-to-metal (MTM) sealing capability for high pressure. The NEXStar TRSV actuator design includes the field-proven, high-performance, non-elastomer hydraulic piston used throughout Halliburton rod-piston TRSVs. The HST MTM body joints and the high-performance actuator place this valve in the premium category while the simple, compact design enhances the valve's overall performance to help deliver reliable operation.

## Applications

- General production completions
- Hostile well environments incompatible with elastomers
- Cement-through operations
- Frac-through operations



NEXStar™ TRSV

NEXStar™ tubing-retrievable safety valve specifications

TUBING SIZE (IN.)	MAXIMUM OD (IN.)	INTERNAL PACKING BORE (IN.)	PRESSURE RATING (PSI)
2 7/8	4.65 to 4.91	2.125 to 2.313	5,000 to 10,000
3 1/2	5.03 to 5.62	2.562 to 2.813	5,000 to 10,000
4 1/2	5.965* 6.62 to 7.35	3.688 to 3.813	5,000 to 10,000

\*Slimline option (NE™ safety valve)

For more information, contact your local Halliburton representative or visit us on the web at [www.halliburton.com](http://www.halliburton.com)

Sales of Halliburton products and services will be in accord solely with the terms and conditions contained in the contract between Halliburton and the customer that is applicable to the sale.

H014996 12/25 © 2025 Halliburton. All Rights Reserved.