

UNCONVENTIONAL SOLUTIONS | OPENHOLE ISOLATION

# ZoneGuard® HE packer

High-expansion sealing capabilities for a wide range of openhole applications

## FEATURES

- Hydrostatic assist feature for positive pressure on element
- High-expansion element package
- Anti-preset mechanism
- Small running OD
- Adjustable setting shear value
- Internal locking system

## BENEFITS

- Provides selective production management in horizontal wellbores
- Reliably controls inflow or injection within selected sections of the wellbore
- Wide range of openhole isolation capabilities with one packer design
- Optional setting procedure; either hydraulic, hydrostatic, or hydrostatic-assist

## Overview

The Halliburton ZoneGuard® HE (High-Expansion) packer is designed for situations where a high-expansion sealing element is required and when large variations in hole gauge diameter are anticipated. The packer uses a multi-durometer, multi-element package with a unique back-up and deployment system to deliver industry-leading sealing performance in a large range of open or cased hole diameters in the most challenging wellbore environments. The packer is well suited for zonal isolation in multiple applications such as sand control, production management, stimulation, and stage cementing.

The ZoneGuard HE packer is run as part of the completion string and can be set either hydrostatically or hydraulically, depending on the well conditions. The hydrostatic-set ZoneGuard HE packer requires a shifting tool to shift an internal sleeve that allows the hydrostatic pressure to enter into the setting chamber and set the packer. The hydraulic-set ZoneGuard HE packer can be set by plugging the tubing below the packer or with an isolation straddle tool to provide hydraulic pressure to the setting chamber. The hydraulic ZoneGuard HE packer can also contain a hydrostatic assist feature, which helps maintain positive pressure on the packer at all times.



HAL121618

**ZoneGuard® HE packer - technical specifications**

TOOL CONNECTION	MAX METAL OD	MIN. ID	MIN. BORE HOLE	MAX. BORE HOLE	LENGTH	TEMP RATING	MAX. PRESSURE RATING AT MIN. BORE ID	SETTING PROCESS
	(IN.)	(IN.)	(IN.)	(IN.)				
4 1/2 12.60 lbs. VAMTOP®	5.630	3.490	6	8 1/4	130.70	325°F	5000 psi	Hydraulic
4 1/2 12.75 lbs. API-EU	5.630	3.490	6	8 1/4	169.08	325°F	5000 psi	Hydrostatic
5 1/2 17.0 lbs. NEWVAM®	8.000	4.670	8 1/2	11 1/2	142.33	325°F	5000 psi	Hydraulic
5 1/2 17.0 lbs. API-LC	8.00	4.870	8 1/2	11 1/2	170.85	325°F	5000 psi	Hydrostatic
6 5/8 32 lbs. VAMTOP®	8.000	4.890	8 1/2	11 1/2	140.88	325°F	5000 psi	Hydraulic

For more information, contact your local Halliburton representative or visit us on the web at [www.halliburton.com](http://www.halliburton.com)

Sales of Halliburton products and services will be in accord solely with the terms and conditions contained in the contract between Halliburton and the customer that is applicable to the sale.

H08307 11/24 © 2024 Halliburton. All Rights Reserved.