

Atmospheric Models with Powered Damper

Energy Savings

- Built-in heat traps on the water inlet and outlet reduce the amount of heat lost through piping
- Exceed NRCan energy efficiency standards

Benefits

- Flue damper for increased energy efficiency and performance
- 24 Volt Gas Valve offers:
 - › Diagnostic capabilities
 - › Monitoring of damper to ensure proper operation and safety
 - › Spark ignition eliminating the need for a standing pilot
- Robust 1/4" pilot tubing
- Durable brass drain valve
- Turbulator dip tube reduces sediment build-up at bottom of the tank
- Glass lining provides superior protection against tank corrosion
- Plugs into a standard 110/120V outlet (10 ft. power cord included)

- Easy-to-access combustion chamber
- Conveniently located T&P and drain valve for ease of installation and serviceability
- Top mounted heavy duty anode rod for added tank protection

Warranty*

- 6 year against inner tank leakage
- 6 year on component parts



Illustrated model: UG40-40SD3-N2 100



C US
LOW LEAD
CONTENT



Canada

ENERGUIDE

Uniform Energy Factor (UEF)
Gas / Propane-fired Storage Water Heaters

This product's capacity*
Very small
Low
Medium
High


This product
0.66-0.69

more → energy use ← least

*Only compare products of similar capacities
Visit energyguide.gc.ca/water-heater-label for more information.

*From the installation date. Installation must be made by a professional., otherwise the warranty is SIX (6) years on the tank and ONE (1) year on parts.

Atmospheric Models with Powered Damper



SPECIFICATIONS													
Model	Capacity			Input BTU	Altitude Feet (Meters)	Recovery Rate 90°F / 50°C			First Hour Rating GPH (LPH)	Energy Factor	UEF	Warranty*	
	US gal.	Liters	IMP gal.			US gal.	Liters	IMP gal.				Tank /	Parts
NATURAL GAS													
UG40-40SD3-N2 100	40	151	33	40,000	10,100 (3,078)	41	155	34	67 (254)	0.67	0.66	6 /	6
UG50-40SD3-N2 100	50	189	42	40,000	10,100 (3,078)	41	155	34	81 (307)	0.67	0.69	6 /	6

*Installation must be made by a professional. Otherwise the warranty is SIX (6) years on the tank and ONE (1) year on parts.

DIMENSIONS								
Model	A	B	C	D	E	F	Drafthood Connector Diameter	Shipping Weight
	inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches	lb (kg)
UG40	54 (137)	47 3/4 (121)	22 (56)	13 (33)	8 (20)	41 (104)	3 or 4	149 (68)
UG50	55 3/4 (142)	49 1/2 (126)	24 (61)	13 (33)	8 (20)	42 1/2 (108)	3 or 4	183 (83)