

Flexible Models - 108 (61 Imp. gallons)

Standards

- These models meet the safety and construction requirements of CSA Standard C22.2 No. 110
- Meet or exceed the standby loss requirements of NRCan and ASHRAE 90.1 Standard

Benefits

- **COMMERCIAL DESIGN:** Manufactured with thicker special steel and works so as to feed the elements or a bank of elements alternately (Light or Medium Duty) or simultaneously (Heavy Duty)
- Insulated with a uniform 2 inch (5 cm) layer of insulation reducing heat loss and energy costs
- Two (2) oversized high quality magnesium anodes to provide superior protection against the corrosive effects of water and extend the life of the tank
- Inner tank is glass-lined with a uniquely formulated blue cobalt glass enriched with zircon
- 1-1/2" hot and cold water NPT di-electric connections on all models
- Increased ease of voltage and power conversion on site

- **CONVERSION KIT :** Allows multiple different configurations. Conversion on site
- T&P valve(supplied) to protect the tank from damaging effects of excessive temperature and pressure
- Equipped with two hinged doors for easy service access to components
- Brass drain valve
- Surface mount thermostat with maximum setpoint of 160°F (Heavy Duty) or 180°F (Light & Medium Duty)
- CSA certified immersion heating elements
- Patented twist-lock flange for easier element replacement



Warranty

- 3-year warranty against inner tank leakage
- 1-year warranty on parts




Flexible Models - 108 (61 Imp. gallons)

Light & Medium Duty - 208, 240, 277 & 480 Volts / Single-Phase



MODEL NUMBER STRUCTURE



VOLTAGE INDEX

A	208 Volts
B	240 Volts
D	480 Volts

SPECIFICATIONS

Model*	Input	Amperage			Phase	Number of elements
	kW	208 V	240 V	480 V		
LIGHT & MEDIUM DUTY - 2 or 4 elements						
1082Y-1-3S	3	14.4	12.5	6.3	1	2
1082Y-1-4.5S	4.5	21.6	18.8	9.4		
1082Y-1-5S	5	24.0	20.8	10.4		
1082Y-1-6S	6	-	25.0	12.5		
1084Y-1-6S	6	28.8	25.0	12.5		4
1084Y-1-9S	9	43.3	37.5	18.8		
1084Y-1-10S	10	48.1	41.7	20.8		
1084Y-1-12S	12	-	50.0	25.0		


* Replace the "Y" by the letter referring to its voltage (refer to the following "Voltage index" as well as the "Model Number Structure" for further details).

CAPACITY & DIMENSIONS


Model	Storage Capacity			A	B	C	D	E	F	G	Est. Shipping Weight
	IMP gal.	Liters	US gal.	inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches (cm)	lb (kg)
All 108	61	279	74	3 1/8 (7.9)	51 3/8 (130.5)	59 5/8 (151.4)	4 7/8 (12.4)	60 7/8 (71.8)	28 1/4 (71.8)	24 (61)	285 (129.3)

Flexible Models - 108 (61 Imp. gallons)

Heavy Duty - 208, 240, 277 & 480 Volts



MODEL NUMBER STRUCTURE



VOLTAGE INDEX

A	208 Volts
B	240 Volts
D	480 Volts

SPECIFICATIONS

Model*	Input	Amperage			Phase	Number of elements
	kW	208 V	240 V	480 V		
HEAVY DUTY - 3, 6 or 9 elements						
1083Y-1-6S	6	28.8	25.0	12.5	1	3
1083Y-3-6S		16.7	14.7	7.2	3	
1083Y-1-9S		9	43.3	37.5	18.8	
1083Y-3-9S	25.0		21.7	10.8	3	
1083Y-1-12S	12		57.7	50.0	25.0	
1083Y-3-12S		33.3	28.9	14.4	3	
1083Y-1-13.5S		13.5	64.9	56.3	28.1	
1083Y-3-13.5S	37.5		32.5	16.2	3	
1083Y-1-15S	15		72.1	62.5	31.3	
1083Y-3-15S		41.6	36.1	18.0	3	
108XY-1-18S		18	86.5 [†]	75.0	37.5	1
108XY-3-18S	50.0 [†]		43.3	21.7	3	
1086Y-1-24S	24	115.4	100.0	50.0	1	6
1086Y-3-24S		66.6	57.7	28.9	3	
1086Y-1-27S		27	129.8	112.5	56.3	
1086Y-3-27S	74.9		65.0	32.5	3	
1086Y-1-30S	30		144.2	125.0	62.5	
1086Y-3-30S		83.3	72.2	36.1	3	
108XY-1-36S	36	173.1 ^{††}	150.0	75.0	1	6 or 9
108XY-3-36S		99.9 ^{††}	86.6	43.3	3	
1089Y-1-40.5S	40.5	194.7	168.8	84.4	1	9
1089Y-3-40.5S		112.4	97.4	48.7	3	
1089Y-1-45S		45	216.3	187.5	93.8	
1089Y-3-45S	124.9		108.3	54.1	3	
1089Y-1-54S	54		—	255.0	112.5	
1089Y-3-54S		—	129.9	65.0	3	

* Replace the "X" in the model number by the element quantity shown in the "Number of elements" column as well as the "Y" by the letter referring to its voltage (refer to the following "Voltage index" as well as the "Model Number Structure" for further details).

[†] For 208 V Models with a 18 kW input, only the 6-element configuration is possible.


^{††} For 208 V Models with a 36kW input, only the 9-element configuration is possible.

CAPACITY & DIMENSIONS

Model	Storage Capacity			A	B	C	D	E	F	G	Est. Shipping Weight
	IMP gal.	Liters	US gal.	inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches (cm)	
All 108	61	279	74	3 1/8 (7.9)	51 3/8 (130.5)	59 5/8 (151.4)	4 7/8 (12.4)	60 7/8 (155)	28 1/4 (71.8)	24 (61)	285 (129.3)

Flexible Models - 108 (61 Imp. gallons)

Heavy Duty - 600V / Three-Phase



SPECIFICATIONS				
Model	Input	Number of elements	Amperage	
	kW			
HEAVY DUTY - 600V				
1083C-3-6S	6	3	5.8	
1083C-3-9S	9		8.7	
1083C-3-12S	12		11.5	
1083C-3-13.5S	13.5		13.0	
1083C-3-15S	15		14.4	
1083C-3-18S	18		17.3	
1086C-3-18S	18	6	17.3	
1086C-3-24S	24		23.1	
1086C-3-27S	27		26.0	
1086C-3-30S	30		28.9	
1086C-3-36S	36		34.6	
1089C-3-36S	36	9	34.6	
1089C-3-40.5S	40.5		39.0	
1089C-3-45S	45		43.3	
1089C-3-54S	54		52.0	

CAPACITY & DIMENSIONS											
Model	Storage Capacity			A	B	C	D	E	F	G	Est. Shipping Weight
	IMP gal.	Liters	US gal.	inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches (cm)	inches (cm)	lb (kg)
All 108	61	279	74	3 1/8 (7.9)	51 3/8 (130.5)	59 5/8 (151.4)	4 7/8 (12.4)	60 7/8 (71.8)	28 1/4 (71.8)	24 (61)	285 (129.3)