

SAFETY DATA SHEET - DUCT SEAL



SECTION 1: Identification of the Substance/Mixture and of the Company

| | | |
|--|--|--|
| Product Identifier: Product Form: Mixture Product Name: DUCT SEAL | Manufacturer Details: Aeroseal LLC 225 Byers Road, Suite 1 Miamisburg, OH 45342 Tel: 1-877-349-3828 aeroseal.com | Emergency Telephone Number: Emergency number: 937-428-9300 |
| Intended Use of the Product: Sealing HVAC ductwork leaks only | | |

SECTION 2: Hazards Identification

Emergency Overview

Appearance: Milky white solution **Physical state:** Liquid **Odor:** Sweet

This product is a stable dispersion of very small polymer particles in water, surfactants, hydrocolloid stabilizers, and minor amounts of inorganic salts.

Potential Health Effects

| | | |
|-------------------------------------|--|--|
| Exposure Routes | Inhalation, skin / eye contact, ingestion | |
| Inhalation | May cause irritation to respiratory tract | |
| Skin Contact | May cause slight skin irritation | |
| Eye Contact | May cause slight eye irritation | |
| Ingestion | Unknown – Safe handling and hygiene practices are recommended to avoid ingestion | |
| Aggravated Medical Condition | Pre-existing disorders of the following organs (or organ systems) may be aggravated by exposure to this material – skin, upper respiratory tract, lung (for example, asthma-like conditions) | |
| Symptoms | Signs and symptoms of exposure to this material through breathing, swallowing, and/or prolonged contact of the material through the skin may include, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), lung irritation, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), difficulty in breathing, lung edema (fluid buildup in the lung tissue) | |

SECTION 3: Composition

| Name | CAS No. | %(w/w) |
|-------------------------|--------------|---|
| Vinyl Acetate Copolymer | Trade Secret | 35% max |
| Vinyl Acetate Monomer | 108-05-4 | ~ 0.019% <0.0093% (after application – when dried) |

SECTION 4: First Aid Measures

| | |
|---------------------|---|
| General | Never give anything by mouth to an unconscious person. If you feel discomfort, seek medical advice (show the label where possible). |
| Inhalation | Not expected to present a significant inhalation hazard under anticipated condition of normal use. When symptoms occur, move exposed person to fresh air at once. Administer artificial respiration if breathing has stopped. Keep at rest. Call for medical attention. |
| Skin Contact | Not expected to require first aid measures. Immediately flush contaminated skin with water and wash with soap and water. |
| Eye Contact | Immediately flush with water for at least 15 minutes with eyelids apart to ensure irrigation of eye and lid tissues. Remove contact lenses, if present. Get medical help if redness, pain, or irritation persists. |
| Ingestion | Rinse mouth. Small ingested amounts are not expected to produce adverse health effects. Amounts larger than 1 fl. oz. should be recovered from stomach by aspiration. Immediately call a POISON CENTER or doctor/physician. |

Most Important Symptoms and Effects

| | |
|---------------------|---|
| General | Effects of exposure (inhalation or ingestion or skin contact) to substance may be delayed |
| Inhalation | In large amounts may cause irritation in respiratory tract |
| Skin Contact | Product is not irritating to skin |
| Eye Contact | Redness and blurred vision |
| Ingestion | Unknown |

SECTION 5: Firefighting Measures

| | |
|----------------------------|---|
| Fire Hazard | Product is not flammable |
| Explosion Hazard | Product is not explosive |
| Extinguishing Media | Use extinguishing media appropriate for surrounding fire or dry chemical, Carbon-dioxide (CO ₂). Exercise same caution as when fighting any chemical fire. Do not enter fire area without proper protection gear, including eye and respiratory protection. |
| Unusual Hazards | When polymer burns, water, carbon-dioxide, carbon monoxide, and smoke are produced. Pyrolysis products may include such materials such as acetic acid, acrolein, and acetaldehyde. |

SECTION 6: Accidental Release Measures

Prevent additional discharge of material, if possible to do so without hazard. Soak up small spills with sand, earth absorbent or inert material. Scoop up and place in clean, dry, and marked container. Flush away residue with large quantities of water. Pump large spills into marked containers for prompt disposal.

Personal Precautions, Protective Equipment and Emergency Procedure

Refer to Section 8 for personal protective equipment (PPE)

For Emergency Personnel

Equip clean-up crew with proper protection
Ventilate area

SECTION 7: Handling and Storage

Precaution for Safe Handling

Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

Conditions for Safe Storage, Including Any Incompatibilities

Store away from heat and strong oxidizing agents and acids. Use in well-ventilated areas only. Keep product in original container and at above 32°F.

SECTION 8: Exposure Control/Personal Protection

Exposure Controls

Ventilation Ventilation is always recommended to maintain the vapor concentration below the ACGIH TWA (10ppm Vinyl acetate)

Personal Protective Equipment

Respiratory Protection Use NIOSH/ MSHA approved filter or respirator where vapor or mist is generated

Eye Protection Wear safety glasses with side shields or chemical goggles, if splash may occur

Protective Gloves Chemically resistant gloves to minimize skin contact



SECTION 9: Physical and Chemical Properties

| Information on Basic Chemical and Physical Properties | |
|---|------------------------------------|
| Physical State | Liquid |
| Appearance | Milky white |
| Odor | Sweet |
| Odor Threshold | Not available |
| pH | 3.8-4.2 |
| Relative Evaporation Rate | Not available |
| Melting Point | Not available |
| Freezing Point | <0oC (32oF) |
| Boiling Point | 100oC (212oF) |
| Flash Point | Does not Flash below boiling point |
| Auto-ignition Temperature | Not available |
| Decomposition Temperature | Not available |
| Flammable (solid, gas) | Not available |
| Lower Flammable Limit | Not available |
| Upper Flammable Limit | Not available |
| Vapor Pressure | 17.54 mm Hg @ 20oC (68oF) |
| Relative Vapor Density at 20oC | Not available |
| Relative Density | 0.98-1.05 @ 25oC (77oF) |
| Density | 8.2-8.8 lb/gal |
| Specific Gravity | Not available |
| Solubility | Water: soluble 20oC (68oF) |
| Low Pow | Not available |
| Low Kow | Not available |
| Viscosity, Kinematic | Not available |
| Viscosity, Dynamic | >1 @ 20oC (68oF) |
| Explosion Data – Sensitivity to Mechanical Impact | Not available |
| Explosion Data–Sensitivity to Static Discharge | Not available |

SECTION 10: Stability and Reactivity

| | |
|---|--|
| Chemical Stability | Product is stable. |
| Conditions to Avoid | Coagulation may occur following freezing, thawing, or boiling. Avoid direct sunlight or extremely hot or cold conditions. |
| Incompatible Materials | Strong oxidizers, bases, alkali materials such as sodium or metal hydrides. |
| Hazardous Reactions | Product will not undergo hazardous polymerization. |
| Hazardous Decomposition Products | When polymer burns, water, carbon dioxide, carbon monoxide, and smoke are produced. Pyrolysis products may include acetic acid and irritating toxic fumes. |

SECTION 11: Toxicological Information

| Product: Duct Seal | |
|--|--|
| Acute Toxicity | Not classified |
| LD50 and LC50 Data | Not available |
| Skin Corrosion/Irritation | Not Classified |
| pH | 3.8-4.2 |
| Serious Eye Damage/Irritation | Not classified |
| Respiratory or Skin Sensitization | Not classified |
| Germ Cell Mutagenicity | Not classified |
| Teratogenicity | Not available |
| Carcinogenicity | Not classified |
| Specific Target Organ Toxicity (Repeated Exposure) | Not classified |
| Aspiration Hazard | Not classified |
| Symptoms/Injuries After Inhalation | Inhalation in large amounts may cause irritation |
| Symptoms/Injuries After Skin Contact | Product is not irritating to skin |
| Symptoms/Injuries After Eye Contact | Product not considered to be irritating to eyes, but may cause redness or blurred vision |
| Symptoms/Injuries After Ingestion | May be harmful if ingested in large quantities |

| Ingredient: Vinyl Acetate Monomer (108-05-4) | |
|--|---------------------------------|
| LD50 Oral Rat | 2920 mg/kg |
| LD50 Dermal Rat | 2320 mg/kg |
| LC50 Inhalation Rat | 11400 mg/m3 (Exposure time: 4h) |
| ATE (dust, mist) | 1.5 mg/l/4h |

| Product: Duct Seal | |
|--------------------|-------------------|
| Toxicity | Not classified |
| Mobility in soil | No data available |

Ingredient: Vinyl Acetate Monomer (108-05-4)

| | |
|------------|--|
| LC50 Fish1 | 14mg/l (Exposure time 96h- Species: Pimephales promelas [static]) |
| LC50 Fish2 | 15.04-21.54 mg/l (Exposure time: 96h- Species: Lepomis macrochirus [static]) |
| Log Pow | 0.73 |

SECTION 12: Ecological Information

Other Information: Avoid release to environment.

SECTION 13: Disposal Consideration

Dispose of waste material in accordance with all local, regional, national, provincial, territorial, and international regulations.

| | |
|---------------------------|---------------|
| In Accordance with D.O.T. | Not Regulated |
| In Accordance with IMDG | Not Regulated |
| In Accordance with IATA | Not Regulated |
| In Accordance with TDG | Not Regulated |
| Unit Container | 1 Gallon |

| | HMIS Hazard Rating |
|---------------------|----------------------------------|
| Health | 1 |
| Flammability | 0 |
| Physical Hazard | 0 |
| Personal Protection | E (safety glasses, gloves, mask) |

| | NFPA Fire Diamond |
|------------------------|-------------------|
| Health | 1 |
| Flammability | 0 |
| Instability/Reactivity | 0 |
| Special Notice | N/A |

SECTION 14: Transport Information

HMIS Legend:

0: Minimal Hazard

1: Slight

2: Moderate

3: Serious

4: Severe

Refer to HMIS III by ACA for exact definition

SECTION 15: Regulatory Information

NFPA Legend:

0: No Hazard

1: Slight

2: Moderate

3: Serious

4: Severe

Refer to NFPA 704 standard for exact definition

U.S. Federal Regulations

Product: Duct Seal

California Proposition 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, defects, or other reproductive harm.

Ingredient: Vinyl Acetate Monomer (108-05-4)

Listed on the United States TSCA inventory

Listed on SARA Section 302

Listed on SARA Section 313

SARA Section 302 – Threshold Planning Quantity (TPQ): 1000

SARA Section 313 – Emission Reporting: 0.1%

SECTION 16: Other Information

Document Prepared by: Aeroseal LLC (Tel- 1-877-349-3828)

Revision date: 02/02/2023

Notification Status

| | |
|---|-----------------------|
| United States. TSCA list | Y (Positive listing) |
| Canada. Canadian Environmental Protection Act Domestic Substances List (DSL) (Can. Gaz. Part II, Vol. 133) | Y (Positive listing) |
| Australia. Industrial Chemical (Notification and Assessment) Act Japan. Kashin-Hou Law List | N (Negative listing) |
| Korea. Toxic Chemical Control Law (TCCL) list | N (Negative listing) |
| Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act | N (Negative listing) |
| China. Inventory of Existing Chemical Substances | N (Negative listing) |

This document has been prepared in accordance with SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 (g). The information provided herein is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. The information is related only to the specific material designated and may not be valid for such material used in combination with other materials or in any processes, unless specified in the text.

No warranties of any kind, either expressed or implied are made regarding products described or information set forth, or that the products, design, data or information may be used without infringing the intellectual property rights of others.

Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstance.

This document is available for download at: www.aeroseal.com/sds



aeroseal.com