RUBOTA 4WD DIESEL UTILITY VEHICLE RUBOTA 4WD DIESEL UTILITY VEHICLE Series







Get ready for an advanced RTV experience.

Kubota RTVs have been the best-selling diesel utility vehicles in North America since 2004.* And no wonder. Each year, they set the standard for ruggedness and reliability, proving themselves ready to work day after day under all kinds of conditions.

Well, the best just got a whole lot better. Meet the latest Kubota RTV-X Series, four rough-andready RTV's models that raise the bar on comfort, convenience, and performance.

It's an advanced driving experience, with a smoother ride, better driveability, more legroom, and improved ergonomics throughout.

Ready for an RTV experience you won't forget anytime soon? Visit your Kubota dealer today and experience for yourself the all new RTV-X Series.

*Power Products Marketing North American Utility Vehicle Market Reports

KUBOTA 4WD DIESEL UTILITY VEHICLE

RTV-X Series

The Kubota RTV X-Series. Dependable performance, excellent

When there's work to be done on the far side of nowhere, you need a vehicle that can get you there quickly, get the job done efficiently, and get you back comfortably.

ENTAX SIGNO

Comfort and versatility make this Kubota's most popular model for all types of jobs. It comes with a powerful 21.6 HP diesel engine and your choice of Kubota Orange or Realtree AP Camo styling.

RTV-X1120D

A step up in power, torque, performance, and style, the RTV-X1120D has everything you need to get the job done, including a rugged and dependable 24.8 HP diesel engine and handsome blue-tinted halogen headlights.







Power when and where you need it

Even when the path disappears, you can rely on the RTV-X Series' powerful diesel engines to keep you moving forward. Kubota-built and trail-proven, these 3-cylinder liquid-cooled diesel engines have a well-earned reputation for dependable performance even in the harshest terrains. The RTV-X900 comes with a robust 21.6 HP engine, while the RTV-X1120D, RTV-X1100C and RTV-X1140 provide an extra boost of power from 24.8 HP engines.







RTV-X900

VHT-X (Variable Hydraulic Transmission)

Kubota has more experience in variable hydraulic transmissions than any other Utility Vehicle manufacture. The engine torque is maximized through the advanced variable displacement HST motor, resulting in a wider torque band. The Large oil cooler enhances the VHT-X's performance and durability through cooler operating temperatures.



Two-speed In-line Shift

You'll shift less often and maintain better control, thanks to new transmission gearing with just two forward speeds (high and low), plus neutral, and reverse.



Strong High-rigidity Frame

The high-rigidity steel frame isolates the occupants from noise, vibrations, and harshness. With structural strength that few in the industry can match, this durable frame

can take years of punishment from heavy loads and rough terrain.

20% Larger, Clogresistant Radiator

Open the hood, and you'll find the radiator and air-intake located high and up front, where the air is cleaner and cooler. This improves both radiator performance and simplifies maintenance. Kubota's wide fin pitch design minimizes clogging, further improving radiator performance.





Get in and buckle up. You're about to experience an advanced level of driving performance.

Front & Rear Extra Duty Independent **Suspension**



Regardless of the terrain or load, independent suspension on all four wheels ensures a truly exceptional ride. **Kubota's Extra Duty IRS (Independent** Rear Suspension) technology also sets a new standard for durability.





Height-adjustable Front and Rear Suspension

Whether you've got a heavy load or no load at all, adjustment of the front and rear suspension height will ensure the proper vehicle height for a smooth ride and optimum driveability for hard to get to work environments.

High Ground Clearance


The X-series raises the bar on ground clearance—to a full 10.4" with 8" of suspension travel—letting you glide over the bumps rather than through them.

Limited-Slip Front Differential

True 4-wheel drive with a limited-slip front differential and a locking rear differential help reduce wheelspin to a minimum, giving you greater control and a smoother ride on rough or muddy terrain.

CV Joint **Protectors** and **Skid Plates**

Obstacles on the path? CV joint protectors and heavyduty skid plates will protect the most critical parts of the engine and transmission.



Multi Wet Disc Brakes / Dynamic **Braking**

The RTV-X series uses Multi-disc wet brakes which provide longer brake life. You'll also feel more secure. especially when traveling down long inclines, knowing that dynamic braking is providing additional braking power and greater driving control.







60:40 Split-bench Seats

The split-bench style seat is ergonomically designed to provide hours of working comfort. The driver's side is adjustable fore and aft.*

*Driver's side seat adjuster is not available on RTV-X900 General Purpose models.



Easily accessible Parking Brake

The parking brake is conveniently located on the dashboard for easier access as well as more legroom.



Power Steering

Responsive hydrostatic power steering gives you the control you need to tame any terrain. The steering wheel is tilt-adjustable, allowing you to set the optimum angle for your driving style.*

*Tilt-feature is not available on RTV-X900 General Purpose models.



Glove Box*

A large glove box on the passenger side provides fast access to critical tools and personal effects.


*Glove box is not available on RTV-X1100C models.

*Glove box cover is optional on RTV-X900 General Purpose models.



Digital Meter Cluster

Bright, with large, easy-to-read indicators, this digital meter cluster keeps you informed of all critical driving conditions, including speed, hours, and miles traveled. An Overheat Alarm (light and audio) helps prevent engine damage.



Under-seat Storage Compartments

Large compartments under the split-bench seats provide plenty of convenient storage space for tools, tie-downs, and personal items.

he capacity for hauling, the strength for towing. Carry up to 15.2 cubic feet of cargo It's not enough to get you there and back. You need to get your stuff there and back, as well. This heavy-duty steel cargo box can do that for you, carrying up to a halfton (1,102 lbs.) of tools, firewood, gear, supplies...whatever you need to haul from here to there and back again. Cargo tie-down hooks help keep your gear secure. **Dumping Cargo Box*** With the flick of a single lever, the hydraulic-lift cargo box rises and your cargo slides out. Cargo that could take significant physical strength and time to unload can now be dumped with little effort in mere seconds. *Manual dumping on RTV-X900 General Purpose model.

*Photo with factory installed Spray-on Bedliner option.



Get ready for an advanced level of comfort and performance. Get rea

Here's the one you've been waiting for. The one with more of everything.

More power, more torque, more performance, more style. We call it the RTV-X1120D. You'll call it amazing.

More powerful engine and transmission

For jobs that require extra acceleration and climbing power, the RTV-X1120-series are the obvious choice. They pack both Kubota's proven 24.8 HP diesel engine and the reliable VHT-X transmission, which provide a top speed of 29 mph as well as plenty of hillclimbing power.









RTV-X1120

Three-point Seatbelts

With the RTV-X1120D's increased speed comes increased dynamic loads; so you and your passenger are strapped in with three-point seatbelts.

Half Door

Half doors on the driver and passenger sides help keep out the dirt, brush, and other external objects, while letting you enter and exit with ease.



Alloy Wheels

You'll travel in style with these good-looking, machine-polished alloy wheels.* Clear Coating

helps keep them bright and shiny.

*Realtree AP Camo model features black alloy wheels with polished outer surfaces.



So comfortable, so fun to drive, you'll find excuses to take it for a spin.



Premium Grand Cab

Whether it's hot and humid, cold and windy, or raining cats and dogs, you'll stay dry and comfortable inside the RTV-X1100C's quiet and luxurious air-conditioned and heated cab. Built around a unibody frame that is virtually airtight, soundproof, and rattle-free, the cab incorporates highly efficient air-conditioning, heating, and defogging functions, as well as antennas and speakers for an optional radio. And when the weather is nice? Just roll down the fully opening windows. This truly is the best all-weather, all-comfort, all-the-time working environment you'll ever experience on the trail.



MFORT CAB

RTV-X1100C

Air Conditioner and Heater

Hot or cold, rain or shine, the temperature inside can always be just right for you. The air conditioner, defroster, and heater system are powerful, efficient, and standard equipment on the RTV-X1100C.





Unibody Cab and Chassis Frame

You'll enjoy a smoother, quieter, more comfortable ride, thanks to the RTV-X1100C's integrated unibody cab and chassis frame. They form a rigid yet lightweight unit that is rugged, airtight, lownoise, and rattle-free. Even more impressive, the



Versatility & Performance. Front PTO attachment options for RTV-X1100.



RTV-X1100C



Power Module & PTO K-Connect

K-Connect is fast & reliable connection system with high quality LED light, 4 point hitch and optional grill guard, can easily be removed for seasonal storage. The PTO is gear box driven for durability and precision, and fittings are accessible greaseable for preventative maintenance.



LED lights



4 point hitch



Optional front grill adaptor kit



Control handle & PTO switch.

Simple intuitive control for all implements.



Snowblower 66'

Professional grade snowblower has 66' wide two stage for commercial use. Equipped with a four blade fan for superior performance, this snowblower throws snow farther than the competitors. The hydraulic chute rotation and deflection is standard.



Sweeper 66'

66' wide PTO driven sweeper turns at more than 240 rpm. Standard polyethelene brushes loaded with 34 (24' diameter) wafer brushes that can easily be replaced within 20 minutes



V-Plow 78'

78' wide plow designed for heavy duty application, to accomodate the width of the RTV-X1100C when fully angled at 30

degrees. A double acting cylinder on each wing for true back dragging action.



Straight Blade 78'

78' wide blade you can rely on.
New curvature offers better role of
the snow. Operators can use it in
float or down pressur
better performance.



RTV-X1140

From industry-leading cargo capacity to comfortable seating for four adults in three simple steps that can be performed easily by just one person.

[K-vertible™] Kubota's unique system to convert vehicle from 1 row to 2 row seating less than a minute.







Reposition the sides of the bed

Swing the front side panels of the cargo bed towards the back of the bed and fold down the front panel.

2 Reposition the cargo bed

Next, lift the front of the cargo bed and secure it.

Reposition the protective screen and bench seat

Next, move back and secure the protective screen with back rest. Finally, lower and secure the bench seat. Reverse these three steps to restore the RTV-X1140's full-length bed.

A variety of standard and optional features to let you work productively

Newly Designed ROPS

The poles at the rear have been eliminated for a cleaner look and easier cargo loading from the sides in the 2-seat configuration. A 5th pole has been added in the rear middle of the frame to ensure the same high level of ROPS performance that meets the SAE J2194 and OSHA 1928 ROPS standards.



More Comfortable Rear Seat

More legroom for the backseat passengers means more comfort and less fatigue, especially on long journeys. Your crew will arrive fresh and ready for action.



Standard Hydraulic Dump Bed

Dump sand, gravel, turf, or just about anything you can think of, from the RTV-X1140's whopping, 19.1 cu. ft./9.9 cu. ft. (two-seat and fourseat configurations, respectively) capacity cargo bed. An easy-to-operate lever activates this hydraulic bed-lift system in either two or fourseat configuration.



and travel comfortably.

RTV-X1140



A variety of optional cab and accessories further improve comfort, safe



■ Metal FOPS Canopy (RTV-X900 & RTV-X1120D only) VC5000



■ Plastic Canopy (RTV-X900 & RTV-X1120D only – Shown with VC5056 LED Strobe Light) VC5011



Laminated Windshield (RTV-X900 & RTV-X1120D only)
VC5020



■ Tempered Glass Windshield (RTV-X900 only)
VC5025



■ Poly Windshied (RTV-X900 & RTV-X1120D only) VC5023



■ Metal Doors with sliding windows (RTV-X900 & RTV-X1120D only)

VC5090 - Black

VC5091 - Orange



■ Rear Panel (RTV-X900 & RTV-X1120D only – Shown with optional rear worklights and flashers) VC5040



■ RTV Mirror Kit
(RTV-X900 & RTV-X1120D only)
VC5076



■ Dome Light (RTV-X900 & RTV-X1120D only) VC5053



■ Wiper (RTV-X900 & RTV-X1120D only) VC5030



■ LED Front Worklights (x2) (RTV-X900 & RTV-X1120D only) VC5050



■ Rear Work Light
(RTV-X900 & RTV-X1120D only)
VC5051

ty and convenience.



■ Strobe Light

VC5056 - RTV-X900 & RTV-X1120D

VC5058 - RTV-X1100C



■ RTV Mirror Kit (RTV-X1100C only) V5059 – Cab




■ 72" General Duty Straight Blade with Quick Hitch V5008



■ Commercial 72" Hydraulic Straight Blade V5290



■ Commercial 72" V-Blade V5291



■ 60" Hydraulic Rotary Broom V5260



■ Front Hydraulic Quick Hitch V5289



■ Hydraulic Control & Valve System V5232 – 2-function Control & Valve V5233 – 3-function Hydraulic Valve Upgrade Kit (not shown)



■ Cargo Box Spreader (RTV-X900 & RTV-X1100C only) V5005



■ Winch Kit (4,000lbs capacity) V5244



■ Trailer Hitch Ball Mount Kit V5200



■ Turn Signal/Hazard Light Kit V5237

SPECIFICATIONS

Model				RTV-X900 General Purpose	RTV-X900 W	/orksite	RTV-X1120 General Purpose	RTV-X11	20 Worksite
Body color			Kubota Orange	Kubota Orange	Realtree® AP Camo	Kubota Orange	Kubota Orange		
	Make			9	KUBOTA D902-E4-UV				
	Туре			3-0	cylinders, 4-cycle, diesel, OHV				
Engine			cu.in (cc)	54.8 (898)					
Engine	· · · · · · · · · · · · · · · · · · ·		HP (kW)/rpm		21.6 (16.1)@3200				
			111 (NV1)/1-P111		Liquid				
-	Cooling system Battery				560 CCA				
Transmission	Dationy				000 0071				
Gear selection									
Max. traveling speed			mph (km/h)		0-25 (0-40)		1		0-29
	Front differential		mpn (mn/n/		0 20 (0 40)				0 =0
4WD system	Rear differential								
Ctooring	Real unierential								
Steering Brakes	Front / Rear								
Dianes	Parking brake								
									Independent,
}	Front suspension		:- (m)					ļ	Inaepenaem,
Suspension	Front suspension tra	avel	in. (mm)						
-	Rear suspension		. , ,						
	Rear suspension tra	ivei	in. (mm)						0 F (060)
Ground clearance			in. (mm)						0.5 (266)
	Rear in. (mm)		in. (mm)				1		0.4 (263)
Headlights	-		. , .		Two 37.5 Watt halogen		Two 37.5 Watt blue-tint		
Occupant Protective	Tubular overhead structure in. (mm)		in. (mm)				2.0 (50.8) steel tube		
System (OPS)	Seat belts				2-point				3-
	Certification				J2194 and OSHA 1928 ROPS			SAE J219	4 and OSHA
ļ	Length		in. (mm)	120.3 (3055)	122.5 (3	110)	120.3 (3055)		
ļ	Width		in. (mm)				63.2 (1605)		
	Height, overall in. (mm)		, ,				79.5 (20		
Dimensions	Front tread centers in. (mm)		in. (mm)					48	3.8 (1240)
			in. (mm)						3.8 (1240)
	Wheelbase in		in. (mm)				80).5 (2045)	
	Turning radius		ft. (m)					1	3.1 (4.0)
Weight			lbs. (kg)	1907 (865)	1973 (8	95)	1995 (905)		
Towing capacity			lbs. (kg)						
Payload capacity			lbs. (kg)	1664 (755)	1598 (7	25)			1510
Cargo bed	Material								
	Width × Length × Depth in. (mm)		in. (mm)					57.7 (1465) × 4	40.5 (1030) ×
ļ	Volume		cu. ft. (m ³)					15	5.2 (0.43)
ļ	Bed height (unloaded)		in. (mm)						4.9 (887)
<u> </u>	Cargo bed load		lbs. (kg)						102 (500)
	Dumping system		. 3/	Manual	Hydro pow	ver lift	Manual		
Fuel tank capacity	, 3 - 7		U.S. gals (ℓ)		7: - F				
Sound rating at operator	or's ear at max rpm		dB. (A)		85				
Tires	Front and rear	ATV	` '						
		HDWS				25 × 10-12, 6-ply			
		TURF		25×10-1	2 4-ply	25 × 10 12, 0 pty			
Front guard design			Simple, center only	Center and I	humner	Simple, center only	Conto	er and bumper	
Alloy wheel (not availab	ole with Turf tire\			Simple, certier only	Center and I	· · · · · · · · · · · · · · · · · · ·		Cente	and bumper
	Jie With Full tile)						Opt.		
				0	a		0.1		
Hydraulic bed lift Spray-on bed liner				Opt.	Std. Opt.		Opt.		Opt.

	RTV-X1	120 Deluxe	RTV->	(1100C	RTV-X114	RTV-X1140 Worksite		
Realtree® AP Camo	Kubota Orange	Realtree® AP Camo	Kubota Orange	Realtree® AP Camo	Kubota Orange	Realtree® AP Camo		
		KUBOTA D1105-E4-UV			·			
		3-cylinders, 4-cycle, diesel, OH	V					
		68.5 (1123)						
		24.8 (18.5)@3000						
		Liquid						
		670 CCA						
Variable hydro trar	nsmission (VHT-X)							
Hi-Lo range forwar	d, neutral, reverse							
0-46.4)				0-2	5 (0-40)			
Limited-slip	differential							
Foot operated of	differential lock							
Hydrostat	tic power							
Wet-disc	brakes							
Rear wheel, h	and operated							
Dual A-arms with a	djustable spring preload							
8 (2	205)							
Independent with	n coil over shock							
8 (2	205)							
					11.2	(285)		
					9.4	(240)		
alogen, optical axi	s adjustment			Two 37.5	Watt halogen			
<u> </u>			2.4 x 2.4 (61 x 61)	deformed steel tube		steel tube		
oint			(/		-point			
928 ROPS and AN	JSI B71 9				OSHA 1928 ROPS			
020 1101 0 4114 711		5 (3110)		5, t2 52 15 + tilla		(3610)		
	 -	- (- : - :)	65.4	(1660)		(1605)		
				(2090)		(2025)		
				(====)		(1280)		
						(1280)		
						(2495)		
2061	(025)		2370 (1075) 17.1 (5.2)			(3.2)		
1300				237	0 (1073)			
685)	(390)			160	29 (739)			
Ste	201			102	(739)			
1.2 (285)	56 1				Long: 57.7 (1465) × 51.1 (1300) × 11.2 (285)	/ Chart E7 7 (146E) v 06 0 (660) v 11 0 (06		
1.2 (203)								
						/ Short: 9.9 (0.28)		
						(900)		
					Long: 1102 (500)	/ Short: 661 (300)		
	(00)	Hydro	power lift					
7.9	(30)		-	20		<u> </u>		
84			3	33		34		
25 × 10-								
<u> </u>	25 × 10-12, 6-ply	_		25 × 1	0-12, 6-ply			
			25 × 10-12, 4-ply					
		Center, bum			Center and bumper (Orange model) / 0			
		Std.	0	pt.	Opt. or Std. (Orange mo	del) / Opt. (Camo model)		
		S	d.					
		Std.	Opt.					

*"Realtree®" is a registered trademark of Jordan Outdoor Enterprises, Ltd. The company reserves the right to change the above specifications without notice. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. For off-highway use only.

Kubota Canada Ltd. reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, sately and product information, consult your local Kubota dealer and the operator's manual. Power (HPPKW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for Canada only. For information regarding Kubota Corporation's global web site. Kubota does not provide parts, warranty or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or services for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

KUBOTA CANADA LTD.

Head Office: 1155 Kubota Drive, Pickering, Ontario, L1X 0H4 TEL: 1 800-405-6916

Visit our web site at: www.kubota.ca



©2021 Kubota Corporation

