

# UNPARALLELED IMPLEMENT VERSATILITY

Kubota's narrow tractors are equipped with an extensive selection of performance-matched implements, purpose-built to conquer your most challenging tasks with ease.

**ROTARY CUTTERS**

**ROTARY TILLER**

**BOX BLADE**

**CULTIVATOR**

**SPREADER**

**REAR BLADE**

**MOLDBOARD PLOWS**

**AND MORE!**



# 0-50 HP B/LX/L NARROW TRACTORS

THE ULTIMATE SOLUTION FOR NURSERIES, VINEYARDS, AND ORCHARDS



Descriptions, specifications, images, colours and accessories contained in this brochure are based on information believed to be correct at the time this publication was approved for printing. Although descriptions, specifications, images, colours and accessories are believed to be correct, accuracy cannot be guaranteed. Errors and omissions excepted. Kubota Canada Ltd. reserves the right to change the stated specifications, colours and accessories without notice. Some items shown may be optional and some products shown may not be available at all dealerships. This brochure is for informational purposes only. To the fullest extent permitted by law, Kubota disclaims all representations and warranties, express or implied, as well as any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the Canadian market only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global website. Kubota does not provide parts, warranty or service for any product which is re-sold or retailed in any country other than the country for which the product(s) were designed or manufactured.

**Kubota Canada LTD.**

Head office: 1155 Kubota Drive, Pickering, ON L1X 0H4

NARROW-CUT-24-EN / Nov 24



# THE ULTIMATE SOLUTION FOR NURSERIES, VINEYARDS, AND ORCHARDS

Are you tired of working with tractors that are too bulky for your property or lack the power to handle specialized tasks? Kubota's Narrow Tractor models offer the perfect solution for the unique demands of nurseries, vineyards, and orchards. Our tractors are built to navigate tight spaces, providing you with the power, control, and durability you need.

B2401DTN	LX3520DTN	L4802DTN
		
35.4"	39.4"	52.7"
<b>Pump Capacity:</b> 16.6 L/min (4.4) gals/min	<b>Pump Capacity:</b> 19.7 L/min (5.2) gals/min	<b>Pump Capacity:</b> 29.4 L/min (7.8) gals/min
<b>Perfect Fit For Nurseries, Vinyards, Orchards, Vegetable Farms</b> Mowing, Spraying, Weeding		

## WHY CHOOSE KUBOTA?

### 1. Tailored to Your Needs

#### Perfect Fit

Kubota's narrow design allows you to work within tight spaces while maintaining full power and control.

#### Strong Hydraulic Capacity

Achieve maximum performance for all attachments, whether spraying, mowing, or towing and weeding.

#### Effortless Control

The 12-grade gear shift drive delivers smooth operation for any task, while the LX3520DTN's draft control ensures efficiency when towing.

### 2. Quality You Can Trust

#### Compact Size, Uncompromising Power

The compact design doesn't mean sacrificing power. With horsepower ranging up to 48.4, Kubota's narrow tractors provide the strength you need in a small package.

### 3. Comfort and Ease of Use

#### Ergonomic Layout

Designed for long hours, Kubota's tractors provide maximum comfort with intuitive controls and reduced vibrations.

#### Foldable ROPS

Need to work under low trees or store in tight spaces? Our foldable center ROPS make it easy to operate and store the tractor.

Model		B2401DTN	LX3520DTN	L4802DTN
<b>PTO Power</b>				
KW (HP)		14.3 (19.2)	22.1 (29.6)	30.2 (40.5)
<b>Engine</b>				
Engine gross power	<i>kW (HP)</i>	16.3 (21.9)	26.0 (34.9)	36.1 (48.4) / 2600
Manufacturer		Kubota	Kubota	Kubota
Model		D1105-E4-D35	V1505-CR-TE5-D40R6	V2403-CR-E5
Type		E-TVCS, liquid cooled, 4-cycle diesel	Direct injection, Vertical, water-cooled, 4 cycle diesel	Direct injection, Vertical, Water-Cooled, 4 cycle diesel
Number of Cylinders		3	4	4
Bore and Stroke	<i>mm (in.)</i>	78x78.4 (3.1x3.1)	78x78.4 (3.1x3.1)	87 x 102.4 (3.4 x 4.0)
Total Displacement	<i>cm³ (cu.in.)</i>	1123 (68.5)	1498 (91.4)	2,434 (148.5)
Rated Revolution	<i>rpm</i>	2600	2600	2600
Maximum Torque	<i>N-m (ft.-lb)</i>	71.7 (52.9)	117.5 (86.8)	152.8 (112.7)
<b>Capacities</b>				
Fuel Tank	<i>L (U.S.gals.)</i>	23 (6.1)	32 (8.5)	51 (13.5)
Engine Oil (with filter)	<i>L (U.S.gals.)</i>	3.1 (0.8)	4.7 (5.0)	8.2 (8.7)
Engine Coolant	<i>L (U.S.gals.)</i>	3.9 (1.0)	4.3 (4.5)	6.5 (6.9)
Transmission Case	<i>L (U.S.gals.)</i>	12.5 (3.3)	21.0 (5.5)	40 (10.6)
<b>Dimensions</b>				
Overall Length (without 3P)	<i>mm (in.)</i>	2360 (92.9)	2494 (98.2)	2990 (117.7)
Overall Width (minimum tread)	<i>mm (in.)</i>	900, 990 (35.4, 39.0)	1000 (39.4)	1365 (53.7)
Overall Height	<i>mm (in.)</i>	(with ROPS) 1910 (75.2)	2134 (84)	With ROPS - 2410 (94.9) Top of Steering Wheel - 1425(56.1)
Wheel Base	<i>mm (in.)</i>	1560 (61.4)	1550 (61.0)	1845 (72.6)
Minimum Ground Clearance	<i>mm (in.)</i>	300 (11.8)	325 (12.8)	295 (11.6)
Tread Front	<i>mm (in.)</i>	705 (27.8)	842 (33.1)	1055 (41.5)
Tread Rear	<i>mm (in.)</i>	700, 790 (27.6, 31.1)	778 (30.6)	1050 (41.3)
<b>Weight</b>				
kg (lbs.)		(with ROPS) 605 (1334)	977 (2154)	(with ROPS) 1525 (3362)
<b>Clutch</b>				
		Dry Single Plate	Dry Single Plate	Dry Type Single Stage
<b>Travelling System</b>				
Tires (Turf) Front / Tires (Turf) Rear		5-12 / 8-16	6-14 / 8.3-24	7.2-16 / 11.2-24
Steering		Integral type power steering	Hydraulic Power Steering	Hydrostatic Power Steering
Transmission		Gear Shift, 9 Forward and 3 Reverse	12 Forward and 12 Reverse Synchronized Main Gear Shift and Mechanical Shuttle Transmission	Gear Shift, 8 Forward and 8 Reverse
Brake		Wet Disk Type	Wet Disk Type	Mechanical, Wet Disk Type
Minimum Turning Radius (with Brake)	<i>m (feet)</i>	2.1 (6.9)	2.1 (7.5)	2.7 (8.9)
<b>Hydraulic Unit</b>				
Hydraulic Control System		Position Control	Position Control	Position Control
Pump capacity	<i>L/min (gals/min)</i>	3P: 16.6 (4.4)	3P: 19.7 (5.2)	29.4 (7.8)
3-Point Hitch		Category 1	Category 1	Category 1
Max. lift force - At Lift Points	<i>kg (lbs.)</i>	750 (1653)	1065 (2348)	1300 (2870)
600mm (24 in.) behind lift point	<i>kg (lbs.)</i>	590 (1301)	825 (1819)	1053 (2320)
<b>PTO</b>				
Rear-PTO		SAE 1-3 / 8, 6 spline	SAE 1-3 / 8, 6 splines	SAE 1-3/8, 6-splines
PTO / Engine speed	<i>rpm</i>	540/2505, 1000/2560	540 / 2530, 540E / 1850	540 / 2475