

## For Earth, For Life



# COMMERCIAL-GRADE MOWERS Stand-On

Whatever the job, from small to large, there's a Kubota stand-on mower offering professionals the durability, convenience, and performance they need.



## **COMMERCIAL STAND-ON MOWERS**

SZ Series

## Kubota Comfort and Productivity

Kubota Stand-On Mowers are some of the fastest machines in their class, while delivering superior comfort and durability. The mower deck delivers superior mowing performance that professionals demand. You'll be able to get more done in even the tightest spaces.

These Stand-On Mowers are designed to offer a smooth and easy ride, all while delivering high-end operational power and maneuverability. The SZ Series stand-on mowers feature the following:

- > All models are powered by Kawasaki commercial-grade engines, including an EFI option.
- > Adjustable reference bar and dampers give the operator a personalized experience.
- > Toolless adjustable tracking keeps you driving straight.
- > Kubota Stand-On Mowers provide exceptional transport speed, allowing maximum speeds of up to 17.70 kph.
- > The fuel tank is housed inside the control tower, protecting the fuel tank and allowing for a lower center-of-gravity design.
- > Wide and angled operator platform offers ample foot space, as well as the option of flipping up the platform to easily walk behind.
- > Accessible maintenance points reduces downtime.
- > Quick and easy cog/gear style deck level adjustments.
- > New ZERO T rear tire For better traction especially on side-hill operation.



### SZ19 / 36" Deck | SZ22 / 48" Deck | SZ26 / 52" Deck | SZ26 / 61" Deck





SZ Series	SZ19 / 36" DECK	SZ22 / 48" DECK	SZ26 / 52" DECK	SZ26 / 61" DECK		
Engine Type	Kawasaki FX600V	Kawasaki FX691V	Kawasaki FT730V-EFI	Kawasaki FT730V-EFI		
Horsepower (gross)*	19	22	26	26		
Fuel Capacity (I)	19.30		24.61			
Speed (KPH)	14.48	16.89 17.70				
Transmission	Hydro-Gear ZT3100		Hydro-Gear ZT3600			
Deck Type	Floating Fabricated Steel with Wear band					
Deck	7 ga deck with 7 ga skirts 10 Ga deck/7 ga skirt with adjustable front baffle					
Cutting Height	1.5–4.5"					
Starter	Electric					
Spindle Bearings	1" shaft with maintenance-free precision ground double-sealed bearings					
Deck Drive	Warner Mag Stop 125 ft-lb electric clutch Warner Mag Stop 200 ft-lb electric clutch					
Front Tires / Rear Tires	11 x 4-5 (no-flat) / 20 x 8-10	13"x6.5"-6 non flat / 23"x 8.5"-12	13" x6.5"-6" non flat	t / 23"x 10.5"-12"		
Brake	Cog Style Parking Lock / Hand Lever					
Weight (kg)	376.94	437.72	452.23	469		
Length / Height	62.5" / 45"		63.75" / 45.75"			
Warranty	2 Yr - Unlimited Hours					

\*These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.



#### GET YOUR STAND-ON ACCESSORIES

Accessory	SZ19-36	SZ22-48	SZ26-52	SZ26-61
Mulch Kit	SMK36-2	SMK48-2	SMK52-2	SMK61-2
Discharge Plate	SBP36-2	SBP48-2	SBP52-2	SBP61-2
Striping Kit		SSK48	SSK52-61	
Weight Kit	SWK36	SWK48		

Kubota Canada Ltd. reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KV) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for Canada only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



#### KUBOTA CANADA LTD.

Head Office: 1155 Kubota Drive, Pickering, Ontario L1X 0H4 TEL: (905) 294-7477

Visit our web site at: www.kubota.ca