




BD7510 15' & 20' NO-TILL DRILL

Introducing the new BD7510 Drill line, engineered specifically for no-till operators who need a mid-sized drill that folds to under 10' for ease of transport. Available in 15' and 20' working widths, BD7510 Drills are built to last.

BD7510 Drills feature a leading coultter to seed in nearly any condition and the trusted Great Plains Metering System that consistently meters large seed, small seed, and fertilizer – all through the main box of the drill. The innovative folding tongue design keeps the operator in the cab – even when switching between field and transport modes.

Features & Benefits



LEADING COULTER OPTIONS

Row units on the BD7510 utilize an integrally-mounted coultter to cut residue and prepare a mini seedbed ahead of the trailing double-disc opener. Coultter blade options include exclusive 5/8" Turbo coultter blades or 5/16" fluted coultter blades.



NARROW TRANSPORT DESIGN

Featuring hydraulic tongue latches, BD7510 15' and 20' drills are folded and unfolded by operating a single hydraulic lever from the tractor cab. All fold to under 10' for field-to-field, down-the-road, and through-the-gate convenience.



ROW SPACINGS & OPENERS

Row spacing options vary by working width. 15' models offer a choice of 6" or 7.5" spacing, while 20' models are offered in 7.5" spacing only. The 6" row spacing model utilizes an 07 Series opener, while those with 7.5" spacing use an 06 Series row unit. Both openers feature a leading coultter and row unit combination with the opener moving independently of the coultter. The double-disc blades are 13.5" in diameter, 4mm thick, and are offset 1/4". Triple-lip sealed bearings reduce maintenance and keep the blades operating smoothly. Depth is easily adjusted with an 18-position T-handle on each opener.

ADDITIONAL STANDARD FEATURES

- Up to 3.2 bu./ft. main box capacity
- Digital acremeter
- V-bottom dividers in main seed box
- Seed tubes and flaps
- Walkboard w/ steps
- Watertight manual holder
- Toolbox w/ calibration equipment
- LED safety lighting
- Quick disconnect seed hoses
- Automatic locks
- 2-point hitch

OPTIONS

- Native Grass box attachment
- Weights
- Small seeds box attachment
- Keeton® seed firmers
- Markers
- Smooth performance seed tubes
- Shaft monitor kit
- Work light kit
- Hand drill calibration tool
- Agitator

**to be offered by 2026*

15' & 20' No-Till Drill	Working Width	Engine H.P. Required	Row Spacing	Seed Box Capacity	Small Seeds Box	Native Grass Box Capacity
BD7510-15-3006	15'	150+	6"	46 bu.	7.5 bu.	15 bu.
BD7510-15-2475			7.5"			
BD7510-20-3275	20'	200+	7.5"	64 bu.	10 bu.	20 bu.

Specifications are subject to change without prior notification.
Images may not depict current or standard production models.