



Кубота

SNOW SOLUTIONS

MADE FOR CANADIANS





TABLE OF CONTENTS

6 | T
SERIES

8 | GR
SERIES


10 | F
SERIES

12 | BX & B01
SERIES

16 | LX
SERIES

20 | R, SVL, SSV
SERIES

24 | RTV
SERIES





YOUR SNOW REMOVAL SOLUTIONS

Getting the job done in winter weather is all about determination and adaptability. After all, no two snowfalls are the same. That's why Kubota's snow removal solutions offer a wide range of snow removal equipment and configurations across our products and universal compatibility on select units, so they'll work alongside any equipment you already have. So whether it's a plough, a snow pusher or a snowblower, you can count on your Kubota equipment to be a team player.



RESIDENTIAL SOLUTIONS

From acres of estate to clear or simply need to get the car out of the garage after a storm, Kubota has snow removal solutions that are up to the task. Kubota offers a wide variety of versatile attachments built as tough as any Canadian winter. The result is a total solution that gets the snow out of your way.

COMMERCIAL SOLUTIONS

Whether you've got yards to feedlots, we know tough jobs can't wait for the snow to melt. Keep your fleet moving and your work in progress with Kubota snow removal solutions. Built to handle whatever Canadian winters can throw at them, Kubota's range of blades, sweepers and snowblowers are straightforward, reliable, and ready to go to work. Plus, with our coast-to-coast dealer network and Canadian head office, you can get parts and service quickly – before the next snowfall.



T SERIES

RESIDENTIAL SOLUTIONS

Step up to the Kubota T Series and get more of everything you want in a premium lawn tractor. More comfort to keep you relaxed and refreshed. More convenience to make the job easier. More efficiency to get the job done fast. And, of course, more Kubota dependability and durability to keep your T Series doing what it does best: making your lawn look great.



SNOWBLOWER



SNOW BLADE

ATTACHMENT SPECS

SNOW BLADE	Hitch	Description	
		T2833	
		Hitch Type	Front
		Blade Type	Straight
		Angle Type	Manual
		Maximum Width (Length)	48"
	General	Maximum Pivot Angle (Degrees)	30 degrees
		Cutting Edge	Reversible
		Skid Shoes	STD & Adjustable
		Moldboard Height	15 1/2"
		Moldboard Thickness	12 GA
		Base Equipment Weight	90 lbs

SNOWBLOWER	General	Description	
		T2834	
		Hitch Type (Front / Rear Mount)	Front - Hitch
		Blower Type	2 Stage
		Approx. Shipping Weight (lbs)	272 lbs
		Overall Width	46"
		Working Width	46"
		Working Height	17 1/2"
		Overall Length (w/hitch)	22 1/2"
	Impeller	Impeller Diameter	13 3/4"
		Number of Impeller Blades	3
	Auger	Auger Drive	Belt
		Auger Diameter	12 3/4"
	Housing	Housing Thickness	16 GA
		Side Panel Thickness	12 GA
	Chute	Chute Position	Left
		Rotation of Chute	Manual
		Deflector Adjustment	Yes
	Cutting Edge	Replaceable	Yes
	Skid Shoes	Replaceable & Adjustable	Yes

AVAILABLE T90 SERIES MODELS:
T2090
T2290



ATTACHMENT SPECS

		Description	GR2705	GR2848
SNOW BLADE	Hitch	Hitch Type	Front/Direct Mount	Front/Fun Connect
		General	Blade Type	Straight
	Angle Type		Manual	Manual
	Maximum Width (Length)		48"	48"
	Maximum Pivot Angle (Degrees)		30 degrees	30 degrees
	Cutting Width @ Max Degrees Angle		41"	41"
	Cutting Edge		Reversible	Reversible
	Skid Shoes		STD & Adjustable	STD & Adjustable
	Moldboard Height		15 1/2"	17"
	Moldboard Thickness		12 GA	12 GA
	Base Equipment weight		-	141 lbs
	Steel Cutting Edge Replacement	Yes	Yes	

		Description	GR2847
SWEEPER	Hitch	Hitch Type	Front/Fun Connect
		General	Height
	Overall Width		49 1/2"
	Working Width		43"
	Maximum Pivot Angle (Degrees)		18 degrees
	Working Width @ Max Angle		40 3/4"
	Brush Type		100% polypropylene (as std)
	Brush Diameter		18"
	Main Housing Thickness		14 GA
	Weight	114 lbs	

		Description	GR2728	GR2846
SNOWBLOWER	General	Hitch Type (Front / Rear Mount)	Front/Direct Mount	Front/Fun Connect
		Drive Type	PTO	PTO
		Approx. Shipping Weight (LBS.)	260	260
		Overall Width	46"	46"
		Working Width	46"	46"
		Working Height	18 1/2"	17"
		Overall Length (w/hitch)	42 1/2"	43"
	Impeller	Impeller Width	5"	5 1/2"
		Number of Impeller Blades	3	3
	Auger	Auger Drive	Roller Chain #40	Roller Chain #40
		Auger Diameter	12 1/2"	12 3/4"
	Housing	Housing Thickness	14 GA	16 GA
		Side Panel Thickness	12 GA	12 GA
	Chute	Rotation of Chute	Manual (Electric Optional)	Electric
		Deflector Adjustment	Manual (Electric Optional)	Manual (Electric Optional)
	Cutting Edge	Replaceable	Yes	Yes
	Skid Shoes	Replaceable and Adjustable	Yes	Yes

OUTSTANDING TRACTION FOR DEMANDING JOBS

Kubota's GR Series is engineered to allow you to cover every inch of workspace with its tight turning radius and outstanding traction. And regardless of the job at hand, we have the perfect attachment for you to get it done efficiently and with ease. In fact, winter might just be your best season yet.



SNOWBLOWER



SNOW BLADE



SWEEPER

AVAILABLE SERIES MODELS:
GR2020
GR2120



F SERIES

ALL-WEATHER RELIABILITY AND PERFORMANCE

The Kubota F Series has been redesigned to give you greater versatility and precision from summer to sub zero. This mighty mower sweeps, plows, clears snow and clips lawns, giving you the performance you need to get the job done right. The dealer installed cabin offers added comfort while the Tier 4 engine is powerful and fuel-efficient.



SNOWBLOWER



SNOW BLADE



SWEEPER

ATTACHMENT SPECS

		Description	L2163	F6610
SWEEPER	Hitch	Hitch Type	Quick Hitch/PTO Shaft	Quick Hitch/PTO Shaft
		Height	25 3/4"	25"
	General	Overall Width	63 1/2"	71"
		Working Width	56 1/2"	65 1/2"
		Maximum Pivot Angle (Degrees)	20 Degrees	25 Degrees
		Working Width @ Max Angle	51 1/2"	59 1/2"
		Brush Type	Standard: 100% Poly	Standard: 100% Poly
		Brush Speed Range	–	258 RPM @ 3000 RPM
		Main Housing Thickness	–	14 GA
		Side Housing Thickness	–	11 GA
Optional Equipment	Approx. Shipping Weight (lbs)	444 lbs	550 lbs	
	Dust Deflector	Yes	Yes	
	50/50 Poly Brush	No	Yes	

		Description	B2763	F6010	F7210
SNOW BLADE	Hitch	Hitch Type	Quick Hitch	4 Point Hitch	4 Point Hitch
		Blade Type	Straight	Straight	Straight
	General	Angle Type	Manual (Optional Hydraulic)	Hydraulic	Hydraulic w/ cross over relief
		Maximum Width (Length)	60"	60"	72"
		Maximum Pivot Angle (Degrees)	30 degrees	30 degrees	30 degrees
		Cutting Width @ Max Degrees Angle	52 1/2"	52 1/2"	62"
		Cutting Edge	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable
		Skid Shoes	Yes	Yes	Yes
		Moldboard Height	21"	22 1/2"	22 1/2"
		Moldboard Thickness	3 GA	3 GA	3 GA
Optional Equipment	Base Equipment Weight	285 lbs	445 lbs	465 lbs	
	Poly Cutting Edge	Yes	Yes	Yes	
	Cross Over Relief	Yes	Yes	–	

		Description	F5220	F5720	F5110	F5710
SNOWBLOWER	General	Hitch Type (Front /Rear Mount)	Quick Hitch	Quick Hitch	4 Point Hitch	4 Point Hitch
		Blower Type	2 Stages	2 Stages	2 Stages	2 Stages
		Approx. Shipping Weight	498 lbs	532 lbs	498 lbs	532 lbs
		Overall Width	51"	57"	51"	57"
		Working Width	51"	57"	51"	57"
		Working Height	24"	24"	24"	24"
		Overall Length (w/hitch)	30 3/4"	30 3/4"	30 3/4"	30 3/4"
		Impeller	Impeller Diameter	17 3/4"	17 3/4"	17 3/4"
	Number of Impeller Blades		4	4	4	4
	Auger	Auger Drive	Reduction Box	Reduction Box	Reduction Box	Reduction Box
		Auger Diameter	13 3/4"	13 3/4"	13 3/4"	13 3/4"
	Housing	Housing Thickness	12 GA	12 GA	12 GA	12 GA
		Side Panel Thickness	12 GA	12 GA	12 GA	12 GA
	Chute	Chute Position	Right	Right	Right	Right
		Rotation of Chute	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Deflector Adjustment		Manual (optional hydraulic or electric)	Manual (optional hydraulic or electric)	Manual (Optional Hydraulic)	Manual (Optional Hydraulic)	
Cutting Edge	Replaceable	Yes	Yes	Yes	Yes	
Skid Shoes	Replaceable and Adjustable	Yes	Yes	Yes	Yes	
Optional Equipment	Snowblower Extensions	Yes	Yes	Yes	Yes	

AVAILABLE SERIES MODELS:
F2690
F3710



BX & B01 SERIES



RESIDENTIAL SOLUTIONS

From acres of estate to clear or simply need to get the car out of the garage after a storm, Kubota has snow removal solutions that are up to the task. Kubota offers a wide variety of versatile attachments built as tough as any Canadian winter. The result is a total solution that gets the snow out of your way.



SNOWBLOWER



SWEeper



SNOW BLADE



SNOW PUSHER

ATTACHMENT SPECS

		Description	BX2812	BX2826	STB0554	STB0560	STB1060	STB01072
SNOW BLADE	Hitch	Hitch Type	Front, K-Connect	Front, K-Connect	Loader Mount	Loader Mount	Loader Mount	Loader Mount
		Blade Type	Straight Blade	V Blade	Straight Blade	Straight Blade	Straight Blade	Straight Blade
	General	Angle Type	Hydraulic	Hydraulic	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)
		Maximum Width (Length)	60"	60"	54"	60"	60"	72"
		Maximum Pivot Angle (Degrees)	30 degrees	30 degrees	24 degrees	24 degrees	30 degrees	30 degrees
		Cutting Width @ Max Degrees Angle	52"	In V Position 54" In Scoop Position 52"	49"	55"	52"	62"
		Cutting Edge	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable
		Skid Shoes	STD & Adjustable	STD & Adjustable	STD & Adjustable	STD & Adjustable	STD & Adjustable	STD & Adjustable
		Moldboard Height	19 3/4"	16 5/8" center 20" both end	17"	17"	22"	22"
		Moldboard Thickness	7 GA	14 GA	12 GA	12 GA	12 GA	12 GA
		Base Equipment Weight	230 lbs	280 lbs	278 lbs	288 lbs	368 lbs	390 lbs
		Optional Equipment	Poly Cutting Edge	Yes	-	Yes	Yes	Yes

ATTACHMENT SPECS

		Description	BX2816	BX2830	BX2822A	K51-20-06	K54-22-06
SNOWBLOWER	General	Hitch Type (Front /Rear Mount)	Front, K-Connect	Front, K-Connect	Front, K-Connect	Rear, 3 Pt	Rear, 3 Pt
		Blower Type	2 Stage	2 Stage	2 Stage	2 Stage	2 Stage
		Approx. Shipping Weight	287 lbs	500 lbs	520 lbs	555 lbs	575 lbs
		Overall Width	50"	49 1/4"	56 1/4"	51 1/2"	54 1/2"
		Working Width	49 3/4"	48"	55"	50 1/2"	53 1/2"
		Working Height	20"	20"	20"	24 1/2"	25 1/2"
		Overall Length (w/hitch)	26 3/8"	30"	30"	36 1/2"	36 1/2"
	Impeller	Impeller Diameter	15 3/4"	15 3/4"	15 3/4"	20"	22"
		Number of Impeller Blades	4	4	4	4	4
	Auger	Auger Drive	Chain #40	Worm Gear	Worm Gear	Chain #50	Chain #60
		Auger Diameter	12 3/4"	12 3/4"	12 3/4"	15"	15"
	Housing	Housing Thickness	14 GA	12 GA	12 GA	12 GA	12 GA
		Side Panel Thickness	11 GA	7 GA	7 GA	11 GA	11 GA
	Chute	Rotation of Chute	Manual (Hydraulic Opt)	Hydraulic with motor	Hydraulic with motor	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)
Deflector Adjustment		Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	
Cutting Edge	Replaceable	Yes	Yes	Yes	Yes	Yes	
Skid Shoes	Replaceable and Adjustable	Yes	Yes	Yes	Yes	Yes	

		Description	BX2814	
SWEEPER	Hitch	Hitch Type	Front, K-Connect	
		Height	25"	
	General	Overall Width	62"	
		Working Width	56"	
		Maximum Pivot Angle (Degrees)	25 degrees	
		Working Width @ Max Angle	48 1/2"	
		Brush Type	100% polypropylene	
		Brush Speed Range	270 RPM @ 3000 RPM	
		Main Housing Thickness	16 GA	
		Side Housing Thickness	12 GA	
		Approx. Shipping Weight (LBS.)	480 lbs	
		Optional Equipment	Dust Deflector	Optional

		Description	SPL0548	SPL0560
LOADER MOUNT SNOW PUSHER	Hitch	Hitch Type	Loader Mount	Loader Mount
		Working Width	48"	60"
	General	Approx. Capacity	9 ft³	12 ft³
		Weight (Poly Optional)	168 lbs	190lbs
		HP Range	Max 28 HP	Max 28 HP
		Cutting Edge	Reversible and Replaceable	Reversible and Replaceable
		Moldboard Thickness	12 GA	12 GA
		Side Panel Thickness	7 GA	7 GA



AVAILABLE BX SERIES MODELS:

BX1880
 BX2380
 BX2680
 BX23S

AVAILABLE B01 SERIES MODELS:

B2301
 B2601
 B2401



LX SERIES



JACK FROST? MEET THE JACK OF ALL TRADES.

Tackle your property's every icy task, with the all-new Kubota LX Series tractor. With its 4-point hitch and K-Connect, you can quickly and easily switch out any attachment—snow shovels and pushers, snowblowers, loaders, sweepers, or just about any other tool. The proven Kubota diesel engine, available with a turbocharge option, puts big power and torque where you need it most; under your precise control.



SNOWBLOWER



SWEeper



SNOW BLADE



SNOW PUSHER

ATTACHMENT SPECS

		Description	LX2960	LX2972	STB1060	STB01072
SNOW BLADE	Hitch	Hitch Type	Front, K-Connect	Front, K-Connect	Loader Mount	Loader Mount
		Blade Type	Straight Blade	Straight Blade	Straight Blade	Straight Blade
	General	Maximum Cutting Width	60"	72"	60"	72"
		Angle Type	Hydraulic	Hydraulic	Hydraulic	Hydraulic
		Maximum Pivot Angle (Degrees)	30 degrees	30 degrees	30 degrees	30 degrees
		Cutting Width @ 30 Degrees Angle	52 1/2"	62"	52"	62"
		Cutting Edge	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable
		Skid Shoes	STD & Adjustable	STD & Adjustable	STD & Adjustable	STD & Adjustable
		Moldboard Height	22 1/2"	22 1/2"	22"	22"
		Moldboard Thickness	3 GA	3 GA	12 GA	12 GA
		Base Equipment Weight (Poly Cutting Edge is Optional)	430 lbs	450 lbs	368 lbs	390 lbs
		Poly Cutting Edge	Yes	Yes	Yes	Yes

ATTACHMENT SPECS

		Description	LX2963	K51-22-7CF	K64-22-7CF	K51-20-06	K54-22-06	K64-24-07	
SNOWBLOWER	Hitch	Hitch Type (Front / Rear Mount)	Front, K-Connect	Front, K-Connect	Front, K-Connect	Rear, 3 Pt	Rear, 3 Pt	Rear, 3 Pt	
	General	Blower Type	2 Stage	2 Stage	2 Stage	2 Stage	2 Stage	2 Stage	2 Stage
		Approx. Shipping Weight	530 lbs	605 lbs	635 lbs	555 lbs	575 lbs	680 lbs	680 lbs
		Overall Width	64 1/4"	51 3/4"	64 3/4"	51 1/2"	54 1/2"	64 3/4"	64 3/4"
		Working Width	63"	50 1/2"	63 1/2"	50 1/2"	53 1/2"	63 1/2"	63 1/2"
		Working Height	23"	25 3/4"	25 3/4"	24 1/2"	25 1/2"	64 3/4"	64 3/4"
	Overall Length (w/ hitch)	47"	39 1/2"	39 1/2"	36 1/2"	36 1/2"	37 3/4"	37 3/4"	
	Impeller	Impeller Diameter	17 5/8"	22"	22"	20"	22"	24"	24"
		Number of Impeller Blades	4	4	4	4	4	4	4
	Auger	Auger Drive	Worm Gear	Chain #60	Chain #60	Chain #50	Chain #60	Chain #60	Chain #60
		Auger Diameter	13 3/4"	15"	15"	15"	15"	15"	15"
	Housing	Housing Thickness	12 GA	12 GA	12 GA	12 GA	12 GA	12 GA	12 GA
		Side Panel Thickness	12 GA	11 GA	11 GA	11 GA	11 GA	11 GA	11 GA
	Chute	Chute Position	Left	Left	Left	Right	Right	Right	Right
		Rotation of Chute	Hydraulic with motor	Hydraulic	Hydraulic	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)
		Deflector Adjustment	Manual	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)
Cutting Edge	Replaceable	Replaceable & reversible, carbon steel	Replaceable & reversible, carbon steel	Replaceable & reversible, carbon steel	Replaceable & reversible, carbon steel	Replaceable & reversible, carbon steel	Replaceable & reversible, carbon steel	Replaceable & reversible, carbon steel	
Skid Shoes	Replaceable and Adjustable	Adjustable & replaceable, 3 positions	Adjustable & replaceable, 3 positions	Adjustable & replaceable, 3 positions	Adjustable & replaceable, 3 positions	Adjustable & replaceable, 3 positions	Adjustable & replaceable, 3 positions	Adjustable & replaceable, 3 positions	

		Description	LX2950	
SWEeper	Hitch	Hitch Type	Front, K Connect	
	General	Height	25"	
		Overall Width	71"	
		Working Width	65 1/2"	
		Maximum Pivot Single (Degrees)	25 Degrees	
		Working Width @ Max Angle	59 1/2"	
		Brush Type	100% polypropylene	
		Brush Speed Range	258 RPM @ 3000 RPM	
		Main Housing Thickness	14 GA	
		Side Housing Thickness	11 GA	
	Approx. Shipping Weight (lbs)	550 lbs		
Optional Equipment	Dust Deflector	Optional		

		Description	SPL1060	SPL1072
LOADER MOUNT SNOW PUSHER	Hitch	Hitch Type	Loader Mount Quick Attach	Loader Mount Quick Attach
	General	Working Width	60"	72"
		Work Height	24"	24"
		Approx. Capacity	22 ft³	26 ft³
		Depth	10"	10"
		Weight	346 lbs	377 lbs
		HP Range	20-45 HP	20-45 HP
		Cutting Edge	Reversible and Replaceable	Reversible and Replaceable
Moldboard Thickness	10 GA	10 GA		
Side Panel Thickness	1/2"	1/2"		



AVAILABLE SERIES MODELS:
LX2610
LX3310

THE NEW:
LX2620
LX3520
LX4020





R, SVL, SSV SERIES

BUILT FOR ALL KINDS OF CANADA

Building in Canada has its own challenges. What you need for downtown is different from what you need out-of-town. It's why our equipment is cold weather tested. It's also why we offer compact sizes for flexibility, versatile attachments for multitasking, and comfort for long days on the job.



SNOWBLOWER



TRIP EDGE BLADE



SNOW PUSHER



SNOW BUCKET

ATTACHMENT SPECS

	Description	SBL30	SB35	K66247HB	K76249HB	K76249HH	K842611HH	SBL2566	SBL2574	SBL842410HH
General	Hitch Type	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch
	Approx. Shipping Weight	791 lbs	1035 lbs	767 lbs	767 lbs	1,160 lbs	1,644 lbs	816 lbs	938 lbs	988 lbs
	Working Width	74" & 84"	84"	66"	75 7/8"	75 7/8"	84 1/2"	66"	74"	84"
	Working Height	-	-	27"	27 1/2"	27 1/2"	31 3/4"	27"	27"	27"
	Overall Length (w/hitch)	38 1/4"	38 1/4"	39"	35 1/4"	35 1/4"	46 7/8"	45 3/4"	45 3/4"	45 3/4"
Impeller	Impeller Width	7"	7"	7"	9"	9"	11"	8"	8"	10"
	Number of Impeller Blades	5	5	4	4	4	4	4	4	4
	Impeller Diameter	26 3/8"	26 3/8"	24"	24"	24"	26"	24"	24"	24"
Auger	Auger Diameter	16"	16"	15"	15"	14 3/4"	20"	16"	16"	16"
	Housing Thickness	10 GA	10 GA	11 GA	11 GA	11 GA	11 GA	10 GA	10 GA	10 GA
Housing	Side Panel Thickness	1/4"	1/4"	3/16"	3/16"	3/16"	3/16"	3/16"	3/16"	3/16"
	Rotation of Chute	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Spout Deflector	Foldable Chute	Foldable Chute	3 Piece Hydraulic Chute	3 Piece Hydraulic Chute	3 Piece Hydraulic Chute	3 Piece Hydraulic Chute	2 Piece Hydraulic Chute	2 Piece Hydraulic Chute	2 Piece Hydraulic Chute
	Cutting Edge	Replaceable	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Skid Shoes	Replaceable and Adjustable	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes



ATTACHMENT SPECS

		Description	LM2584	LM2596	LM25108
SNOW BUCKET		Weight (w/o Optional Cutting Edge) (kg)	719 lbs (326)	803 lbs (364)	869 lbs (394)
		Struck Capacity (m3)	30.9 ft³ (.87)	35.4 ft³ (1)	40.4 ft³ (1.14)
		Heap Capacity (m3)	39.62 ft³ (1.12)	45.64 ft³ (1.29)	51.6 ft³ (1.46)
		Overall Width (m)	85" (2.16)	97" (2.46)	109" (2.77)
		Overall Height (cm)	33-1/4" (83.8)	33-1/4" (83.8)	33-1/4" (83.8)
		Bucket Floor Thickness (mm)	3/16" (5)	3/16" (5)	3/16" (5)
		Bucket Side Wall Thickness (mm)	1/4" (6)	1/4" (6)	1/4" (6)
		Bucket Cutting Edge Thickness (mm)	3/4" (19)	3/4" (19)	3/4" (19)
		Working Depth of Bucket (m)	41-1/4" (1.05)	41-1/4" (1.05)	41-1/4" (1.05)
		Optional Bolt-On Cutting Edge	Reversible and replaceable	Reversible and replaceable	Reversible and replaceable

		Description	TE3596	TE35108	
TRIP EDGE BLADE	Hitch	Hitch Type	Front/Serrated	Front/Serrated	
	General		Blade Type	Straight Blade	Straight Blade
			Maximum Cutting Width	96"	108"
			Angle Type	Hydraulic	Hydraulic
			Maximum Pivot Angle (Degrees)	30 degrees	30 degrees
			Cutting Edge	Reversible and Replaceable	Reversible and Replaceable
			Skid Shoes	STD & Adjustable	STD & Adjustable
			Moldboard Height	30"	30"
			Moldboard Thickness	7 GA	7 GA
			Base Equipment Weight (Poly cutting edge is Optional)	1,114 lbs	1,134 lbs
			Poly Cutting Edge	Yes	Yes

		Description	SSP2596	
SNOW PUSHER	Hitch	Hitch Type	Quick Attach	
	General		Working Width	96"
			Work Height	24"
			Approx. Capacity	64 ft³
			Lift Capacity of Carrier	5,000 Lbs
			Weight (Poly Blade Optional)	844 lbs
			HP Range	50 - 80 HP
			Cutting Edge	Reversible and Replaceable
	Moldboard Thickness	3/16"		
	Side Panel Thickness	5/16"		



AVAILABLE R SERIES MODELS:

- R430
- R540
- R640

AVAILABLE SVL SERIES MODELS:

- SVL65-2
- SVL75-3
- SVL97-2

AVAILABLE SSV SERIES MODELS:

- SSV65
- SSV75





RTV SERIES

DON'T LET SNOW SLOW YOU DOWN

Meet the line up of utility vehicles that goes from summer to winter-ready in a matter of seconds. The RTV Series is powered by Kubota's durable and high-performing diesel engine, giving you plenty of horsepower for snowblowing, snow clearing and sweeping. With optional cold weather utility cabs, the weather may be cooling down, but for the RTV Series, things are just heating up.



SNOWBLOWER



SNOW BLADE



SWEeper

ATTACHMENT SPECS

		Description	V5008	V5290	V5291	V5294A	V5295A	V0840	V4308
SNOW BLADE	Model Compatibility	Series	RTV-X, RTV-X1100C, RTV-X1130, RTV-X1140	RTV-X, RTV-X1100C	RTV-X, RTV-X1100C	RTV-X, RTV-X1100C, RTV-X1130, RTV-X1140	RTV-X, RTV-X1100C, RTV-X1130, RTV-X1140	RTV-XG850	RTV520
	Hitch	Hitch Type	A-Frame	Quick Hitch	Quick Hitch	K Connect	K Connect	Winch Lift	Quick Hitch
	General	Blade Type	Straight Blade	Straight Blade	V Blade	Straight Blade	V Blade	Straight Blade	Straight Blade
		Angle Type	Manual (Optional Hydraulic)	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Manual	Manual (Optional Electric)
		Maximum width (Length)	72"	72"	72"	78"	78"	74"	60"
		Maximum Pivot Angle (Degrees)	28 degrees	29 degrees	30 degrees	30 degrees	30 degrees	30 degrees	30 degrees
		Cutting Width @ Max Degrees Angle	64 3/5"	64 3/5"	66" in V Position	68"	69 1/2" in V Position	64"	52"
		Cutting Edge	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable	Replaceable	Replaceable	Replaceable	Replaceable
		Skid Shoes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
		Moldboard Height	19"	24 3/16"	22 5/16"	24"	24"	19 5/8"	22"
Moldboard Thickness	12 GA	10 GA	3/16"	14 GA	14 GA	10 GA	12 GA		
Base Equipment Weight	238 lbs	255 lbs	300 lbs	220 lbs	290 lbs	202 lbs	185 lbs		
Optional Equipment	Hard Plastic/Poly Cutting Edge	No	No	No	Yes	Yes	Yes	Yes	

		Description	V5296
SNOWBLOWER	Model Compatibility	Series	RTV-X & X1100C
	General	Hitch Type (Front / Rear Mount)	K Connect Quick Hitch
		Blower Type	2 Stage
		Approx. Shipping Weight	540 lbs
		Working Width	66"
		Working Height	20"
		Overall Length (w/hitch)	30"
	Impeller	Impeller Width	5 5/8"
		Number of Impeller Blades	4
	Auger	Auger Drive	Gear
Auger Diameter		12 3/4"	
Housing	Housing Thickness	12 GA	
	Side Panel Thickness	12 GA	
Chute	Rotation of Chute	Hydraulic	
	Deflector Adjustment	Hydraulic	
Cutting Edge	Replaceable	Replaceable & Reversible	
Skid Shoes	Replaceable and Adjustable	Adjustable and Replaceable	

		Description	V5266	V5260
SWEeper	Model Compatibility	Series	RTV-X & X1100C	RTV-X & X1100C
	Hitch	Hitch Type	K Connect	Quick Hitch
		Drive Type	K Connect PTO	Hydraulic
	General	Height	25"	25"
		Overall Width	70 1/2"	75 3/8"
		Working Width	65 1/2"	60
		Maximum Pivot Angle (Degrees)	25 degrees	25 degrees
		Working Width @ Max Angle	59 1/2"	55"
		Brush Type	Standard: 100% Poly	Standard: 100% Poly
		Main Housing Thickness	16 GA	16 GA
Side Housing Thickness		12 GA	12 GA	
Approx. Shipping Weight	480 lbs	360 lbs		
Optional Equipment	Dust Deflector	Yes	Yes	
	50/50 Poly Brush	Yes	No	



AVAILABLE RTV SERIES MODELS:
RTV520, RTV-X, RTV-X1140, RTV-X1100, RTV-XG850





Descriptions, specifications, images, colours and accessories contained in this brochure are based on information believed to be correct at the time this publication was approved for printing. Although descriptions, specifications, images, colours and accessories are believed to be correct, accuracy cannot be guaranteed. Errors and omissions excepted. Kubota Canada Ltd. reserves the right to change the stated specifications, colours and accessories without notice. Some items shown may be optional and some products shown may not be available at all dealerships. This brochure is for informational purposes only. To the fullest extent permitted by law, Kubota disclaims all representations and warranties, express or implied, as well as any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the Canadian market only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global website. Kubota does not provide parts, warranty or service for any product which is re-sold or retailed in any country other than the country for which the product(s) were designed or manufactured.

Kubota Canada LTD.

Head office: 1155 Kubota Drive, Pickering, ON L1X 0H4