



R, SVL, SSV SERIES

BUILT FOR ALL KINDS OF CANADA

Building in Canada has its own challenges. What you need for downtown is different from what you need out-of-town. It's why our equipment is cold weather tested. It's also why we offer compact sizes for flexibility, versatile attachments for multitasking, and comfort for long days on the job.



SNOWBLOWER



TRIP EDGE BLADE



SNOW PUSHER



SNOW BUCKET

ATTACHMENT SPECS

		Description	SBL30	SB35	K66247HB	K76249HB	K76249HH	K842611HH	SBL2566	SBL2574	SBL842410HH
SNOWBLOWER	General	Hitch Type	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch	Skid Steer Hitch
		Approx. Shipping Weight	791 lbs	1035 lbs	767 lbs	767 lbs	1,160 lbs	1,644 lbs	816 lbs	938 lbs	988 lbs
		Working Width	74" & 84"	84"	66"	75 7/8"	75 7/8"	84 1/2"	66"	74"	84"
		Working Height	—	—	27"	27 1/2"	27 1/2"	31 3/4"	27"	27"	27"
		Overall Length (w/hitch)	38 1/4"	38 1/4"	39"	35 1/4"	35 1/4"	46 7/8"	45 3/4"	45 3/4"	45 3/4"
	Impeller	Impeller Width	7"	7"	7"	9"	9"	11"	8"	8"	10"
		Number of Impeller Blades	5	5	4	4	4	4	4	4	4
		Impeller Diameter	26 3/8"	26 3/8"	24"	24"	24"	26"	24"	24"	24"
	Auger	Auger Diameter	16"	16"	15"	15"	14 3/4"	20"	16"	16"	16"
	Housing	Housing Thickness	10 GA	10 GA	11 GA	11 GA	11 GA	11 GA	10 GA	10 GA	10 GA
		Side Panel Thickness	1/4"	1/4"	3/16"	3/16"	3/16"	3/16"	3/16"	3/16"	3/16"
		Rotation of Chute	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
		Spout Deflector	Foldable Chute	Foldable Chute	3 Piece Hydraulic Chute	3 Piece Hydraulic Chute	3 Piece Hydraulic Chute	3 Piece Hydraulic Chute	2 Piece Hydraulic Chute	2 Piece Hydraulic Chute	2 Piece Hydraulic Chute
	Cutting Edge	Replaceable	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Skid Shoes	Replaceable and Adjustable	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	



ATTACHMENT SPECS

SNOW BUCKET	Description	LM2584	LM2596	LM25108
	Weight (w/o Optional Cutting Edge) (kg)	719 lbs (326)	803 lbs (364)	869 lbs (394)
	Struck Capacity (m3)	30.9 ft³ (.87)	35.4 ft³ (1)	40.4 ft³ (1.14)
	Heap Capacity (m3)	39.62 ft³ (1.12)	45.64 ft³ (1.29)	51.6 ft³ (1.46)
	Overall Width (m)	85" (2.16)	97" (2.46)	109" (2.77)
	Overall Height (cm)	33-1/4" (83.8)	33-1/4" (83.8)	33-1/4" (83.8)
	Bucket Floor Thickness (mm)	3/16" (5)	3/16" (5)	3/16" (5)
	Bucket Side Wall Thickness (mm)	1/4" (6)	1/4" (6)	1/4" (6)
	Bucket Cutting Edge Thickness (mm)	3/4" (19)	3/4" (19)	3/4" (19)
	Working Depth of Bucket (m)	41-1/4" (1.05)	41-1/4" (1.05)	41-1/4" (1.05)
	Optional Bolt-On Cutting Edge	Reversible and replaceable	Reversible and replaceable	Reversible and replaceable

TRIP EDGE BLADE	Hitch	Description	TE3596	TE35108
		Hitch Type	Front/Serrated	Front/Serrated
	General	Blade Type	Straight Blade	Straight Blade
		Maximum Cutting Width	96"	108"
		Angle Type	Hydraulic	Hydraulic
		Maximum Pivot Angle (Degrees)	30 degrees	30 degrees
		Cutting Edge	Reversible and Replaceable	Reversible and Replaceable
		Skid Shoes	STD & Adjustable	STD & Adjustable
		Moldboard Height	30"	30"
		Moldboard Thickness	7 GA	7 GA
		Base Equipment Weight (Poly cutting edge is Optional)	1,114 lbs	1,134 lbs
		Poly Cutting Edge	Yes	Yes

SNOW PUSHER	Hitch	Description	SSP2596
		Hitch Type	Quick Attach
	General	Working Width	96"
		Work Height	24"
		Approx. Capacity	64 ft³
		Lift Capacity of Carrier	5,000 Lbs
		Weight (Poly Blade Optional)	844 lbs
		HP Range	50 - 80 HP
		Cutting Edge	Reversible and Replaceable
		Moldboard Thickness	3/16"
		Side Panel Thickness	5/16"



AVAILABLE R SERIES MODELS:

R430
R540
R640

AVAILABLE SVL SERIES MODELS:

SVL65-2
SVL75-3
SVL97-2

AVAILABLE SSV SERIES MODELS:

SSV65
SSV75

