

# LX SERIES



## JACK FROST? MEET THE JACK OF ALL TRADES.

Tackle your property's every icy task, with the all-new Kubota LX Series tractor. With its 4-point hitch and K-Connect, you can quickly and easily switch out any attachment—snow shovels and pushers, snowblowers, loaders, sweepers, or just about any other tool. The proven Kubota diesel engine, available with a turbocharge option, puts big power and torque where you need it most; under your precise control.



**SNOWBLOWER**



**SWEEPER**



**SNOW BLADE**



**SNOW PUSHER**

# ATTACHMENT SPECS

| | | Description | LX2960 | LX2972 | STB1060 | STB01072 |
|---|---|---|---|---|---|---|
| SNOW BLADE | Hitch | Hitch Type | Front, K-Connect | Front, K-Connect | Loader Mount | Loader Mount |
| | General | Blade Type | Straight Blade | Straight Blade | Straight Blade | Straight Blade |
| | | Maximum Cutting Width | 60″ | 72″ | 60″ | 72″ |
| | | Angle Type | Hydraulic | Hydraulic | Hydraulic | Hydraulic |
| | | Maximum Pivot Angle (Degrees) | 30 degrees | 30 degrees | 30 degrees | 30 degrees |
| | | Cutting Width @ 30 Degrees Angle | 52 1/2″ | 62″ | 52″ | 62″ |
| | | Cutting Edge | Reversible and Replaceable | Reversible and Replaceable | Reversible and Replaceable | Reversible and Replaceable |
| | | Skid Shoes | STD & Adjustable | STD & Adjustable | STD & Adjustable | STD & Adjustable |
| | | Moldboard Height | 22 1/2″ | 22 1/2″ | 22″ | 22″ |
| | | Moldboard Thickness | 3 GA | 3 GA | 12 GA | 12 GA |
| | | Base Equipment Weight (Poly Cutting Edge is Optional) | 430 lbs | 450 lbs | 368 lbs | 390 lbs |
| | | Poly Cutting Edge | Yes | Yes | Yes | Yes |

# ATTACHMENT SPECS

| | | Description | LX2963 | K51-22-7CF | K64-22-7CF | K51-20-06 | K54-22-06 | K64-24-07 | K64-24-07INV | K74-24-07INV |
|---|---|---|---|---|---|---|---|---|---|---|
| | **Hitch** | Hitch Type (Front / Rear Mount) | Front, K-Connect | Front, K-Connect | Front, K-Connect | Rear, 3 Pt | Rear, 3 Pt | Rear, 3 Pt | Rear, 3PT Inverted | Rear, 3PT Inverted |
| **SNOWBLOWER** | **General** | Blower Type | 2 Stage | 2 Stage | 2 Stage | 2 Stage | 2 Stage | 2 Stage | 2 Stage | 2 Stage |
| | | Approx. Shipping Weight | 530 lbs | 605 lbs | 635 lbs | 555 lbs | 575 lbs | 680 lbs | 750 lbs | 770 lbs |
| | | Overall Width | 64 1/4″ | 51 3/4″ | 64 3/4″ | 51 1/2″ | 54 1/2″ | 64 3/4″ | 66 1/4″ | 76 1/2″ |
| | | Working Width | 63″ | 50 1/2″ | 63 1/2″ | 50 1/2″ | 53 1/2″ | 63 1/2″ | 63 1/2″ | 73 3/4″ |
| | | Working Height | 23″ | 25 3/4″ | 25 3/4″ | 24 1/2″ | 25 1/2″ | 64 3/4″ | 25 1/2″ | 25 1/2″ |
| | | Overall Length (w/hitch) | 47″ | 39 1/2″ | 39 1/2″ | 36 1/2″ | 36 1/2″ | 37 3/4″ | 40 1/4″ | 40 1/4″ |
| | **Impeller** | Impeller Diameter | 17 5/8″ | 22″ | 22″ | 20″ | 22″ | 24″ | 24″ | 24″ |
| | | Number of Impeller Blades | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| | **Auger** | Auger Drive | Worm Gear | Chain #60 | Chain #60 | Chain #50 | Chain #60 | Chain #60 | Chain #60 | Chain #60 |
| | | Auger Diameter | 13 3/4″ | 15″ | 15″ | 15″ | 15″ | 15″ | 15″ | 15″ |
| | **Housing** | Housing Thickness | 12 GA | 12 GA | 12 GA | 12 GA | 12 GA | 12 GA | 14 GA | 14 GA |
| | | Side Panel Thickness | 12 GA | 11 GA | 11 GA | 11 GA | 11 GA | 11 GA | 14 GA | 14 GA |
| | **Chute** | Chute Position | Left | Left | Left | Right | Right | Right | Right | Right |
| | | Rotation of Chute | Hydraulic with motor | Hydraulic | Hydraulic | Manual (Hydraulic Opt) | Manual (Hydraulic Opt) | Manual (Hydraulic Opt) | Manual or Hydraulic | Manual or Hydraulic |
| | | Deflector Adjustment | Manual | Manual (Hydraulic Opt) | Manual (Hydraulic Opt) | Manual (Hydraulic Opt) | Manual (Hydraulic Opt) | Manual (Hydraulic Opt) | Manual (Hydraulic or Electric Opt) | Manual (Hydraulic or Electric Opt) |
| | **Cutting Edge** | Replaceable | Replaceable & reversible, carbon steel | Replaceable & reversible, carbon steel | Replaceable & reversible, carbon steel | Replaceable & reversible, carbon steel | Replaceable & reversible, carbon steel | Replaceable & reversible, carbon steel | Yes | Yes |
| | **Skid Shoes** | Replaceable and Adjustable | Adjustable & replaceable, 3 positions | Adjustable & replaceable, 3 positions | Adjustable & replaceable, 3 positions | Adjustable & replaceable, 3 positions | Adjustable & replaceable, 3 positions | Adjustable & replaceable, 3 positions | Adjustable & replaceable, 3 positions | Adjustable & replaceable, 3 positions |

| | | Description | LX2950 |
|---|---|---|---|
| **SWEEPER** | **Hitch** | Hitch Type | Front, K Connect |
| | **General** | Height | 25″ |
| | | Overall Width | 71″ |
| | | Working Width | 65 1/2″ |
| | | Maximum Pivot Single (Degrees) | 25 Degrees |
| | | Working Width @ Max Angle | 59 1/2″ |
| | | Brush Type | 100% polypro-pylene |
| | | Brush Speed Range | 258 RPM @ 3000 RPM |
| | | Main Housing Thickness | 14 GA |
| | | Side Housing Thickness | 11 GA |
| | | Approx. Shipping Weight (lbs) | 550 lbs |
| | **Optional Equipment** | Dust Deflector | Optional |

| | | Description | SPL1060 | SPL1072 |
|---|---|---|---|---|
| **LOADER MOUNT SNOW PUSHER** | **Hitch** | Hitch Type | Loader Mount Quick Attach | Loader Mount Quick Attach |
| | **General** | Working Width | 60″ | 72″ |
| | | Work Height | 24″ | 24″ |
| | | Approx. Capacity | 22 $ft^3$ | 26 $ft^3$ |
| | | Depth | 10″ | 10″ |
| | | Weight | 346 lbs | 377 lbs |
| | | HP Range | 20-45 HP | 20-45 HP |
| | | Cutting Edge | Reversible and Replaceable | Reversible and Replaceable |
| | | Moldboard Thick-ness | 10 GA | 10 GA |
| | | Side Panel Thick-ness | 1/2″ | 1/2″ |





**AVAILABLE SERIES MODELS:**
LX2620
LX3520
LX4020