



LX SERIES

JACK FROST? MEET THE JACK OF ALL TRADES.

Tackle your property's every icy task, with the all-new Kubota LX Series tractor. With its 4-point hitch and K-Connect, you can quickly and easily switch out any attachment—snow shovels and pushers, snowblowers, loaders, sweepers, or just about any other tool. The proven Kubota diesel engine, available with a turbocharge option, puts big power and torque where you need it most; under your precise control.



SNOWBLOWER



SWEeper



SNOW BLADE



SNOW PUSHER

ATTACHMENT SPECS

		Description	LX2960	LX2972	STB1060	STB01072
SNOW BLADE	Hitch	Hitch Type	Front, K-Connect	Front, K-Connect	Loader Mount	Loader Mount
		Blade Type	Straight Blade	Straight Blade	Straight Blade	Straight Blade
	General	Maximum Cutting Width	60"	72"	60"	72"
		Angle Type	Hydraulic	Hydraulic	Hydraulic	Hydraulic
		Maximum Pivot Angle (Degrees)	30 degrees	30 degrees	30 degrees	30 degrees
		Cutting Width @ 30 Degrees Angle	52 1/2"	62"	52"	62"
		Cutting Edge	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable
		Skid Shoes	STD & Adjustable	STD & Adjustable	STD & Adjustable	STD & Adjustable
		Moldboard Height	22 1/2"	22 1/2"	22"	22"
		Moldboard Thickness	3 GA	3 GA	12 GA	12 GA
		Base Equipment Weight (Poly Cutting Edge is Optional)	430 lbs	450 lbs	368 lbs	390 lbs
		Poly Cutting Edge	Yes	Yes	Yes	Yes

ATTACHMENT SPECS

		Description	LX2963	K51-22-7CF	K64-22-7CF	K51-20-06	K54-22-06	K64-24-07	
SNOWBLOWER	Hitch	Hitch Type (Front / Rear Mount)	Front, K-Connect	Front, K-Connect	Front, K-Connect	Rear, 3 Pt	Rear, 3 Pt	Rear, 3 Pt	
	General	Blower Type	2 Stage	2 Stage	2 Stage	2 Stage	2 Stage	2 Stage	2 Stage
		Approx. Shipping Weight	530 lbs	605 lbs	635 lbs	555 lbs	575 lbs	680 lbs	
		Overall Width	64 1/4"	51 3/4"	64 3/4"	51 1/2"	54 1/2"	64 3/4"	
		Working Width	63"	50 1/2"	63 1/2"	50 1/2"	53 1/2"	63 1/2"	
		Working Height	23"	25 3/4"	25 3/4"	24 1/2"	25 1/2"	64 3/4"	
		Overall Length (w/ hitch)	47"	39 1/2"	39 1/2"	36 1/2"	36 1/2"	37 3/4"	
	Impeller	Impeller Diameter	17 5/8"	22"	22"	20"	22"	24"	
		Number of Impeller Blades	4	4	4	4	4	4	
	Auger	Auger Drive	Worm Gear	Chain #60	Chain #60	Chain #50	Chain #60	Chain #60	
		Auger Diameter	13 3/4"	15"	15"	15"	15"	15"	
	Housing	Housing Thickness	12 GA	12 GA	12 GA	12 GA	12 GA	12 GA	
		Side Panel Thickness	12 GA	11 GA	11 GA	11 GA	11 GA	11 GA	
	Chute	Chute Position	Left	Left	Left	Right	Right	Right	
		Rotation of Chute	Hydraulic with motor	Hydraulic	Hydraulic	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	
		Deflector Adjustment	Manual	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	Manual (Hydraulic Opt)	
	Cutting Edge	Replaceable	Replaceable & reversible, carbon steel	Replaceable & reversible, carbon steel	Replaceable & reversible, carbon steel	Replaceable & reversible, carbon steel	Replaceable & reversible, carbon steel	Replaceable & reversible, carbon steel	
	Skid Shoes	Replaceable and Adjustable	Adjustable & replaceable, 3 positions	Adjustable & replaceable, 3 positions	Adjustable & replaceable, 3 positions	Adjustable & replaceable, 3 positions	Adjustable & replaceable, 3 positions	Adjustable & replaceable, 3 positions	

		Description	LX2950
SWEeper	Hitch	Hitch Type	Front, K Connect
	General	Height	25"
		Overall Width	71"
		Working Width	65 1/2"
		Maximum Pivot Single (Degrees)	25 Degrees
		Working Width @ Max Angle	59 1/2"
		Brush Type	100% polypropylene
		Brush Speed Range	258 RPM @ 3000 RPM
		Main Housing Thickness	14 GA
		Side Housing Thickness	11 GA
		Approx. Shipping Weight (lbs)	550 lbs
	Optional Equipment	Dust Deflector	Optional

		Description	SPL1060	SPL1072
LOADER MOUNT SNOW PUSHER	Hitch	Hitch Type	Loader Mount Quick Attach	Loader Mount Quick Attach
	General	Working Width	60"	72"
		Work Height	24"	24"
		Approx. Capacity	22 ft³	26 ft³
		Depth	10"	10"
		Weight	346 lbs	377 lbs
		HP Range	20-45 HP	20-45 HP
		Cutting Edge	Reversible and Replaceable	Reversible and Replaceable
		Moldboard Thickness	10 GA	10 GA
	Side Panel Thickness	1/2"	1/2"	



AVAILABLE SERIES MODELS:
LX2610
LX3310

THE NEW:
LX2620
LX3520
LX4020

