

L TRACTOR

PERFORMANCE
MATCHED
ATTACHMENTS



L TRACTOR PERFORMANCE MATCHED ATTACHMENTS

Land Pride's relationship with Kubota allows our products to be performance matched to your tractor by Kubota and Land Pride Engineering. This process assures you that the horsepower rating, weight, and width of your implement matches the specifications of your L tractor.

All attachment sizes may not be applicable to all L Tractors. L Series sizes are Performance Matched to select L Tractors. Other sizes in the series may be available for other series of Kubota tractors. Options pictured on Kubota tractors may not be available on your local V-Series tractor. Please consult your local HP requirements and visit [kubota.ca](#) to locate your nearest dealer.

This catalog highlights the broad assortment of products engineered to meet the needs of L Series owners. From Grapples to Rakes, cutters to Tillers, you'll get more work done faster and more efficiently. And you'll have peace of mind knowing that Land Pride will stand behind it.



Scan for full specs,
3D spins, features,
and product videos.





ALL-FLEX MOWERS

AFM4211: 30-65 HP

- 111W working width
- 6Deck overlap eliminates skidding
- Rear discharge decks
- Narrow transport width
- Professional series

AFM4214: 40-70 HP

- 14W working width
- 15or 18Deck tires
- Zero turning capabilities
- Standard antiscalp rollers

AFM4216: 40-70 HP

- 168W working width
- Three 7Deck
- 8Deck overlap for zero turning capabilities

AFM4522: 65-100 HP

- 119W working width
- Commercial duty 158blade spindle with cast iron housing
- 18Deck tires with sealant
- Rear discharge decks



GROOMING MOWERS

FDR16 Series: 15-40 HP

- 4860or 70W working width
- Rear discharge
- Single section belt
- 34x 10S gauge wheels
- 36Deck thickness
- 4834or 34cutting height
- 60or 7034or 54cutting height
- Medium lift blades standard
- Optional mulching blades available

FDR25 Series: 15-60 HP

- 70W working width
- Rear discharge
- Folding 3point
- 36Deck thickness
- S rubber tires
- Optional size available



FDR25



FLAIL MOWERS

FM25 Series: 33-80 HP

- 60or 70W working width
- Cutting capacity
- 1wuckfront knives
- 15w heavy duty Y knives
- 1w hammer knives
- 06Variable cutting height
- Additional sizes available for larger tractors



RTA12

ROTARY TILLERS

RTR05 Series: Up to 26 HP

- 4or 50W working widths
- 4C shape blades per flange
- 13Rttr swing diameter
- 6Maximum tilling depth
- Reverse rotation

RTA/RTR12 Series: 15-66 HP

- 4or 50or 58or 66or 74or 80W working widths
- Slipclutch drive
- 4C shape blades per flange
- 15Rttr swing diameter
- 6Maximum tilling depth
- Chaindrive system

RGA/RGR12 Series: 18-66 HP

- 50or 58or 66or 74or 80W working widths
- Slipclutch drive
- 6C shape blades per flange
- 17Rttr swing diameter
- 7Maximum tilling depth
- Geardrive system

RTA/RTR20 Series: 23-75 HP

- 70W working width
- 6C shape blades per flange
- 17Rttr swing diameter
- 7Maximum tilling depth

RTA/RTR25 Series: 25-75 HP

- 70W working width
- 6C shape blades per flange
- 17Rttr swing diameter
- 7Maximum tilling depth

RTA35 Series: 35-95 HP

- 76W working width
- Offset up to 5
- 6C shape blades per flange
- 19Rttr swing diameter
- 7Maximum tilling depth

RTA/RGA models are forward rotation. RTR/RGR models are reverse rotation.

*Tilling depth depends on conditions and fluffiness of tilled area. Multiple passes may be required.





ROTARY CUTTERS

RCR12 Series: 18-60 HP

- 48" x 60" working width
- Front and rear guards
- 13 1/4" cutting height

RCR15 Series: 20-60 HP

- 48" working width
- 13 1/4" x 11" cutting height
- 3' diameter cutting capacity

RCR18 Series: 20-90 HP

- 60" x 70" working width
- 3' diameter cutting capacity
- Fully welded deck

RCF20 Series: 20-65 HP

- 60" x 70" working width
- 3' diameter cutting capacity
- Smooth top design

RCF27 Series: 35-130 HP

- 60" working width
- 3' diameter cutting capacity
- Smooth top design
- Available for larger tractors



RCF20



ROTARY CUTTERS

RCR25 Series: 40-110 HP

- 80" x 10" working width
- 1 1/2' diameter cutting capacity
- chassis of tires

RCF30 Series: 40-110 HP

- 80" x 10" working width
- 1 1/2" cutting height
- 3' diameter cutting capacity

RCF36 Series: 40-130 HP

- 80" x 10" working width
- 10 Gauge deck fully welded
- 3' diameter cutting capacity

RC2512 Series: 40-100 HP

- 10" working width
- 10 Gauge deck thickness
- 7 Gauge side thickness
- 1 1/2' diameter cutting capacity
- Front and rear chain guards

RC2515: 50-100 HP

- 15" working width
- 10 Gauge deck thickness
- 1 1/4" Plate side thickness
- 1 1/2' diameter cutting capacity
- 13" cutting height

RC3712: 50-160 HP

- 10" working width
- 3' diameter cutting capacity
- 10 Gauge deck thickness
- 1 1/4" side thickness



RCF30



RC2512





SPREADERS

PTS Series: 15-50 HP

- 350 lb 563 lb capacity
- Pull type with ball
- Two hopper sizes
- Spill type broadcast spreader
- Ground driven
- Plate vanes and spinner

FSP Series: 15-20 HP Min.

- 350 lb 563 lb 673 lb capacity
- Catch
- Spill type broadcast for even spreading
- Adjustable delivery patterns

PFS Series: 15-20 HP Min.

- 95 lb 150 lb 240 lb capacity
- Penulum type
- Heavy duty tubular frame
- 0-46 ft spreading width
- Adjustable size available for larger tractors



SEED BED ROLLER

SBR Series: 18-52 HP

- 7-11 ft working width
- 11 roller diameter
- Optional tongue ball hitch
- Transport tires on pull type
- Optional Drag Harrow shown

DRAG HARROW

DRG Series: 8-16 HP

- 4-6-8 ft working widths
- 10-12 ft diameter
- High carbon steel tire construction
- Shown here on See-Dee Roller



COMPACT DRILLS

606NT Series: 40 HP Min.

- 6 ft working width
- End wheel roller
- Pull type
- Hydraulic depth stop

706NT Series: 55 HP Min.

- 7 ft working width
- End wheel roller
- Pull type
- 1 bu ft box capacity

ALL-PURPOSE SEEDERS

APS15 Series: 25-130 HP

- 48 ft working width
- Rear spike roller or 1 cast packer wheel roller
- 40 chain with spring loaded roller
- Optional small seed box
- Adjustable sizes available for larger tractors



MULTI-PURPOSE SEEDERS

MPS26: Cat. 2 or Pull-Type

- 7 ft working width
- Available in 3 point or pull type
- Regular and small seed boxes standard
- Optional native grass box with walkbar
- Packer roller ride
- Spike roller with adjustment handle
- Optional acremeter
- Adjustable sizes available for larger tractors





GRADING SCRAPERS

GS25



BOX SCRAPERS

BB25

- GS15 Series: 20-50 HP**
- 48x60 70 Working width
 - Heat-treated shanks
 - 1x6 cutting edges reversible replaceable
 - Replaceable skid shoes
 - Optional rear facing blade
 - Additional sizes available for larger tractors

- GS25 Series: 40-90 HP**
- 70x84 Working width
 - 4x4 Front beam
 - Heat-treated adjustable scarifier shanks
 - Replaceable skid shoes
 - Additional size available for larger tractors

TOP & TILT



Land Pride Top & Tilt Kits are versatile for your tractor 3-point hitch. These popular kits can be used to easily adjust the top link force and lift with a 3-point hitch operator can adjust a hydraulic accessory in an



implement raise and lower hydraulic shanks for example



GS15

- BB12 Series: 17-30 HP**
- 48x54 60 Working width
 - 15 Mounting bar
 - Reversible replaceable cutting edge
 - Additional size available for larger tractors

- BB15 Series: 17-40 HP**
- 60x66 70 Working width
 - 4 Position adjustable shanks
 - 17 Mounting bar
 - Reversible replaceable cutting edge

- BB25 Series: 25-55 HP**
- 60x66 70 84 Working width
 - 4 Position adjustable shanks
 - 17 Mounting bar
 - Clegg type lower hitch

- BB35 Series: 45-120 HP**
- 78x84 Working width
 - Cat 1 hitch
 - Form mounting bar 3 high
 - Double strap lower hitches
 - 4 Position shank
 - Back blade stand
 - Additional size available for larger tractors

- HR25 Series: 30-60 HP**
- 70 Working width
 - 1 Mounting bar
 - Rear back blade
 - Hydraulic retractable shanks



0010





DISC HARROWS

DH15

DH10 Series: Up to 40 HP

- 48" 60" Working widths
- Notched or smooth discs
- Square tube frame
- 7" I-beam spacing
- Adjust gangs up to 11

DH15 Series: Up to 65 HP

- 60" 70" 90" Working widths
- 18" Notched or smooth discs
- Adjustable gang angles
- 4 front 3 rear
- 7" I-beam spacing

DH35 Series: 45-100 HP

- 10" 1" Working widths
- 7" I-beam 9" I-beam spacing
- Angle front or rear gangs up to 18
- Notched or smooth discs
- Optional discs

CORE AERATORS

CA15 Series

- 48" 56" 64" Working widths
- Cat 1011 Lt
- 1" Harrow steel spring material
- 6" Spring spacing
- Up to 4" spring penetration
- Expandable metal weight tray



CA15

CA25 Series: Pull-Type

- 60" 70" Working widths
- Cat 1 hitch
- 5" 6" Spring spacing
- 4" Spring penetration
- Optional water tanks for additional weight
- Storage stand on each corner for stability



RB37 (Shown on MX tractor)

REAR BLADES

RB15 Series: 17-40 HP

- 60" 70" 84" Working widths
- Angle and offset capabilities
- 14" M-bow with replaceable cutting edge
- Adjustable size available for larger tractors

RB16 Series: 20-40 HP

- 60" 70" 84" Working widths
- Adjustable and offset capabilities
- Optional hydraulic angling
- 14" M-bow with replaceable cutting edge
- Adjustable size available for larger tractors

RB26 Series: 25-60 HP

- 70" 84" Working widths
- Adjustable and offset capabilities
- 17" M-bow with replaceable cutting edge
- Adjustable size available for larger tractors

RBT35 Series: 35-65 HP

- 84" Working width
- Manual hydraulic adjustments
- 3" M-bow kthgph
- Adjustable size available for larger tractors

RB37 Series: 35-80 HP

- 70" 84" Working widths
- Adjustable and offset capabilities
- 5" 6" M-bow thickness
- Adjustable size available for larger tractors



RBT35





LANDSCAPE RAKES

LR37

LR16 Series: 20-40 HP

- 60" 7" W"rk"hg w"ths
- 1" H"gh carb"n spr"ng steel teeth
- 7 Angle p"s"t"ns up t" 45"
- Rear "la"e a"ptable
- A"t"onal s"ze ava"lable f"r larger tract"rs

LR26 Series: 25-60 HP

- 84" W"rk"hg w"th
- 7 F"rwar" angles
- H"gh carb"n spr"ng steel teeth
- A"t"onal s"ze ava"lable f"r larger tract"rs

LR37 Series: 30-80 HP

- 84" W"rk"hg w"th
- 5 P"s"n angl"hg up t" 30"
- Rake "ffsets "6" left "r r"ght
- Rear "la"e a"ptable
- A"t"onal s"ze ava"lable f"r larger tract"rs



POST HOLE DIGGERS

SA20

PD10 Series: 15-30 HP

- 6" 9" an" 1" Augers
- 30 HP Gearb"x
- " Output shaft
- Ava"lable D"wn Pressure K"

PD15 Series: 20-40 HP

- 6" 9" an" 1" Augers
- " Output shaft
- Shear"p" protect"n
- 48" Auger length
- Ava"lable D"wn Pressure K"

PD25 Series: 25-55 HP

- 6" 4" Augers
- " Output shaft
- Cat"3 Dr"vel"he w"th shear"p" "r ra"bl"p" protect"n
- Ava"lable D"wn Pressure K"

PD35: 30-75 HP

- 6" 4" Augers
- " 8" Y"ke tub"hg
- " Gearb"x " output shaft
- Cat"3 Dr"vel"he w"th shear"p" "r ra"bl"p" protect"n
- Ava"lable D"wn Pressure K"

HD25: 5-12 GPM

- Cat"1 "r " bucket m"unt
- " 8" Tub"hg
- " Output shaft
- 6" 4" Augers
- Hy"raul" "r"ve

SA20 Series: 6-30 GPM

- Un"versal Qu"ck"Attach
- " bucket m"unt "pt"n
- 6" 36" Auger s"zes
- " 4" 30" "r 36" Tree auger
- " Output shaft



ROCK AUGERS

- 3" 5" H"gh strength tube
- 3" 4" D"uble fl"ght b"re head
- "ullet"style carb"e t"ps
- 1" 3" 4" Square shank" p"t
- 6" 9" 1" 15" 18"
- " 4" f"r SA"0 "nly



(Tips highlighted for illustration)





RIPPER SHANKS

RS15 Series: 35-80 HP

- cat1 □ 3point hitch
- Single ripper shank with shearbolt protection
- 47Ripping depth
- Parking stands



DITCHERS

DT55 Series: 60-150 HP

- 10Impeller
- Optional control chute
- Lubricate chain drive
- Optional gauge wheel
- Optional ripper shank
- Optional skid shoe



QUICK-HITCHES

QH16 Series: Cat. 1

- 1000 lb lifting capacity
- Automatic lock on lower 3point arms
- Optional flaring tip link



ARENA GRADERS

AG15 Series: 18-65 HP

- 60784Working widths
- 4Working depth
- Adjustable leveling bar
- Adjustable rolling basket mesh or pipe



SOIL PULVERIZERS

SP20 Series: 25-35 HP

- 607Working widths
- Heat-treated replaceable sleeves on spikes
- 3Steel shanks reversible

SP30 Series: 30-50 HP

- 7Working width
- Single steel spike roller
- Heat-treated replaceable sleeves on spikes



FIELD CULTIVATORS

FC10 Series: Up to 45 HP

- 48Working width adjustable to 57
- Cat1 hitch
- Spring steel chisels
- Replaceable tips

FC15 Series: Up to 50 HP

- 7Working width
- cat1 3point hitch
- 4Working depth
- x Square tubing frame
- Optional extensions create 96working width LP Exclusive
- Available hitch to pull LP Drag Harrow



RG10

CLAW GRAPPLES

SGC06 Series Claw Grapple

- 60" Working width
- High tensile AR400 steel
- 3" Jaw opening
- Optional 3rd Function Valve

SGC10 Series Claw Grapple

- 60" 7" Working width
- High tensile AR400 steel
- 43" Jaw opening
- Optional 3rd Function Valve



COMBO BUCKETS

CB10 Series: Up to 65 HP

- 60" 7" Working width
- 8" Max jaw opening
- Lower jaw Grade 80 steel
- 3/16" Steel panels
- 1" Hinge points

ROOT GRAPPLES

RG10 Series: Up to 54 HP

- 60" 7" Working width
- A36 Tite material
- 7" Jaw opening
- Available 3rd Function Valve

RG15 Series: 50-100 HP

- 7" 78" Working width
- A36 Tite material
- 36" Jaw opening
- Available 3rd Function Valve
- Grapple only



3RD FUNCTION VALVES

Land Pride 3rd Function Valve accessory kits are versatile and value to your tractor and are available for select Kubota tractors.



WOOD CHIPPERS

WC1503 Series: 12-30 HP

- 3" Lb capacity
- Harlene steel cutting knives
- 4" Rotor pulley diameter
- Adjustable support stands

WC1504 Series: 20-50 HP

- 4" Lb capacity
- 3/16" Main frame thickness
- Direct drive to motor
- 4 Harlene steel cutting knives
- Adjustable support stands



WEIGHT BOXES

WB10

- Cat 1 Quick Hitch compatible
- Shown with optional riser stand

WB15: 24-110 HP

- Cat 1 3" Quick Hitch compatible
- Up to 800 lb weight capacity



GR15

STUMP GRINDERS

GR1525 Series: 25-55 HP

- 3" Pitch Cat 1
- 4" Flywheel with carbide teeth
- 800-1000 rpm cutting wheel speed
- 10" Max cutting depth
- 7" Swing distance
- Slip clutch protected
- 1" Rotor thickness
- Sawtooth base for stability





BALE SPEARS

BS10 & BSR10

BS10

- 1800 lb lift capacity
- Usable spear length 45"
- Upper 19" lower 19"
- Universal QuickAttach

BSR10

- 1800 lb lift capacity
- 3-point cat 1 or cat 2
- Spear length 44"
- Usable upper 19" lower 19"

BSR20

- 3-point lift capacity at 4' from face of frame 3000 lb
- Usable spear length 44"
- Forge spear construction

BS20

- 2500 lb lift capacity
- Usable spear length 45"
- Forge spear construction
- Universal QuickAttach



PALLET FORKS

PFL30

PF20 Series

- Bucket mounted
- 2000 lb lift capacity
- 3' the width
- 1' the height

PFL20 Series

- Universal QuickAttach for front loader plate
- 2000 lb lift capacity
- 4' the width
- 1' the height

PFL30 Series

- Universal QuickAttach for front loader plate
- 3000 lb lift capacity
- 48" the length
- 1'4" the height





SNOW BLOWERS

SB15 Series: 18-59 HP

- 74" Working width
- 4" Diameter Impeller
- 16" Diameter auger
- 3-Point Rear hitch

Inverted/Hybrid 15-55 HP

- 54" or 64" or 74" Working width
- 6" or 4" x 7" Impeller
- 3-Point Inverted or Hybrid
- Optional hydraulic chute rotation

For all snowblower options please see the Snowblower brochure on kubota.ca

SNOW TRIP BLADES

STB10 Series: 25-40 HP

- 60" or 70" Working width
- 1" Curve pusher blade
- Dual trip springs for frame protection
- Hydraulic angle adjustment available
- AR400 skid shoes

STB15 Series: 30-70 HP

- 70" or 84" Working width
- Dual trip springs for frame protection
- 1" Curve pusher blade
- Hydraulic angle adjustment available
- AR400 skid shoes
- Optional lateral scissoring
- Additional size available for larger tractors



SNOW PUSHERS

SPL10 Series: 20-45 HP

- 60" or 70" or 84" Width
- Universal Quick Attach
- 4" Tall x 4" Deep
- 10 gal. Mulch bar with 1/4" spikes
- Optional rubber or steel blade
- Optional pullback blade
- Replaceable AR400 skid shoes



PERFORMANCE MATCHED

This process ensures you that the horsepower, rating, weight, and width of your implement matches your tractor's exact specifications



PRODUCTS IN ACTION

See products in action, view product spins, and find full specs and manuals at landpride.com



SHOPLANDPRIDE.COM

Find apparel, hats, cups, bags, bar stools, and more at ShopLandPride.com





A Division of Great Plains Mfg., Inc.
1525 E. North St. • P.O. Box 5060
Salina, Kansas 67401
Visit Kubota's Dealer Locator at kubota.ca

Revised by KCL
July 2026

Land Pride is a registered trademark of Great Plains Mfg., Inc.