

GR SERIES

OUTSTANDING TRACTION FOR DEMANDING JOBS

Kubota's GR Series is engineered to allow you to cover every inch of workspace with its tight turning radius and outstanding traction. And regardless of the job at hand, we have the perfect attachment for you to get it done efficiently and with ease. In fact, winter might just be your best season yet.



SNOWBLOWER



SNOW BLADE



SWEEPER

ATTACHMENT SPECS

SNOW BLADE

	Description	GR2705	GR2848
Hitch	Hitch Type	Front/Direct Mount	Front/Fun Connect
General	Blade Type	Straight	Straight
	Angle Type	Manual	Manual
	Maximum Width (Length)	48″	48″
	Maximum Pivot Angle (Degrees)	30 degrees	30 degrees
	Cutting Width @ Max Degrees Angle	41″	41″
	Cutting Edge	Reversible	Reversible
	Skid Shoes	STD & Adjustable	STD & Adjustable
	Moldboard Height	15 1/2″	17″
	Moldboard Thickness	12 GA	12 GA
	Base Equipment weight	–	141 lbs
	Steel Cutting Edge Replacement	Yes	Yes

SWEEPER

	Description	GR2847
Hitch	Hitch Type	Front/Fun Connect
General	Height	19″
	Overall Width	49 1/2″
	Working Width	43″
	Maximum Pivot Angle (Degrees)	18 degrees
	Working Width @ Max Angle	40 3/4″
	Brush Type	100% polypropylene (as std)
	Brush Diameter	18″
	Main Housing Thickness	14 GA
	Weight	114 lbs

SNOWBLOWER

	Description	GR2728	GR2846
General	Hitch Type (Front / Rear Mount)	Front/Direct Mount	Front/Fun Connect
	Drive Type	PTO	PTO
	Approx. Shipping Weight (LBS.)	260	260
	Overall Width	46″	46″
	Working Width	46″	46″
	Working Height	18 1/2″	17″
	Overall Length (w/hitch)	42 1/2″	43″
Impeller	Impeller Width	5″	5 1/2″
	Number of Impeller Blades	3	3
Auger	Auger Drive	Roller Chain #40	Roller Chain #40
	Auger Diameter	12 1/2″	12 3/4″
Housing	Housing Thickness	14 GA	16 GA
	Side Panel Thickness	12 GA	12 GA
Chute	Rotation of Chute	Manual (Electric Optional)	Electric
	Deflector Adjustment	Manual (Electric Optional)	Manual (Electric Optional)
Cutting Edge	Replaceable	Yes	Yes
Skid Shoes	Replaceable and Adjustable	Yes	Yes

AVAILABLE SERIES MODELS:

GR2020
GR2120