

OUTSTANDING TRACTION FOR DEMANDING JOBS

Kubota's GR Series is engineered to allow you to cover every inch of workspace with its tight turning radius and outstanding traction. And regardless of the job at hand, we have the perfect attachment for you to get it done efficiently and with ease. In fact, winter might just be your best season yet.





SNOW BLADE



SWEEPER

ATTACHMENT SPECS

		Description	GR2705	GR2848				Description	GR2847
SNOW BLADE	Hitch	Hitch Type	Front/Direct Mount	Front/Fun Connect		SWEEPER	Hitch	Hitch Type	Front/Fun Connect
	General	Blade Type	Straight	Straight			General	Height	19"
		Angle Type	Manual	Manual				Overall Width	49 1/2"
		Maximum Width (Length)	48"	48"				Working Width	43"
		Maximum Pivot Angle (Degrees)	30 degrees	30 degrees				Maximum Pivot Angle (Degrees)	18 degrees
		Cutting Width @ Max Degrees Angle	41"	41"				Working Width @ Max Angle	40 3/4"
		Cutting Edge	Reversible	Reversible				Brush Type	100% polypropylene (as std)
		Skid Shoes	STD & Adjustable	STD & Adjustable				Brush Diameter	18"
		Moldboard Height	15 1/2"	17"				Main Housing Thickness	14 GA
		Moldboard Thickness	12 GA	12 GA				Weight	114 lbs
		Base Equipment weight	-	141 lbs				Wolght	
		Steel Cutting Edge Replacement	Yes	Yes					

		Description	GR2728	GR2846
		Hitch Type (Front / Rear Mount)	Front/Direct Mount	Front/Fun Co
		Drive Type	PTO	PT0
		Approx. Shipping Weight (LBS.)	260	260
	General	Overall Width	46"	46"
		Working Width	46"	46"
		Working Height	18 1/2"	17"
EB		Overall Length (w/hitch)	42 1/2"	43"
N		Impeller Width	5"	5 1/2"
SNOWBLOWER	Impeller	Number of Impeller Blades	3	3
MO	A.1.90%	Auger Drive	Roller Chain #40	Roller Chain
NS	Auger	Auger Diameter	12 1/2"	12 3/4"
•,	Housing	Housing Thickness	14 GA	16 GA
	Housing	Side Panel Thickness	12 GA	12 GA
	Chute	Rotation of Chute	Manual (Electric Optional)	Electric
	Giute	Deflector Adjustment	Manual (Electric Optional)	Manual (Electric Opt
	Cutting Edge	Replaceable	Yes	Yes
	Skid Shoes	Replaceable and Adjustable	Yes	Yes

AVAILABLE SERIES MODELS: GR2020 GR2120

