



Land Pride & Kubota Standard L Tractor Series, Performance Matched Implements, Attachments & Loader Attachments

Performance Matched Standard L Series Implements

IMPLEMENT TYPE	MODEL	MOUNTING TYPE	WEIGHT (LBS)	WORKING WIDTH	L2502	L3302	L3902	L4802
	CA1556**		170 lbs	50"	√	√	✓	√
Acretore	CA1564**		184 lbs	58"	✓	✓	✓	✓
Aerators	CA1572**	3-Point Hitch Cat 1	208 lbs	66"	✓	✓	✓	✓
	CA2560**		464 lbs	60"	√	✓	✓	✓
	CA2572**		480 lbs	72"	✓	✓	✓	√
	AG1560		338 lbs	60"	√	√	✓	√
Arena Graders	AG1572	3-Point Hitch Cat 1	373 lbs	72"	✓	✓	✓	√
	AG1584		409 lbs	84"	✓	✓	✓	✓
	AFM3011		2040 lbs	11'	Χ	Χ	✓	√
All Flex Mowers	AFM4211	Drawbar Pull-Type	3000 lbs	11'	X	X	✓	✓
	AFM4214		3315 lbs	14'	X	X	X	✓
	BB1260		346 lbs	60"	✓	Χ	X	Х
	BB1266	3-Point Hitch Cat 1	370 lbs	66"	✓	X	X	Χ
	BB1560		428 lbs	60"	✓	✓	✓	X
	BB1566		450 lbs	66"	✓	✓	✓	X
Box Blades	BB1572		504 lbs	72"	Χ	✓	✓	✓
DOX Diaues	BB2572		549 lbs	72"	Χ	✓	✓	✓
	BB2584		593 lbs	84"	Х	Х	X	✓
	MR1572		615 lbs	72"	Х	✓	✓	✓
	HR2572		851 lbs	72"	Х	✓	✓	✓
	DH1048		421 lbs	48"	√	√	✓	Х
	DH1060		533 lbs	60"	✓	✓	✓	Х
Disk Harrows	DH1560	3-Point Hitch Cat 1	628 lbs	60"	√	✓	✓	✓
	DH1572		714 lbs	72"	Х	X	Х	√
	DH1590		865 lbs	90"	Х	Х	Х	✓
Ditcher	DT35	3-Point Hitch Cat 1	390 lbs	18"	Χ	✓	✓	√
	DRG04		89 lbs	48"	✓	✓	√	✓
Drag Harrows	DRG06	Drawbar Pull-Type	138 lbs	72"	√	√	✓	√
	DRG08		185 lbs	96"	✓	✓	✓	✓
Field Cultivator	FC10	3-Point Hitch Cat 1	135 lbs	48"-57"	✓	✓	✓	✓
Tielu Guillyaloi	FC15	3-1 Omit inton Oat 1	290 lbs	75"	✓	✓	✓	✓

✓ - Available X - Unavailable



	FM2560		974 lbs	60"	Х	√	✓	✓
Flail Mowers	FM2672	3-Point Hitch Cat 1	1040 lbs	72"	Х	✓	✓	✓
	FM2584		1236 lbs	84"	X	Х	Х	√
Food Plot Seeder	FPS48**	Drawbar Pull-Type	370 lbs	54"	√	√	√	√
	GS0560		350 lbs	60"	√	√	Х	Х
	GS1548		437 lbs	48"	✓	√	√	✓
Grading Scrapers	GS1560	3-Point Hitch Cat 1	511 lbs	60"	X	✓	✓	✓
	GR1572		594 lbs	72"	X	✓	✓	✓
	GR2572		728 lbs	72"	Х	X	X	✓
	FDR1660		577 lbs	60"	✓	√	√	Х
Grooming Mowers	FDR1672	3-Point Hitch Cat 1	619 lbs	72"	✓	√	✓	Х
Orderning mowers	FDR2572	3-1 OINCTINGIT CALT	718 lbs	72"	✓	✓	✓	√
	FDR2584		812 lbs	84"	X	√	√	✓
	LR1660		241 lbs	60"	<u>√</u>	√	✓	X
	LR1672		270 lbs	60"	√	√	√	X
	LR1684		291 lbs	72"	✓	1	√	X
Landscape Rakes	LR1696	3-Point Hitch Cat 1	316 lbs	96"	✓	√	√	X
Lanuscape Nakes	LR2684		330 lbs	84"	Х	√	√	√
	LR2696		348 lbs	96"	X	✓	√	√
	LR3784	3-Point Hitch Cat 1,2	460 lbs	84"	X	✓	√	✓
	LR3796		483 lbs	96"	X	✓	√	✓
Moldboard Plows	MP10	3-Point Hitch Cat 1	294 lbs	14"	√	√	√	√
	MP20		513 lbs	27.5"	X	√	✓	✓
	PD15**		161 lbs	6", 9", 12"	√	√	✓	Х
	PD25**		186 lbs		Х	√	✓	✓
	PD35**	3-Point Hitch Cat 1	233 lbs	6", 9", 12"	Х	✓	√	✓
Post Hole Diggers	HD25**		235 lbs	15", 18" & 24"-36" Tree	✓	✓	√	✓
	HD25**	Loader Mount	268 lbs	Auger	✓	✓	✓	√
	SA20**		173 lbs		✓	√	✓	√
	PR1660		980 lbs	60"	Х	√	√	√
Powered Rakes	PR1672	3-Point Hitch Cat 1	1000 lbs	72"	X	√	√	✓
	PR1690		1150 lbs	90"	X	X	√	√
	RB1560		248 lbs	60"	<u>/·</u>	√	√	X
	RB1572		269 lbs	72"	√	√	√	X
	RB1584		289 lbs	84"	· ✓	√ ·	√ ·	X
	RB1660		283 lbs	60"	· ✓	√ ·	√	X
Rear Blades	RB1672	3-Point Hitch Cat 1	297 lbs	72"		√	√	X
	RB1684		319 lbs	84"	→	√	√	√
	RB2672		369 lbs	72"		√	√	√
	RB2684		396 lbs	84"	X	√	√	√
	RB2696		425 lbs	96"	X	X	X	√
Ripper Shanks	RS15	3-Point Hitch Cat 1	210 lbs	41"	X	X	✓	√
Tappor Origina	1.010	3 i dilit illoii dat i	210 100	. 1			,	•

	RCR1248		400 lbs	48"	✓	✓	✓	✓
	RCR1260		496 lbs	60"	✓	✓	✓	✓
	RCR1272		568 lbs	72"	√	√	✓	√
	RCR1548		424 lbs	48"	√	·	· ✓	·
Rotary Cutters	RCR1860	3-Point Hitch Cat 1	599 lbs	60"				
					√	√	√	√
	RCR1872		737 lbs	72"	X	✓	✓	✓
	RCF2060		620 lbs	60"	✓	✓	✓	✓
	RCF2072		745 lbs	72"	Х	✓	✓	✓
	RTR1250		435 lbs	50"	✓	✓	✓	X
	RTR1258		463 lbs	58"	✓	✓	✓	✓
	RTR1266		493 lbs	66"	✓	✓	✓	✓
	RTR1274		521 lbs	74"	Χ	✓	✓	✓
	RTR1282		582 lbs	82"	Х	X	X	✓
Rotary Tillers	RGR1250	3-Point Hitch Cat 1	497 lbs	50"	✓	✓	✓	✓
(Reverse Turning)	RGR1258		530 lbs	58"	✓	✓	✓	✓
	RGR1266		567 lbs	66"	✓	✓	✓	✓
	RGR1274		601 lbs	74"	X	✓	✓	✓
	RGR1282		653 lbs	82"	X	Х	X	✓
	RTR1574		508 lbs	74"	X	✓	✓	✓
	RTR2570		868 lbs	70"	X	✓	✓	✓
	RTA1250		421 lbs	50"	✓	✓	✓	X
	RTA1258	3-Point Hitch Cat 1	448 lbs	58"	✓	✓	✓	✓
	RTA1266		476 lbs	66"	✓	✓	✓	✓
	RTA1274		503 lbs	74"	X	✓	✓	✓
Rotary Tillers	RTA1282		552 lbs	82"	X	X	X	✓
(Forward Turing)	RGA1250		493 lbs	50"	✓	✓	✓	X
	RGA1258		526 lbs	58"	✓	✓	✓	✓
	RGA1266		562 lbs	66"	√	✓	√	✓
	RGA1274		596 lbs	74"	X	√	√	√
	RGA1282		647 lbs	82"	X	X	X	√
	RTA3576		856 lbs	76"	X	Х	Х	✓
Scarifiers	SF2566	3-Point Hitch Cat 1	208 lbs	60"	X	✓	✓	✓
- Courmons	SF2577	o i omit i mon out i	235 lbs	72"	Χ	✓	✓	✓
	SBR72-3PT	3-Point Hitch Cat 1	486 lbs	69"	√	√	√	√
Seedbed Rollers	SBR72-PT	Drawbar Pull-Type	577 lbs	69"			· ✓	√
	JDIN/Z-F I	Diawbai Full-Type	311 103		V	✓	V	V
Snowblowers	K54-22-06		460 lbs	54" ext. to 60"	✓	✓	✓	X
(Rear Mount)	K64-24-07INV		540 lbs	64"	✓	✓	✓	✓
,	K64-24-07	3-Point Hitch Cat 1	600 lbs	64" ext.	√	✓	√	✓
	1.04-24-07		000 ID3	To 69" 74" ext.	V	V	V	V
	K74-24-09		640 lbs	To 79"	Х	Х	✓	✓
	SP2060**		491 lbs	60"	✓	✓	✓	X
Soil Pulverizer	SP2072**	3-Point Hitch Cat 1	561 lbs	72"	✓	✓	✓	X
July altonizor	SP3072**		671 lbs	72"	X	✓	✓	✓
	SP3084**		721 lbs	84"	X	X	✓	✓
Spike-Tooth Harrow	STH1590	Drawbar Pull-Type	237 lbs	90"	✓	√	✓	√



	FSP500**		119 lbs	37"	✓	✓	✓	✓
	FSP700**		128 lbs	44"	✓	✓	✓	✓
	FSP1000**		139 lbs	47"	✓	✓	✓	✓
Spreaders	PFS4000**	3-Point Hitch Cat 1	196 lbs	46"	✓	✓	✓	✓
оргошиото	PFS5060**		287 lbs	55"	✓	✓	✓	✓
	PFS8010**		403 lbs	75"	✓	✓	✓	✓
	PTS500**	Drawbar Pull-Type	165 lbs	37"	✓	✓	✓	✓
	PTS700**		176 lbs	44"	✓	✓	✓	✓
Straw Crimper	CR2572**	3-Point Hitch Cat 1	475 lbs	69"	✓	✓	✓	✓
Wood Chippers	WC1503	3-Point Hitch Cat 1	369 lbs	3"	√	✓	Χ	Х
Wood Chippers	WC1504		450 lbs	4"	✓	✓	✓	✓
Weight Box	WB10	3-Point Hitch Cat 1	Quick Hitch Compatible	n/a	√	✓	✓	√
Rear Quick Hitch	QH10	3-Point Hitch Cat 1	68 lbs	n/a	✓	✓	✓	✓
	QH15		70 lbs	n/a	✓	✓	✓	✓
	QH16		70 lbs	n/a	✓	✓	✓	✓

Performance Matched Standard L Series <u>Attachments</u>

TRACTOR ATTACHMENTS	MODEL	MOUNTING TYPE	WEIGHT (LBS)	WORKING WIDTH	L2502	L3302	L3902	L4802
Loader & Buckets	LA526FL ¹	Direct Pin Type	986 lbs	60"	✓	✓	✓	X
	LA5261	2-Lever Quick Attach	1070 lbs	66"	✓	✓	✓	X
	LA765 ¹		1455 - 1552 lbs	72"	X	X	X	√
Backhoe & Buckets	BH77	4 Daint Maunt	n/a	10", 12", 16" 24"	✓	✓	✓	X
	BH92	4-Point Mount	n/a	12", 16", 18" 24", 36"	X	X	X	✓

¹⁻ Requires Ballast



Performance Matched Standard L Series Loader Attachments

LOADER ATTACHMENTS	MODEL	MOUNTING TYPE	WEIGHT (LBS)	WORKING WIDTH	L2502	L3302	L3902	L4802
Bale Spears	BS10 ¹		156 lbs	50"	✓	✓	✓	√
	BS20 ¹	2-Lever Quick Attach	196 lbs	50"	✓	✓	✓	√
Combo Bucket	CB1060 ¹	2-Lever Quick Attach	360 lbs	60"	✓	✓	✓	X
Combo Buokot	L22451	2 Lovor Quion / maon	620 lbs	72"	X	X	X	✓
	SGC0660 ¹		250 lbs	60"	✓	✓	√	Х
Grapple	SGC1060 ¹	2-Lever Quick Attach	389 lbs	60"	✓	✓	✓	✓
	SGC1072 ¹		447 lbs	72"	✓	✓	✓	✓
	PFL1242 ¹	2-Lever Quick Attach	228 lbs	42"	√	√	√	Х
Pallet Forks	PFL2042		301 lbs	42"	✓	✓	✓	✓
(Loader Mount)	PFL3042		340 lbs	42"	X	X	✓	✓
	PFL3048		358 lbs	48"	Х	Х	√	✓
On any Break and	SPL1060 ¹		346 lbs	60"	√	✓	√	✓
Snow Pushers (Loader Mount)	SPL10721	2-Lever Quick Attach	377 lbs	72"	✓	✓	✓	✓
	SPL1084 ¹		377 lbs	84"	X	X	X	✓
Anala Blada	STB10721		403 lbs	72"	✓	√	✓	Х
Angle Blades (Loader Mount)	STB15721	2-Lever Quick Attach	661 lbs	72"	X	X	X	✓
	STB1584 ¹		648 lbs	84"	X	X	X	✓

¹⁻ Requires Ballast

Notice:

The above identified implements are either manufactured by Kubota or have received an Engineering Release approving use by Kubota, and thus meet the performance matching requirements for the specified power machines for normally anticipated operating conditions. The specifications above are intended for general application; unusual soil, terrain, or severe operating conditions may not allow for the use of a specific implement under those operating conditions. The use of implements or attachments which are neither manufactured or approved by Kubota for use with the specified power machines and which do not meet the above specifications may result in malfunctions or damage to the power machine, damage to other property and/or injury to the operator or to others. Any such malfunctions or damages are not covered by the Kubota express limited warranty. The power machine, implement, and operating conditions need to be evaluated and monitored by the operator to be sure that the conditions are within a safe operating envelope for general use.

- Check with the tractor manual to verify for proper ballasting when using an implement or attachment on the machine.
- Additional kits (Rear Remotes, Third Function valves, etc.) may be required to use any of the above implements. Check with your local dealer to determine what is needed for proper fitment and operation.
- (**) This implement/attachment is approved for the base weight, but allows for additional ballasting (concrete blocks, seed, water tanks). Verify with the tractor manual and ensure proper ballasting before adding any additional weight to the implement/attachment.

Kubota Canada Ltd. notes that specifications and technical information are subject to changes without notice and Kubota does not represent or warrant that the information in this publication is completely accurate or current; however, Kubota used reasonable efforts to set forth and include accurate and up to date information in this publication. Kubota disclaims all representations and warranties, whether express or implied, including, but not limited to, warranties of merchantability and fitness for a particular purpose and Kubota shall not be liable for any damages, whether compensatory, direct, indirect, incidental, special, or consequential, arising out of or in connection with the use of this publication, or in the information therein.

