

RTV SERIES

DON’T LET SNOW SLOW YOU DOWN

Meet the line up of utility vehicles that goes from summer to winter-ready in a matter of seconds. The RTV Series is powered by Kubota’s durable and high-performing diesel engine, giving you plenty of horsepower for snowblowing, snow clearing and sweeping. With optional cold weather utility cabs, the weather may be cooling down, but for the RTV Series, things are just heating up.



SNOWBLOWER



SNOW BLADE



SWEEPER

ATTACHMENT SPECS

SNOW BLADE

	Description	V5008	V5290	V5291	V5294A	V5295A	V4308
Model Compatibility	Series	RTV-X, RTV-X CAB, RTV-X CAB HD, RTV-X LONG BED, RTV-X CREW	RTV-X, RTV-X CAB, RTV-X CAB HD	RTV-X, RTV-X CAB, RTV-X CAB HD	RTV-X, RTV-X CAB, RTV-X CAB HD, RTV-X LONG BED, RTV-X CREW	RTV-X, RTV-X CAB, RTV-X CAB HD, RTV-X LONG BED, RTV-X CREW	RTV520
Hitch	Hitch Type	A-Frame	Quick Hitch	Quick Hitch	K Connect	K Connect	Quick Hitch
General	Blade Type	Straight Blade	Straight Blade	V Blade	Straight Blade	V Blade	Straight Blade
	Angle Type	Manual (Optional Hydraulic)	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Manual (Optional Electric)
	Maximum width (Length)	72″	72″	72″	78″	78″	60″
	Maximum Pivot Angle (Degrees)	28 degrees	29 degrees	30 degrees	30 degrees	30 degrees	30 degrees
	Cutting Width @ Max Degrees Angle	64 3/5″	64 3/5″	66″ in V Position	68″	69 1/2″ in V Position	52″
	Cutting Edge	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable	Replaceable	Replaceable	Replaceable
	Skid Shoes	Yes	Yes	Yes	Yes	Yes	Yes
	Moldboard Height	19″	24 3/16″	22 5/16″	24″	24″	22″
	Moldboard Thickness	12 GA	10 GA	3/16″	14 GA	14 GA	12 GA
	Base Equipment Weight	238 lbs	255 lbs	300 lbs	220 lbs	290 lbs	185 lbs
Optional Equipment	Hard Plastic/Poly Cutting Edge	No	No	No	Yes	Yes	Yes

SNOWBLOWER

	Description	V5296
Model Compatibility	Series	RTV-X, RTV-X CAB, RTV-X CAB HD
General	Hitch Type (Front / Rear Mount)	K Connect Quick Hitch
	Blower Type	2 Stage
	Approx. Shipping Weight	540 lbs
	Working Width	66″
	Working Height	20″
	Overall Length (w/hitch)	30″
Impeller	Impeller Width	5 5/8″
	Number of Impeller Blades	4
Auger	Auger Drive	Gear
	Auger Diameter	12 3/4″
Housing	Housing Thickness	12 GA
	Side Panel Thickness	12 GA
Chute	Rotation of Chute	Hydraulic
	Deflector Adjustment	Hydraulic
Cutting Edge	Replaceable	Replaceable & Reversible
Skid Shoes	Replaceable and Adjustable	Adjustable and Replaceable

SWEEPER

	Description	V5266	V5260
Model Compatibility	Series	RTV-X, RTV-X CAB, RTV-X CAB HD	RTV-X, RTV-X CAB, RTV-X CAB HD
Hitch	Hitch Type	K Connect	Quick Hitch
	Drive Type	K Connect PTO	Hydraulic
General	Height	25″	25″
	Overall Width	70 1/2″	75 3/8″
	Working Width	65 1/2″	60
	Maximum Pivot Angle (Degrees)	25 degrees	25 degrees
	Working Width @ Max Angle	59 1/2″	55″
	Brush Type	Standard: 100% Poly	Standard: 100% Poly
	Main Housing Thickness	16 GA	16 GA
	Side Housing Thickness	12 GA	12 GA
	Approx. Shipping Weight	480 lbs	360 lbs
Optional Equipment	Dust Deflector	Yes	Yes
	50/50 Poly Brush	Yes	No

ATTACHMENT SPECS

		Description	V5002A	V5003A	V5004	V5005
SPREADER	**Model Compatibility**	Series	RTV-X & RTV-X CAB	RTV-X & RTV-X CAB	RTV-X, RTV-X CAB, RTV-X CAB HD	RTV-X, RTV-X CAB, RTV-X CAB HD
	Material Compatibility	Bagged Rock Salt	Yes	No	Yes	Yes
		Bagged Ice Melters	No	Yes	Yes	Yes (w/ V4407)
		Calcium Chloride Pellets	No	Yes	Yes	Yes (w/ V4407)
		Calcium Flakes	No	Yes	Yes	Yes (w/ V4407)
		Bulk Salt	No	No	Yes	Yes
		50/50 Sand Salt Mix	No	No	Yes	Yes
		Granular Fertilizer & Turf Care Materials	No	Yes	No	Yes (w/ V4407)
	General	Mounting Method	Rear hitch mount	Rear hitch mount	Cargo Bed Mounted	Cargo Bed Mounted
		Material Compatibility	Bagged Rock Salt	Bagged Ice Melters Calcium Chloride Pellets Calcium Flakes Granular Fertilizer/Turf Care Materials	Bagged Rock Salt Bagged Ice Melter's Calcium Chloride Pellets Calcium Flakes Bulk Salt 50/50 Sand Salt Mix	Bagged Rock Salt Bagged Ice Melter's Calcium Chloride Pellets* Calcium Flakes* Bulk Salt 50/50 Sand Salt Mixture Granular Fertilizer/Turf Care Materials* Top Dressing/Infield Sand Seed Starter Mulch Grass Seed* Lime Pellets* * Requires V4407 Control Tube
		Volume Capacity	3.0 cu ft (85L)	3.0 cu ft (85L)	6.0 cu ft (170L)	11.0 cu ft (311L)
		Weight Capacity	240 lbs (109kg)	240 lbs (109kg)	480 lbs (218kg)	800 lbs (363kg)
		Spreading Width	20' (6m)	20' (6m)	36" (0.9m)	30' (9.1m)
		Spinner	10" (254mm)	10" (254mm)	N/A	12" (305mm)
		Spinner Material	Nylon/Glass Reinforced (resin)	Adj fin Stainless Steel	N/A	Powder Coated Steel
		Auger	3" vertical high-flow auger	N/A	N/A	3" Diameter
		Feedgate	N/A	Electronically Controlled	N/A	N/A
		Hopper Dimensions	22" x 30" (559mm x 762mm)	22" x 30" (559mm x 762mm)	20.25" x 48" (514mm x 1219mm)	53" x 48.5" (1346mm x 1232mm)
		Overall Dimensions	22" x 30" x 32" (559mm x 762mm x 813mm)	22" x 30" x 32" (559mm x 762mm x 813mm)	24" x 49.5" x 28" (610mm x 1257mm x 71.1mm)	64" x 48.5" x 27" (1626mm x 1232mm x 686mm)
		Empty Weight	70 lbs	75 lbs (34kg)		280 lbs (127kg)
		Motors	Dual Electric, 12V, Semi-Sealed	Dual Electric, 12V, Semi-Sealed	Direct Drive, 12V, Sealed	12V, Semi-Sealed





AVAILABLE SERIES MODELS:

RTV520
RTV-X
RTV-X CREW
RTV-X CAB
RTV-X CAB HD
RTV-X LONG BED