



For Earth, For Life
Kubota

M

KUBOTA DIESEL TRACTOR M6S-111 ROPS

A clean running engine with the power and speeds to tackle a wide range of jobs.

The standard economy tractor M6S-111 ROPS can take on a variety of tasks. Ideal for hay and cattle operations and outstanding performance for uses such as loader work, haying operations, mowing and more.

Technology Driven Engine Features

The M6S-111 ROPS is equipped with a Kubota turbocharged V3800 Tier IV Final engine which has a Common Rail System (CRS), intercooler and Exhaust Gas Recirculation (EGR). Employment of a Diesel Particulate Filter (DPF) and a Selective Catalytic Reduction (SCR) system for minimized emissions. Additionally, it also has a RPM Memory to recall preferred engine RPM settings with the touch of a button and Constant RPM Management to keep the engine speed constant for stable operation.

Horse Power

Engine gross power (97/68EC): 114.1 HP
PTO power at rated engine RPM: 95.0 HP

Weight

The M6S-111 4WD has gained additional weight from the previous model, weighting 8466 lbs. With its weight and stability, it can now handle more tasks with its best performance.

Dimensions



16 Speed Swing Shift Transmission

The M6S-111 ROPS comes with 4 gears on main shift, High/Low range gear shift and a Swing Shift. Swing Shift adds 4 more speeds to the main shift by actuating the electric-over-hydraulic High/Low synchronized range shift- giving you access to a total of 8 speeds! The optional creep provides additional 8 speeds, therefore, 24F/24R speeds.

32 Speed Swing Shift Plus Transmission

The M6S-111 ROPS has a model that has Dual Speed as a standard. Swing Shift and Dual Speed can be easily operated with the main shift lever. With the use of optional creep, it has 48F/48R speeds! Put this feature to best use when in varying tractor load environments like working in mixed soil conditions or during hay tool applications. It is surely enough for the most demanding and precise work.

De-Clutch Switch on the Main Shift Lever

The de-clutch switch allows you to shift a gear without using the clutch pedal. This switch electro-hydraulically disengages the clutch while being pressed and reengages once the button is released.

High Hydraulic Performance

The M6S-111 ROPS comes with 2 standard rear remote valves and can add an additional valve. Standard valves are one self-cancelling detent valve and one floating detent valve. With 17.6 GPM flow and an optional third

remote valve, this tractor is ready to accept implements requiring multiple valves.

Other Features

- Electro Hydraulic Shuttle
- Steering tilt angle up to 40 degrees
- Fuel tank capacity of 46 gallons
- Easier to refill fuel and DEF by locating the filler neck on the lefthand side
- Large LCD monitor improved visibility and operation
- Redesigned floor layout to ensure leg space and improved ride comfort



Brochure Disclaimer:
This brochure contains information that **may not** be accurate for the Canadian Market.

Specifications

Model			M6S-111 ROPS
			SDS2
Wheel drive			4WD
Engine			
Type (make: Kubota)			V3800-TIEF4-Direct Injection, Water-cooled 4 Cycle Diesel, Common Rail System, Turbocharger, Intercooler, DPF, DOC, SCR
Cylinders and displacement	cu. in. (cc)		4-cylinder, 230 (3769)
Engine gross power (97/68EC)	HP (kW)		114.1 (85.1)
PTO power (at rated RPM)	HP (kW)		95 (70.8)
Alternator	Amp		80
Rated engine speed	rpm		2600
Fuel tank capacity	gal. (ℓ)		46 (175)
Transmission			
No. of speeds	Standard		F32 R32
	Creep (opt.)		F48 R48
Traveling speed	mi/h (km/h)		1.31 – 23.34 (2.11 – 37.56)
Shuttle			Electro-hydraulic
Clutch			Hydraulic Wet Clutch
Rear wheel brake			Hydraulic Wet Disk Type
Mechanical differential lock			Front / Rear
PTO			
Clutch			Hydraulic Wet Clutch
Revolution	rpm		540/1000
Hydraulics			
Type			Open-Center
Draft control			Top Link Draft Sensing
Lift capacity at 24 in. behind lift point (OECD)	lbs. (kg)		3858 (1750), 5732 (2600) with 2 assist cylinders (option)
Lower link			Telescopic
Category			II
Rear remotes			2 standard (3rd & flow control valve optional)
Pump output (remote)	gal/min (ℓ/min)		17.6 (66.6)
Exterior			
Hood			Full-open
Dimensions			
Wheel base	in. (mm)		95.9 (2435)
Minimum ground clearance*	in. (mm)		16.9 (430)
Tread*	Front	in. (mm)	62.2, 66.1 (1580, 1680)
	rear	in. (mm)	67.2, 73.2, 75.0, 81.1 (1705, 1860, 1905, 2060)
Overall length	in. (mm)		163.2 (4145)
Overall height (ROPS unfolded)	in. (mm)		105 (2670)
Overall width	in. (mm)		92.5 (2350)
Weight	lbs. (kg)		8466 (3840)
Turning radius w/o brake	ft. (m)		15.4 (4.7)
Standard tires	Front		13.6 – 24
	rear		18.4 – 34 Cast

* When standard tires are equipped

Kubota Canada Ltd. reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for Canada only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

©2017 Kubota Corporation



KUBOTA CANADA LTD.

Head Office:
1155 Kubota Drive, Pickering, Ontario L1X 0H4
TEL: (905) 294-7477

Visit our web site at: www.kubota.ca

