

Land Pride & Kubota LX Tractor Series, Performance Matched Implements, Attachments & Loader Attachments

Performance Matched LX20 Series *Implements*

IMPLEMENT TYPE	MODEL	MOUNTING TYPE	WEIGHT (LBS)	WORKING WIDTH	LX2620	LX3520	LX4020
Aerators	CA1548**	3-Point Hitch Cat 1	156 lbs	41"	✓	✓	✓
	CA1556**		170 lbs	50"	✓	✓	✓
	CA1564**		184 lbs	58"	✓	✓	✓
	CA1572**		208 lbs	66"	✓	✓	✓
	CA2560**		464 lbs	60"	✓	✓	✓
	CA2572**		480 lbs	72"	✓	✓	✓
Arena Graders	AG1560	3-Point Hitch Cat 1	338 lbs	60"	✓	✓	✓
	AG1572		373 lbs	72"	✓	✓	✓
	AG1584		409 lbs	84"	✓	✓	✓
Box Blades	BB1248	3-Point Hitch Cat 1	316 lbs	48"	✓	✓	✓
	BB1254		325 lbs	54"	✓	✓	✓
	BB1260		346 lbs	60"	✓	✓	✓
	BB1266		370 lbs	66"	✓	✓	✓
	BB1560		428 lbs	60"	✓	✓	✓
	BB1566		450 lbs	66"	✓	✓	✓
	BB2560		471 lbs	60"	✓	✓	✓
	BB2566		500 lbs	66"	✓	✓	✓
Disk Harrows	DH1048	3-Point Hitch Cat 1	421 lbs	48"	✓	✓	✓
	DH1060		533 lbs	60"	✓	✓	✓
	DH1560		628 lbs	60"	✓	✓	✓
	DH1572		714 lbs	72"	X	✓	✓
Drag Harrows	DRG04	Drawbar Pull-Type	89 lbs	48"	✓	✓	✓
	DRG06		138 lbs	72"	✓	✓	✓
	DRG08		185 lbs	96"	✓	✓	✓
Field Cultivator	FC10	3-Point Hitch Cat 1	135 lbs	48" - 57"	✓	✓	✓
	FC15		290 lbs	75"	✓	✓	✓
Food Plot Seeder	FPS48**	Drawbar Pull-Type	370 lbs	54"	✓	✓	✓
Grading Scrapers	GS0548	3-Point Hitch Cat 1	310 lbs	48"	✓	✓	✓
	GS0560		350 lbs	60"	✓	✓	✓
	GS1548		437 lbs	48"	✓	✓	✓
	GS1560		511 lbs	60"	X	✓	✓
	GS1572		594 lbs	72"	X	✓	✓

✓ - Available X - Unavailable

Grooming Mowers	FDR1648	3-Point Hitch Cat 1	486 lbs	48"	✓	✓	✓
	FDR1660		577 lbs	60"	✓	✓	✓
	FDR1672		619 lbs	72"	✓	✓	✓
Landscape Rakes	LR1660	3-Point Hitch Cat 1	241 lbs	60"	✓	✓	✓
	LR1672		270 lbs	60"	✓	✓	✓
	LR1684		291 lbs	72"	✓	✓	✓
	LR2684		330 lbs	84"	X	✓	✓
Moldboard Plows	MP10	3-Point Hitch Cat 1	294 lbs	14"	✓	✓	✓
	MP20		513 lbs	27.5"	X	✓	✓
Post Hole Diggers	PD10**	3-Point Hitch Cat 1	120 lbs	6", 9", 12"	✓	X	X
	PD15**		161 lbs		✓	✓	✓
	PD25**		186 lbs	6", 9", 12" 15", 18" & 24" Tree Auger	✓	✓	✓
	PD35**		233 lbs		X	✓	✓
	HD25**		235 lbs		✓	✓	✓
	HD35**	Loader Mount	268 lbs	✓	✓	✓	
Rear Blades	RB1560	3-Point Hitch Cat 1	248 lbs	48"	✓	✓	✓
	RB1572		269 lbs	60"	✓	✓	✓
	RB1584		289 lbs	72"	✓	✓	✓
	RB1660		283 lbs	60"	✓	✓	✓
	RB1672		297 lbs	72"	✓	✓	✓
	RB1684		319 lbs	84"	✓	✓	✓
Rotary Cutters	RCR1242	3-Point Hitch Cat 1	383 lbs	42"	✓	✓	✓
	RCR1248		400 lbs	48"	✓	✓	✓
	RCR1260		496 lbs	60"	✓	✓	✓
	RCR1272		568 lbs	72"	X	✓	✓
	RCR1548		424 lbs	48"	✓	✓	✓
Rotary Tillers	RTR1242	3-Point Hitch Cat 1	404 lbs	42"	✓	✓	✓
	RTR1250		435 lbs	50"	✓	✓	✓
	RTR1258		463 lbs	58"	✓	✓	✓
	RTR1266		493 lbs	66"	✓	✓	✓
	RTR1274		521 lbs	74"	X	✓	✓
	RGR1242		462 lbs	42"	✓	✓	✓
	RGR1250		497 lbs	50"	✓	✓	✓
	RGR1258		530 lbs	58"	✓	✓	✓
	RGR1266		567 lbs	66"	✓	✓	✓
	RTA1242		391 lbs	42"	✓	✓	✓
	RTA1250		421 lbs	50"	✓	✓	✓
	RTA1258		448 lbs	58"	✓	✓	✓
	RTA1266		476 lbs	66"	✓	✓	✓
	RTA1274		503 lbs	74"	X	✓	✓
	RGA1242		458 lbs	42"	✓	✓	✓
	RGA1250		493 lbs	50"	✓	✓	✓
	RGA1258		526 lbs	58"	✓	✓	✓
RGA1266	562 lbs	66"	✓	✓	✓		



Scarifiers	SF2566	3-Point Hitch Cat 1	208 lbs	60"	X	✓	✓
	SF2577		235 lbs	72"	X	✓	✓
Seedbed Rollers	SBR72-3PT	3-Point Hitch Cat 1	486 lbs	69"	✓	✓	✓
	SBR72-PT	Drawbar Pull-Type	577 lbs	69"	✓	✓	✓
Snowblowers (Rear Mount)	K54-22-06	3-Point Hitch Cat 1	460 lbs	54" ext. to 60"	✓	✓	✓
	K64-24-07		540 lbs	64" ext. to 69"	✓	✓	✓
Soil Pulverizer	SP2060	3-Point Hitch Cat 1	491 lbs	60"	✓	✓	✓
	SP2072		561 lbs	72"	✓	✓	✓
Spike-Tooth Harrow	STH1590	Drawbar Pull-Type	237 lbs	90"	✓	✓	✓
Spreaders	FSP500	3-Point Hitch Cat 1	119 lbs	37"	✓	✓	✓
	FSP700		128 lbs	44"	✓	✓	✓
	FSP1000		139 lbs	47"	✓	✓	✓
	PFS4000		196 lbs	46"	✓	✓	✓
	PFS5060		287 lbs	55"	✓	✓	✓
	PFS8010		403 lbs	75"	✓	✓	✓
	PTS500	Drawbar Pull-Type	165 lbs	37"	✓	✓	✓
	PTS700		176 lbs	44"	✓	✓	✓
Straw Crimper	CR2572	3-Point Hitch Cat 1	475 lbs	69	✓	✓	✓
Wood Chippers	WC1503	3-Point Hitch Cat 1	369 lbs	3	✓	X	X
	WC1504		450 lbs	4	✓	✓	✓
Ballast / Weight Box	WB10	3-Point Hitch Cat 1	Quick Hitch Compatible		✓	✓	✓
	B5320		Not Quick Hitch Compatible		✓	✓	✓
Rear Quick Hitch	QH16	3-Point Hitch Cat 1	68 lbs	N/A	✓	✓	✓
			70 lbs	N/A	✓	✓	✓

Proper ballast is required for all attachments, be sure to check with OM or DLR for proper usage.



Performance Matched LX Series *Attachments*

TRACTOR ATTACHMENTS	MODEL	MOUNTING TYPE	WEIGHT (LBS)	WORKING WIDTH	LX2620	LX3520	LX4020
Loader & Buckets	LA535 ¹	2-Lever Quick Attach	562 lbs	54", 60"	✓	X	X
	LA545 ¹	2-Lever Quick Attach	545 lbs	54", 60"	X	✓	✓
Backhoe & Buckets	BH77	4-Point Mount	1107 lbs	10", 12", 16" 24", 36"	✓	✓	✓
Angle Blade (Front Mount)	LX2960 ²	4-Point Front Hitch	430 lbs	60"	✓	✓	✓
	LX2972 ²		450 lbs	72"	✓	✓	✓
Broom (Front Mount)	LX2950 ³	4-Point Front Hitch & K-Connect PTO	475 lbs	60"	✓	✓	✓
Snowblowers (Front Mount)	LX2963 ³	4-Point Front Hitch & K-Connect PTO	390 lbs	63"	✓	✓	✓
	K51-22-7CF ³		505 lbs	51" HD	✓	✓	✓
	K64-22-7CF ³		535 lbs	64" HD	✓	✓	✓
K-Connect 4-Point Hitch	LX2940	Frame Mount	-	-	✓	X	X
	LX6971	Front Hitch	-	-	X	✓	✓
K-Connect PTO System	LX2942	K-Connect	-	-	✓	X	X
	LX6972 ⁴	K Connect PTO	-	-	X	✓	✓
Mid Mount Mowers	RCK60-30	Shaft Driven PTO	374 lbs	60"	✓	X	X
	RC72-30		463 lbs	72"	✓	X	X
	RCK60-40LX ⁴		390.2 lbs	60"	X	✓	✓
	RC72-40LX ⁴		474 lbs	72"	X	✓	✓
Grass Catcher	GCK60-30	Frame Mount	198 lbs	-	✓	X	X

1 - Requires Ballast

2 - Require 4-Point Front Hitch

3 - Requires Mid PTO Kit (LX3520/LX4020 models), 4-Point Front Hitch + K-Connect

4 - Requires Mid PTO kit



Performance Matched LX Series *Loader Attachments*

LOADER ATTACHMENTS	MODEL	MOUNTING TYPE	WEIGHT (LBS)	WORKING WIDTH	LX2620	LX3520	LX4020
Bale Spears	BS10 ¹	2-Lever Quick Attach	156 lbs	50"	✓	✓	✓
	BS20 ¹		196 lbs	50"	✓	✓	✓
Combo Bucket	CB1060 ¹	2-Lever Quick Attach	360 lbs	60"	✓	✓	✓
Grapple	SCG0660 ¹	2-Lever Quick Attach	247 lbs	54"	✓	✓	✓
Pallet Forks (Loader Mount)	PFL1242 ¹	2-Lever Quick Attach	228 lbs	42"	✓	✓	✓
Snow Pushers (Loader Mount)	SPL1060 ¹	2-Lever Quick Attach	346 lbs	60"	✓	✓	✓
	SPL1072 ¹		377 lbs	72"	✓	✓	✓
Angle Blades (Loader Mount)	STB1060 ¹	2-Lever Quick Attach	379 lbs	60"	✓	✓	✓
	STB1072 ¹		403 lbs	72"	✓	✓	✓

1- Requires Ballast

Notice:

The above identified implements are either manufactured by Kubota or have received an Engineering Release approving use by Kubota, and thus meet the performance matching requirements for the specified power machines for normally anticipated operating conditions. The specifications above are intended for general application; unusual soil, terrain, or severe operating conditions may not allow for the use of a specific implement under those operating conditions. The use of implements or attachments which are neither manufactured or approved by Kubota for use with the specified power machines and which do not meet the above specifications may result in malfunctions or damage to the power machine, damage to other property and/or injury to the operator or to others. Any such malfunctions or damages are not covered by the Kubota express limited warranty. The power machine, implement, and operating conditions need to be evaluated and monitored by the operator to be sure that the conditions are within a safe operating envelope for general use.

- Check with the tractor manual to verify for proper ballasting when using an implement or attachment on the machine.
- Additional kits (Rear Remotes, Third Function valves, etc.) may be required to use any of the above implements. Check with your local dealer to determine what is needed for proper fitment and operation.
- (***) This implement/attachment is approved for the base weight, but allows for additional ballasting (concrete blocks, seed, water tanks). Verify with the tractor manual and ensure proper ballasting before adding any additional weight to the implement/attachment.

Kubota Canada Ltd. notes that specifications and technical information are subject to changes without notice and Kubota does not represent or warrant that the information in this publication is completely accurate or current; however, Kubota used reasonable efforts to set forth and include accurate and up to date information in this publication. Kubota disclaims all representations and warranties, whether express or implied, including, but not limited to, warranties of merchantability and fitness for a particular purpose and Kubota shall not be liable for any damages, whether compensatory, direct, indirect, incidental, special, or consequential, arising out of or in connection with the use of this publication, or in the information therein.

