



TS9110 TURBO-SEEDERTM PLUS CART

Maximize efficiency by applying cover crops or dry fertilizer with the all-new TS9110 Turbo-Seeder PLUS Cart. The six-ton capacity tank uses stainless-steel metering augers to handle a wide range of seeding rates with greater accuracy and consistency. Designed to simplify filling, maintenance, and horsepower requirements, the Turbo-Seeder PLUS offers versatility for cover crop seeding and fertilizer application with a steerable, pull-behind cart.

Features & Benefits



HIGH-CAPACITY, SINGLE BIN DESIGN

With a large, 6-ton capacity tank, producers can cover more acres between fills. Product fill screens prevent foreign material from plugging tubes or damaging the metering systems.



SINGLE PWM HYDRAULIC BLOCK

Only one set of hydraulic couplers is required to control the product metering system. The hydraulics include built-in safety valves to protect the system and fan motor. A single hydraulic input reduces hydraulic requirements.



METERING SYSTEM

With one of the industry's most versatile and efficient metering systems, both the fan and drive are run by one hydraulic outlet. Seeds and fertilizer are metered with durable stainless steel augers and distributed through 8-12 air delivery tubes.



STEERABLE CART

The patented steering system permits tight turns and controlled traffic patterns with a 120" wheelbase for 30" rows. Hitch knuckles allow robust movements in difficult terrain. The cart includes a ladder and wide walkboard.

ADDITIONAL STANDARD FEATURES

- Configurable delivery tubes
- Simple, non-pressurized tank made of food grade stainless steel and poly
- Corrosion-resistant components
- The cart's hitch, hydraulics, and air hoses are designed to disconnect quickly from the leading implement, when desired
- 37-pin cable allows speed-compensated rate application with optional ISOBUS rate controller or simple Micro-Trak controller

TS9110 Turbo-Seeder PLUS Cart Rates by Speed 2 Rows per Meter Outlet (Splitters)								
	Turnips (39 lb. ft³)		Rye (45 lb. ft³)		MAP (64 lb. ft³)			
Speed	Min Rate	Max Rate	Min Rate	Max Rate	Min Rate	Max Rate		
15	10	122	12	141	17	200		
12	13	152	15	176	21	250		
10	15	183	18	211	25	300		
8	20	229	23	264	32	375		
6	26	305	30	352	42	500		

COMPATIBLE WITH

- VT1100 TURBO-MAX® 30'-40' MODELS
- HT1100 TERRA-MAX® 30'-40' MODELS

TS9110 Turbo-Seeder PLUS Cart	6-Ton Bin			
Recommended Use	Cover Crops or Fertilizer			
HT1100/ VT1100 Width	30'	35'	40'	
No. of Broadcasters	24	24	24	
Broadcaster Spacing	14.8"	17.3"	19.8"	

Specifications are subject to change without prior notification. Images may not depict current or standard production models.