



# F SERIES

## ALL-WEATHER RELIABILITY AND PERFORMANCE

The Kubota F Series has been redesigned to give you greater versatility and precision from summer to sub zero. This mighty mower sweeps, plows, clears snow and clips lawns, giving you the performance you need to get the job done right. The dealer installed cabin offers added comfort while the Tier 4 engine is powerful and fuel-efficient.



SNOWBLOWER



SNOW BLADE



SWEEPER

## ATTACHMENT SPECS

		Description	L2163	F6610
SWEEPER	Hitch	Hitch Type	Quick Hitch/PTO Shaft	Quick Hitch/PTO Shaft
		Height	25 3/4"	25"
	General	Overall Width	63 1/2"	71"
		Working Width	56 1/2"	65 1/2"
		Maximum Pivot Angle (Degrees)	20 Degrees	25 Degrees
		Working Width @ Max Angle	51 1/2"	59 1/2"
		Brush Type	Standard: 100% Poly	Standard: 100% Poly
		Brush Speed Range	–	258 RPM @ 3000 RPM
		Main Housing Thickness	–	14 GA
		Side Housing Thickness	–	11 GA
Optional Equipment	Approx. Shipping Weight (lbs)	444 lbs	550 lbs	
	Dust Deflector	Yes	Yes	
	50/50 Poly Brush	No	Yes	

		Description	B2763	F6010	F7210
SNOW BLADE	Hitch	Hitch Type	Quick Hitch	4 Point Hitch	4 Point Hitch
		Blade Type	Straight	Straight	Straight
	General	Angle Type	Manual (Optional Hydraulic)	Hydraulic	Hydraulic w/ cross over relief
		Maximum Width (Length)	60"	60"	72"
		Maximum Pivot Angle (Degrees)	30 degrees	30 degrees	30 degrees
		Cutting Width @ Max Degrees Angle	52 1/2"	52 1/2"	62"
		Cutting Edge	Reversible and Replaceable	Reversible and Replaceable	Reversible and Replaceable
		Skid Shoes	Yes	Yes	Yes
		Moldboard Height	21"	22 1/2"	22 1/2"
		Moldboard Thickness	3 GA	3 GA	3 GA
Optional Equipment	Base Equipment Weight	285 lbs	445 lbs	465 lbs	
	Poly Cutting Edge	Yes	Yes	Yes	
	Cross Over Relief	Yes	Yes	–	

		Description	F5220	F5720	F5110	F5710
SNOWBLOWER	General	Hitch Type (Front /Rear Mount)	Quick Hitch	Quick Hitch	4 Point Hitch	4 Point Hitch
		Blower Type	2 Stages	2 Stages	2 Stages	2 Stages
		Approx. Shipping Weight	498 lbs	532 lbs	498 lbs	532 lbs
		Overall Width	51"	57"	51"	57"
		Working Width	51"	57"	51"	57"
		Working Height	24"	24"	24"	24"
		Overall Length (w/hitch)	30 3/4"	30 3/4"	30 3/4"	30 3/4"
	Impeller	Impeller Diameter	17 3/4"	17 3/4"	17 3/4"	17 3/4"
		Number of Impeller Blades	4	4	4	4
	Auger	Auger Drive	Reduction Box	Reduction Box	Reduction Box	Reduction Box
		Auger Diameter	13 3/4"	13 3/4"	13 3/4"	13 3/4"
	Housing	Housing Thickness	12 GA	12 GA	12 GA	12 GA
		Side Panel Thickness	12 GA	12 GA	12 GA	12 GA
	Chute	Chute Position	Right	Right	Right	Right
		Rotation of Chute	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Deflector Adjustment		Manual (optional hydraulic or electric)	Manual (optional hydraulic or electric)	Manual (Optional Hydraulic)	Manual (Optional Hydraulic)	
Cutting Edge	Replaceable	Yes	Yes	Yes	Yes	
Skid Shoes	Replaceable and Adjustable	Yes	Yes	Yes	Yes	
Optional Equipment	Snowblower Extensions	Yes	Yes	Yes	Yes	

**AVAILABLE SERIES MODELS:**  
F2690  
F3710